



L530020ESCPL

20W/39W/70W Accent Fixture

A low wattage metal halide track fixture utilizing 20W, 39W or 70W T4.5 ceramic metal halide capsules providing compact size and adjustable optics. Ideal for accent and wall wash lighting applications. This fixture provides an adjustable beam of light with high efficiency, good color rendering and long life. Injection molded lamp housing has an integral segmented reflector and adjustable light center optics allowing the light beam to be adjusted from spot to flood. Lamp housing adjusts ±90° providing full aiming adjustment and eliminates the "dead zone" found with other fixture designs. 70 Watt units have lockable aiming achieved with a 9/64" Allen wrench (not supplied).


INTEGRAL ELECTRONIC BALLAST

HID


ADJUSTABLE BEAM

ACCEPTS FILTERS

T4.5 CERAMIC METAL HALIDE



L5300 (20 & 39W)
L1= 7 1/4" [184mm]
L = 5 1/4" [133mm]
W = 5 1/4" [133mm]
Max Ext= 9 1/2" [241mm]



L530070
L1= 8" [203mm]
L = 5 1/4" [133mm]
W = 5 1/4" [133mm]
Max Ext= 10 1/2" [267mm]



L530070ESCPLWW

39W/70W Wall Wash Fixture

A low wattage metal halide track fixture utilizing 39W or 70W T4.5 ceramic metal halide capsules optimized for wall wash applications. This fixture provides high efficiency, good color rendering and long life. Injection molded lamp housing has an integral segmented reflector and a fixed lens for horizontal wall washing. Lamp housing adjusts ±90° providing full aiming adjustment and eliminates the "dead zone" found with other fixture designs. 70 Watt units have lockable aiming achieved with a 9/64" Allen wrench (not supplied).


INTEGRAL ELECTRONIC BALLAST

HID


ADJUSTABLE BEAM

ACCEPTS FILTERS

T4.5 CERAMIC METAL HALIDE



L5300 (20 & 39W)
L1= 7 1/4" [184mm]
L = 5 1/4" [133mm]
W = 5 1/4" [133mm]
Max Ext= 9 1/2" [241mm]



L530070
L1= 8" [203mm]
L = 5 1/4" [133mm]
W = 5 1/4" [133mm]
Max Ext= 10 1/2" [267mm]



L530039ESCPLSS

39W/70W Super Spot Fixture


A low wattage metal halide track fixture utilizing 39W or 70W T4.5 ceramic metal halide capsules for narrow beam accent lighting. This fixture provides high efficiency, good color rendering and long life. Injection molded lamp housing has an integral segmented narrow beam reflector. Lamp housing adjusts ±90° providing full aiming adjustment and eliminates the "dead zone" found with other fixture designs. 70 Watt units have lockable aiming achieved with a 9/64" Allen wrench (not supplied).

INTEGRAL ELECTRONIC BALLAST


HID

ACCEPTS FILTERS

T4.5 CERAMIC METAL HALIDE



L5300 (20 & 39W)
L1= 7 1/4" [184mm]
L = 5 1/4" [133mm]
W = 5 1/4" [133mm]
Max Ext= 9 1/2" [241mm]



L530070
L1= 8" [203mm]
L = 5 1/4" [133mm]
W = 5 1/4" [133mm]
Max Ext= 10 1/2" [267mm]

| Track System | Lampholder | Ballast | Reflector | Finish | Optics | Lamp | Style | Voltage | Accessories |
|---|---|--|--|--|---|-----------------|-------------------------------------|---|--|
| | 5300 | | | | | L | | | |
| L=Halo Power-Trac LA=Halo Architectural Linear LF=Halo Architectural Flexible Track | | 20E = 20 Watt Electronic Ballast 39E = 39 Watt Electronic Ballast 70E = 70 Watt Electronic Ballast | SC = Specular Clear Reflector Finish CG= Commercial Gold Reflector Finish | P=White (Land LA only) MB=Black (Land LA only) SL=Silver | Blank=Accent WW=Wall Wash SS=Super Spot | L=Lamp Included | (Blank)=Open Back CB=Closed Back | Blank=120V 277=277V (for Halo Architectural Only) | L200 Series=Color Filters or Beam Modifying Lenses |
| | 5300= Minilume Adjustable Beam Ceramic Metal Halide Track Fixture | | | | | | Open Back | Closed Back | |
| | | | | | | | | | |