

DESCRIPTION

Miniature cylindrical recessed housing and round trimless fixture with regressed black baffle. Includes enclosure with integral transformer and wiring compartment.

For new construction or remodel applications. Insulation must be kept 3" from all sides and at least 1" above the housing.

SPECIFICATION FEATURES

A...Housing

All aluminum construction with 18" of flexible conduit attached to a cylindrical transformer/wiring enclosure. Perforated metal plasterframe adjusts for trimless mounting in 1/2" - 3/4" drywall.

B...Trimless Fixture:

3.2" o.d. round trimless fixture with regressed black baffle. Perforated metal plasterframe allows ceiling compound to be applied directly to the edge of the fixture. Finished in white, black, industrial silver, stainless steel (painted), and primer for matching to existing ceiling color.

C...System Protection:

Thermal protection inside housing. Vent holes in housing provide cooler operation. All aluminum construction provides overall reduced temperatures.

D...Electrical

Electronic or magnetic transformer housed in a separate metal enclosure. Enclosure includes a separated wiring compartment and entry for primary leads.

Catalog #	Туре
Project	
Comments	Date
Prepared by	

E ...Lamp

12V MR16 37 watts max. (not included) "POSI-GRIP" bi-pin lamp socket for firm, mechanical lamp connection. Can accept up to two (2) optical accessories.

Ceiling Cut-Out: 3.50" dia.



LYNX

LX3001TR Miniature Round Trimless Fixture w/ Regress Black Baffle

Cylindrical Housing Transformer/Wiring Enclosure

12V MR16 37 watts max.



ORDERING INFORMATION

LX3001TR			
Fixture LX3001TR Regressed Black Baffle Lynx Trimless Fixture with Housing & Transformer Enclosure	Finish WH = White BK = Black S = Industrial Silver SS = Stainless Steel (painted) PM = Primer	Transformer ELC = Electronic MAG = Magnetic	Voltage 120 = 120 volts 277 = 277 volts

