NEO-RAY™



77

DIRECT

- Staggered light strips with precisely crafted louvers and diffusers create continious bands of even illumination.
- T5 and T8 lamping.
- Direct light distribution.
- · Staggered lamps.
- Die formed steel housing, nominal illuminated sections 4', 6' and 8'.
- Runs are field adjustable.
- 90 degree mitered corners.
- Extruded aluminum ceiling trims with 3/8ths soft lit edge.
- · Selection of diffuser options.

8-23/32" [22/mm]

+ + +

8"
[203mm]

7-11/16" [195mm]
9-1/4" [225mm]
CELING OPENING

9-11-16" [247mm]

Construction

20-gauge steel housing.

Shielding

Parabolic or bold baffles.

Electrical

120, 277, 347 or Universal Voltage electronic ballast. Fixtures and electrical components certified to UL and CUL standards.

Finish

Durable, low gloss, white, powder coated acrylic finish.

Staggered Lamps

T8=3", T5=6"

Mounting

Recessed.

ORDERING INFORMATION:

Sample number: 77-1T8-36-2EB-SI-S72

Series

77

Number of Lamps (not included)

1=1 Lamp **2**=2 Lam

Lamp Type (Length)

T8 T5 T5HO
* Staggered lighting strips ²

Run Length

Overall Nominal Run Length_ft. [Any run length]

Voltage

1=120V **2**=277V **3**=347V **U**=Universal

Ballast

Switching

SI=Single Switching DU=Dual Switching

Emergency

EM=Emergency Pack (Consult Factory)

Fusing

GLR GMF

Shielding

\$58=KSH-12 Clear Acrylic Prismatic Lens with Mullion

\$72=White Bold Baffle

\$79=Semi-Specular Aluminum Parabolic Baffle

1 Due to various constraints, some options may not be combined with others. 2 T8 - 3" Staggered $\,$

T5 - 6" Staggered

Note: Fixture must be installed before ceiling.

SHIELDING OPTIONS







S79 Parabolic Baffle

STAGGERED LAMPS





STANDARD LUMINAIRE LENGTHS

48"	
72"	
96"	

Runs are comprised of above standard sections