



DESCRIPTION:

ELECTRICAL:

CONSTRUCTION:

16 gauge CRS.

Type:



Project:

SYSTEM PROTECTION:

Steel Safety

Cable

c(UL)us

Thermal protection provided to guard against overheating and misuse of insulation over and around fixture.

- WASHES VERTICAL SURFACE WITH EVENLY DIFFUSED LIGHT
- DESIGNED TO BE INSTALLED WITHIN 18" -24" OF VERTICAL SURFACE

Ball Detent

Retainers

9.88" \bigcirc Internal rotation ring with locking (\mathbf{I}) adjustment. Provides 360° rotation and secures original trim position after relamping or 17.50 maintenance. 4.13 INCLUDES LINEAR SPREAD LENS (0)7.50" \bigcirc 4 14 Mudding Ring adjusts in

plaster frame to accommodate 1/2", 5/8", 3/4" & 1" ceilings.

		Voltage / Wattage
Quiet Ceiling Series Lensed Wallwasher Trimless Fixture	White	12V / 50W Max.
with Insulated Ceiling Housing w/ Magnetic Transformer	Black	
	Silver	
	Stainless Steel	
	Primer	
-		with Insulated Ceiling Housing w/ Magnetic Transformer Silver Stainless Steel

For 277 volt transformer add "277" to end of item #. For Chicago Plenum add "CP" to end of item #.

STATE OF WASHINGTON AIRTIGHT APPROVED

RSA LIGHTING

REV 062904 RSA LIGHTING 9660 - 9700 TOPANGA CANYON BLVD. CHATSWORTH CA. 91311 TOLL FREE: 800-356-3030 • 818-349-3030 • FAX: 818-349-3031 • www.rsalighting.com ©2004 RSA Lighting All Rights Reserved • Specifications subject to change without notice. QC25