DESCRIPTION

230 Shallow Bowl Surface Luminaire features direct/indirect illumination with a trim ring.

Catalog #	Туре
Project	
Comments	Date
Prepared by	

SPECIFICATION FEATURES

Material

Cold rolled steel trim and mounting pan with a matte white acrylic diffuser.

Finish (Trim and Mounting Pan)

Standard: Matte White (MW). Premium: Satin Chrome (SC), Polished Chrome (PC), Satin Brass (SB), Polished Brass (PB), Oxidized Brass (OBRS), Satin Nickel (SN), Polished Nickel (PN), Polished Copper (PCP), Satin Copper (SCP), Lacquered Satin Nickel (SNL), Lacquered Satin Chrome (SCL), or Custom Color (CC).

Optics

Refer to

www.shaperlighting.com for complete photometrics.

Ballast

Integral electronic HPF, multi-volt 120/277V (347V Canada), thermally protected with end-oflife circuitry to accommodate the specified lamp wattage.

Lamp/Socket

16": Two (2) 13W (2GX7) 4-pin low wattage CFL lamps or two (2) 26W (G24q-3) 4-pin quad CFL lamps or two (2) 60W A-19 lamps.

24": Two (2) 26W, 32W (GX24q-3) 4-pin CFL triple lamps or two (2) 75W A-19 lamps.

30": Two (2) 26W, 32W (GX24q-3) or 42W (GX24q-4) 4-pin triple CFL lamps, or two (2) 75W A-19 lamps. CFL socket injection molded plastic. INC socket fired ceramic rated for 660W-250V. Lamps furnished by others.

Installation

Supplied with a universal circular strap for a standard 4" J-box or plaster ring. Diffuser and trim are key slotted for ease of installation. Diffuser and trim are key slotted ror

Options

Hand Painted Faux Alabaster Diffuser (FD), Hand Painted Faux Linen Diffuser (LND), Accent Balls (ACB), Damp Location (DL): All Painted Finishes, Lacquered

Satin Nickel (SNL) and Lacquered Stain Chrome (SCL) only, Diamond Cut-Out (DC) - Contact the factory for more patterns, CFL Dimming Ballast (26, 32, 42W only) - Contact the factory for ballast options (DM), Modified Emergency Remote -Refer to spec sheet for drawing (MEM). MRI Applications (INC only) - Contact Factory. Energy Star Rating - Consult Factory.

Labels

U.L. and C.U.L. approved for indoor and damp location. See options for damp location finishing requirements.

Modifications

Shaper's skilled craftspeople with their depth of experience offer the designer the flexibility to modify standard surface luminaires for project specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors, or decorative detailing.




230 SERIES

Shaper shaperlighting.com


Surface Luminaire Shallow Bowl



ORDERING INFORMATION







FNFRGY STAR


Shaper now offers a wide variety of fixtures that can be provided with an Energy Star Rating.




MAGNETIC RESONANCE IMAGING (MRI)

Lighting fixtures for MRI facilities are specialized and unique, requiring non-ferrous construction. Fluorescent fixtures cannot be used due to the ferrous parts in ballasts and lampholders. Modified incandescent fixtures meet the requirements

Refer to the Icon Legend Link on shaperlighting.com DIMENSIONS 230 SERIES SURFACE LUMINAIRE



230 TRIM OPTIONS



COMPANION PRODUCTS



