

GENERAL

Model No. SS______#14 gauge, type 304 stainless steel scullery sink. Compartments 14" deep. Square corner welded construction. Full length 8" high backsplash with 45° sloped top. 1-1/2" wide sloping top channel rims. Integral drainboard/s, sink compartments pitched to drain. Exposed surfaces polished to a satin finish.

Sink, supported on (4) LK251 stainless steel, 1-5/8" O.D. tubular legs, #16 gauge wall thickness. Adjustable bullet shaped feet.

Shaded areas are models carried in stock with standard faucet location.

Non-shaded areas with specified dimensions are standard models which must be made to order – standard faucet location unless otherwise specified.

Last item in each group is custom. Fill in dimensions. Standard faucet location unless otherwise specified. Drainboards over 25-1/2" furnished with one tubular leg.

Drainboards over 48" furnished with two tubular legs.

SPECIFIED FITTINGS:

SUPPLY:

DRAIN:

FURNISHED WITH:


LK251. (Four) Stainless steel tubular legs, 1-5/8" O.D., #16 gauge. Adjustable bullet feet.

ALL DIMENSIONS IN INCHES.

SEE OTHER SIDE FOR DIMENSIONS IN MILLIMETERS.


-(CHECK MODEL SPECIFIED):

	NO DRAINBOARD				
	Model Number	Dimensions			
Y		Α	В		
	SS8124	27	24		
	SS8130	33	30		
	SS8136	39	36		
	• SSC8100				




RIGHT DRAINBOARD

Model	Dimensions		
Number	Α	В	C
SS8124R	491/2	24	24
SS8130R	551/2	30	24
SS8136R	611/2	36	24
• SSC8100R			




LEFT DRAINBOARD

Model	Dimensions		
Number		В	C
SS8124L	491/2	24	24
SS8130L	551/2	30	24
SS8136L	611/2	36	24
• SSC8100L			




RIGHT & LEFT DRAINBOARD

	Model	Dimensions		
_	Number		В	C
	SS8124LR	72	24	24
	SS8130LR	78	30	24
	SS8136LR	84	36	24
	• SSC8100LR			



INDICATE NUMBER OF FAUCET HOLES WHEN PLACING ORDER. (NON-STANDARD FAUCET AND OVERFLOW DRILLING LOCATIONS ARE AVAILABLE. SPECIFY ON DRAWING AT RIGHT.)



(Rev. 6/06)

Sturdibilt® Scullery Sink Square Corner Single Compartment



GENERAL

Model No. SS______#14 gauge, type 304 stainless steel scullery sink. Compartments 356mm deep. Square corner welded construction. Full length 203mm high backsplash with 45° sloped top. 38mm wide sloping top channel rims. Integral drainboard/s, sink compartments pitched to drain. Exposed surfaces polished to a satin finish.

Sink, supported on (4) LK251 stainless steel, 41mm O.D. tubular legs, #16 gauge wall thickness. Adjustable bullet shaped feet.

Shaded areas are models carried in stock with standard faucet location.

Non-shaded areas with specified dimensions are standard models which must be made to order – standard faucet location unless otherwise specified.

Last item in each group is custom.
Fill in dimensions. Standard faucet location unless otherwise specified.
Drainboards over 648mm furnished with one tubular leg.

Drainboards over 1,219mm furnished with two tubular legs.

SPECIFIED FITTINGS:

SUPPLY:

DRAIN:

FURNISHED WITH:


LK251. (Four) Stainless steel tubular legs, 41mm O.D., #16 gauge. Adjustable bullet feet.

ALL DIMENSIONS IN MILLIMETERS. SEE OTHER SIDE FOR DIMENSIONS IN INCHES.

-(CHECK MODEL SPECIFIED):


NO DRAINBOARD

	Model	Dimensions		
<u> </u>	Number	Α	В	
	SS8124	686	610	
	SS8130	838	762	
	SS8136	991	914	
	• SSC8100			




RIGHT DRAINBOARD

	Model	Dimensions		
_	Number		В	C
	SS8124R	1257	610	610
	SS8130R	1410	762	610
	SS8136R	1562	914	610
	• SSC8100R			




LEFT DRAINBOARD

Model	Di	Dimensions		
Number		В	C	
SS8124L	1257	610	610	
SS8130L	1410	762	610	
SS8136L	1562	914	610	
• SSC8100L				



RIGHT & LEFT DRAINBOARD

		Model	Dimensions		
		Number	Α	В	C
		SS8124LR	1829	610	610
		SS8130LR	1981	762	610
		SS8136LR	2134	914	610
		• SSC8100LR			



INDICATE NUMBER OF FAUCET HOLES WHEN PLACING ORDER. (NON-STANDARD FAUCET AND OVERFLOW DRILLING LOCATIONS ARE AVAILABLE. SPECIFY ON DRAWING AT RIGHT.)

