

Specifications — WPC 150 Series, WPB 170 Series

General

Temperature/humidity Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing
Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing

Mounting

NOTE *Audio and video signals are passed through without processing.*

Furniture mount Yes, furniture/wall mountable with standard electrical wall boxes
EU models Mountable into standard 40 mm or 50 mm deep European junction boxes
MK models Mounts to a standard 47 mm deep MK electric type British standard wall box

Enclosure type Metal

Dimensions

WPC 150 EU

Faceplate 3.2" H x 3.2" W x 0.1" D (1-gang EU)
(8.1 cm H x 8.1 cm W x 0.3 cm D)

Device 1.3" H x 1.9" W x 1.1" D
(3.3 cm H x 4.8 cm W x 2.8 cm D)
(Overall rear dimensions, including connectors. Allow at least 1.58" [4 cm] depth in the wall or furniture for device and cable clearance.)

WPC 150 MK

Faceplate 3.4" H x 3.4" W x 0.1" D
(8.5 cm H x 8.5 cm W x 0.3 cm D)
(1-gang MK electric type British Standard wall box frame size)

Device 1.3" H x 1.9" W x 1.1" D
(3.3 cm H x 4.8 cm W x 2.8 cm D)
(Overall rear dimensions, including connectors. Allow at least 1.58" [4 cm] depth in the wall or furniture for device and cable clearance.)

WPC 170 EU

Faceplate 3.2" H x 3.2" W x 0.1" D (1-gang EU)
(8.1 cm H x 8.1 cm W x 0.3 cm D)

Device 1.3" H x 1.9" W x 1.1" D
(3.3 cm H x 4.8 cm W x 2.8 cm D)
(Overall rear dimensions, including connectors. Allow at least 1.58" [4 cm] depth in the wall or furniture for device and cable clearance.)

WPC 170 MK

Faceplate 3.4" H x 3.4" W x 0.1" D
(8.5 cm H x 8.5 cm W x 0.3 cm D)
(1-gang MK electric type British Standard wall box frame size)

Device 1.3" H x 1.9" W x 1.1" D
(3.3 cm H x 4.8 cm W x 2.8 cm D)
(Overall rear dimensions, including connectors. Allow at least 1.58" [4 cm] depth in the wall or furniture for device and cable clearance.)

Product weight

WPC 150 EU 0.2 lb (0.1 kg)
WPC 150 MK 0.2 lb (0.1 kg)
WPC 170 EU 0.2 lb (0.1 kg)
WPC 170 MK 0.2 lb (0.1 kg)

Shipping weight 1 lb (1 kg)

Vibration ISTA 1A in carton (International Safe Transit Association)

Regulatory compliance

Environmental Complies with the appropriate requirements of RoHS, WEEE

MTBF 30,000 hours

Warranty 3 years parts and labor

NOTE *Specifications are subject to change without notice.*

7.6-120908-D1