HALO®



L1901 Live End Connector Housing

To start a run. L901 or L941 required to complete installation.

Finish: White (P)



L1904 L Connector Housing

To connect two track sections at 90° angle. L904 or L943 required to complete

installation. Finish: White (P)



L1906 X Connector Housing

To connect four track sections into a cross configuration. L906 or L946 required to complete installation.

Finish: White (P)



L932 Cross Tee Adapter Clip

Use in track housing groove to assemble 15/16" cross tee. For use with Chicago Metallic 200 System, National Rolling Mills ML System, Donn Corporation DX System.



L935 **Recessed Housing** Hanger

Use to suspend Recessed Power-Trac



L938 Cross Tee End

For use when cross tee is cut. Pop rivet to cross tee and insert into L932, L934 cross tee adapter.



Mini Connector Kit

Contains two joiner strips and hardware. L949.



L1903 Straight Connector and Housing

Connect two Miniature Power-Trac sections end to-end.

Finish: White (P)

L1943 To connect two Halo-2 Power-Trac

sections end-to-end. Finish: White (P)

L1905 T Connector Housing

To connect three track sections into a T configuration. L905, L945R or L945L required to

complete installation.

Finish: White (P)



Housing End Cap

For symmetry of installation at end of run.

Finish: White (P)



Cross Tee Adapter Clip

Use in track housing groove to assemble 9/16" cross tee. For use with Chicago Metallic Tempra 4000 System, National Rolling Mills SLK System, Donn Corporation Centricitee System.



Raceway Cover

Cover allows Recessed Housing to be used as Raceway to carry up to 6 #12 AWG wires. 4' lengths. One cover is required for each raceway channel.



L939 Lathing Tab

Use to suspend Recessed Power-Trac Housing to carrying channel (10" long).

For recessed channel when using L908 or