

CP-A100+FXDUO-77 Bundle*

HITACHI
Inspire the Next



CP-A100 Key Features

- 2,500 Lumens
- Native XGA Resolution
- 12.8 lbs.
- Instant On/Off
- Lamp door on top
- 7W speaker output
- 28 dB (Whisper Mode)
- Component / Composite / S-Video Inputs
- Network Control, Maintenance, & Security
- Rear Mounted High Efficiency Filter
- 2 RGB inputs / 1 RGB output
- Approx 3,000 hours. (whisper mode)
- Security Bar & Transition Detector
- Ultra Short Throw Distance



FXDUO-77 Key Features

- Control using multi-touch hand gestures
- 2 students can work on the board at the same time
- Electronic-free surface can work with damage
- Use finger, any object, or electronic pen (optional)
- includes StarBoard Software with free updates



A100WALLARM

- Small installation footprint
- No wires through ceiling



RM Easiteach

- Includes all Easiteach curriculum toolbars
- Build and deliver dynamic interactive lessons
- Available in PC or Mac version



An Interactive Learning Tool Like No Other

The CP-A100+FXDUO-77 Bundle is a complete interactive learning system that maintains simplicity while utilizing the latest in display and educational technology. This unique package combines the ultra short throw CP-A100 3LCD projector for superb image quality with the StarBoard FXDUO interactive whiteboard to create a revolutionary learning environment. Also included is RM Easiteach software, a dynamic set of educational tools and curriculum resources that make the transition to interactive teaching seamless.

"Awarded *Scholastic Administrator's*
Best in Tech for Interactive Classrooms"



1 Ultra Short Throw LCD Projector

Model No.	CP-A100
Liquid Crystal Panel Structure	0.63" Polysilicon Active-matrix TFT x 3
Number of Pixels	786,432 Pixels
Resolution	540 TV lines
	1024 dots x 768 lines
Colors	16.7 million colors
Aspect Ratio	Native 4:3 / 16:9 compatible
Lens	Fixed
Throw Ratio (distance : width)	0.37
Lamp	220W UHB
Brightness	2,500 lumens
Expected Lamp Life	Approximately 2,000 hours (normal) 3,000 hours (whisper)
Contrast Ratio	500 : 1
Speaker Output	7W (1 speaker)
Power Supply	AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Consumption	340W
Operating Temperature	5°C - 35°C (41°F - 95°F)
Input Signals	RGB, VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC13", MAC16"
	Composite Video, NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N
	Component Video, 480i, 576i, 480p, 720p, 1080i
Acoustic Noise Level	33 dB (28 dB in whisper mode)
H-Sync	15 kHz - 106 kHz
V-Sync	50 kHz - 120 kHz
Vertical Keystone	+ / - 5°
Approvals	UL60950 / C-UL, FCC Part15, Class B, EN60950
RGB Input	Analog RGB, 15-pin D-sub connector x 2
RGB Output	RGB, 15-pin D-sub connector x 1
Video Input	S-Video, Mini DIN 4-pin connector x 1
	Composite Video, RCA jack x 1
	Component Video, RCA jack x 3
Audio	Input, Stereo mini jack x 2, RCA (L/R) x 1 pair
	Output, Stereo mini jack x 1
Ethernet	RJ-45 port / 100 base-T
Control Terminals	9-pin D-sub connector x 1 (RS-232 control)
Other	USB connector (USB mouse) x 1
Dimensions (W x H x D)	15.6" x 14.0" x 5.2"
Weight	12.8 lbs.
Additional Features	Kensington Slot, MyMemory / MyScreen / MyButtons, Digital Gamma Correction, Whiteboard/Blackboard Mode, Input Source Naming
Supplied Accessories	Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual, Security Label CPA100LAMP (DT00891)
Lamp	
Remote Control	HLO2482
Filter	QD60122

Printed 06.09
All specifications are subject to change without notice

2 Interactive Whiteboard

Model No.	FXDUO-77
Input Methods	Image sensor and infrared method
Interface to Computer	USB
Effective Screen Size	77 Inches (62" (W) x 47" (H))
Sampling Rate	Approximately 100 points/sec
Resolution	Approximately 500 lpi
Accuracy	Approximately ±1.5 mm
Board/Surface Material	Particle wood (core), cured resin (surface)
Operating Specification	41 - 95 Fahrenheit, 5 - 35 Celsius, 20 - 80% Humidity without condensation
Dimensions (in)	68"(W) x 53"(H) x 3"(D)
Weight (main unit)	52.9 lbs
Packing dimension (in)	73"(W) x 61"(H) x 5"(D) (FXDUO only)
Packing weight	77 lbs (FXDUO only)
Certificates	FCC, UL, CE, VCCI
Warranty	Five-year limited equipment warranty upon registration. See hardware manual for details.

3 Wall Arm

Model No.	A100WALLARM
Load capacity	50 lbs
Tilt	±20 degree
Roll	±10 degree
Swivel	±15 degree
Throw distance	4" - 16"
Height Adjustment	2.5" (fine tune)
Left/Right portion adjust	1.75" (fine tune)
Cable management	Yes
Dimensions (in)	7.3"(W) x 14.5"(H) x 26.5"(D)

*Bundle Part Number:

CPA100FXDUOARM-P (Windows)
CPA100FXDUOARM-M (Mac)

Hitachi Software Engineering America, Ltd.
(Interactive Media Solutions)

Hitachi Home Electronics America, Inc.
(Business Group)

For Product and Sales Info:
Tel: 800-225-1741
Fax: 619-482-5784
starboard@hitachi-soft.com
www.hitachi-soft.com