



Catalog Number	Finish	Lamp	Wattage	Color Temp	Voltage
DSR01W	White	LED	4W	3000K	120-240V
DSR01SA	Satin Aluminum	LED	4W	3000K	120-240V

### Features

- Heat Sink/Driver Housing:** Die cast aluminum.
- Lens:** Injection molded acrylic clear, developed for optimum optical output.
- Face Plate:** Die cast aluminum.
- Switch Box Mounting Plate:** 18ga. C.R.S. zinc plated, for mounting to a 3 1/2" deep switch box. (Not shown)

### Electrical

**LED:** (1) 4W 3000K white LED. Average expected life, under normal operating conditions is 50,000 hours with lumen maintenance of 70% of original light output.

- Driver:** Class 2 power supply.  
**Voltage:** 120V  
**Output Wattage:** 5 W  
**Input Current (max.):** 100 mA  
**Frequency:** 50/60 Hz  
**Output Voltage (VDC):** 12 V  
**Constant Current:** 500 mA

### Finish

Satin aluminum with protective clearcoat.  
 Matte white powder coat.

### Labels

cULus Listed. Suitable for Dry Locations.  
 Wall mount only.

Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 www.lightolier.com © 2008 Philips Group • B1208