



Catalog Number	Finish	Lamp	Wattage	Color Temp	Voltage
DSS01W	White	LED	4W	3000K	120-240V
DSS01SA	Satin Aluminum	LED	4W	3000K	120-240V

Features

- Heat Sink/Driver Housing:** Die cast aluminum.
- Lens:** Injection molded acrylic clear, developed for optimum optical output.
- Face Plate:** Die cast aluminum.
- Switch Box Mounting Plate:** 18ga. C.R.S. zinc plated, for mounting to a 3 1/2" deep switch box.

Electrical

LED: (1) 4W 3000K white LED. Average expected life, under normal operating conditions is 50,000 hours with lumen maintenance of 70% of original light output.

Driver: Class 2 power supply.
Voltage: 120V
Output Wattage: 5 W
Input Current (max.): 100 mA
Frequency: 50/60 Hz
Output Voltage (VDC): 12 V
Constant Current: 500 mA

Finish

Satin aluminum with protective clear coat.
 Matte white powder coat.

Labels

cULus Listed. Suitable for Dry Locations.
 Wall mount only.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • B1208