



Ceiling Cutout: 9 1/4" (235 mm) Dia.

Reflector Trim	Frame-In Kit
<b>8023 CCLW</b> Comfort Clear™, White Flange <b>8023 CCLP</b> Comfort Clear™, Polished Flange <b>8023 CCL</b> Comfort Clear™, Molded Trim Ring <b>8023</b> <input type="checkbox"/> Add suffix. See options for other finishes	<b>S8142VU</b> 8" aperture, 1 lamp 26/32/42W Triple Tube CFL (120/277V) 4-Pin (Amalgam) <b>Dimming Options:</b> <b>S8142V</b> <input type="checkbox"/> <b>CU3</b> Lightolier PowerSpec 3% Dimming (120/277V) <b>J2LD3</b> Lutron 3% Dimming (277V) <b>J1MX</b> Mark 10 Dimming (120V) Other dimming product available, please consult factory <b>J1LD3</b> Lutron 3% Dimming (120V) <b>JUM7</b> Mark 7 Dimming (120/277V) <b>J2MX</b> Mark 10 Dimming (277V)
	Remodeler Frame-In Kits
	<b>8142VURM</b> 8" aperture, 1 lamp 26/32/42W Triple Tube CFL (120/277V) 4-Pin (Amalgam)

## Features

- Reflector:** 16 ga. Alzak® aluminum, 50° visual cutoff to lamp and lamp image, medium distribution. Comfort Clear™ low iridescence finish. Self-flanged or flangeless with molded white trim ring (field paintable).
- Socket Cup:** Snaps onto reflector neck to assure consistently correct optical alignment without tools.
- Retaining Springs:** Precision-tooled steel friction springs secure reflector to mounting frame for quick, tool-less installation.
- Mounting Brackets:** 16 ga. steel. Adjust from inside of fixture. Use 3/4" or 1 1/2" lathing channel, 1/2" EMT, or optional mounting bars.
- Ballast/J-Box:** Outboard mounted to reduce heat transfer and maintain lamp efficacy and life. Service from below without tools.

## Electrical

**Note:** For ballast electrical data and latest lamp/ballast compatibility refer to "Ballast" specification sheet for complete electrical data.

UL Listed for through branch circuit wiring with max of (8) No 12 AWG, 90 degree C supply conductors.

## Options and Accessories

<b>Comfort Clear™ Finishes<sup>1</sup></b>		<b>Other Finishes</b>	
Diffuse	<b>CCD</b>	White	<b>WH</b>
Champagne Bronze	<b>CCZ</b>	Specular Clear	<b>CL</b>

<sup>1</sup>Specify desired flange

**W** White, **P** Polished

Blank - Molded Ring

## Options and Accessories (continued)

**Other Louver Finishes** Consult Factory

Emergency	Add suffix <b>EM*</b>
Chicago Plenum	Use 6132BULC
Existing/Thk. Ceiling	<b>FA EC6*</b>
Emergency Ltg. Kit	<b>FA EM3E*</b>
Fuse (Slow Blow)	Add Suffix <b>F</b>

\*See Spec. Sheets: FAEC, FAEM

Mounting Bars & Accessories; see Specification Sheet MBA.

Sloped Ceiling Adapters; see Specification Sheet SCA.

IC Frame available; see **C6CFL32** specification sheet.

## Labels

UL listed for damp locations.

Alzak® is a registered trademark of ALCOA.

**US Patent Pending**

Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

www.lightolier.com © 2008 Philips Group • A0608

