



Ceiling Cutout: 5 1/8" L X 9 5/8" W

| Trim Kits | | Frame-In Kits | | | | | | | | |
|-----------------|--------------------------------|---------------|--------|------------------------|---------------|-------------------|---------------------|---------|---------|--------|
| Reflector Trims | Finish / Flange | Frame-In Kits | Type | Ballast | Input Voltage | Quad Tube Wattage | Triple Tube Wattage | Length | Width | Height |
| 9X9CLW | Specular Clear / White | 9X9242HU | Non-IC | Electronic | 120/277V | (2) 26W | (2) 32/42W | 12 1/2" | 14" | 5 3/4" |
| 9X9CLP | Specular Clear / Polished | 9X9242HUEM | Non-IC | Electronic - Emergency | 120/277V | (2) 26W | (2) 32/42W | 12 1/2" | 15 3/4" | 5 3/4" |
| 9X9CCLW | Comfort Clear / White | 9X9242HJUM7 | Non-IC | Mark 7® Dimming | 120/277V | | (2) 32/42W | 12 1/2" | 13 3/4" | 5 3/4" |
| 9X9CCLP | Comfort Clear / Polished | 9X9242HJ1MX | Non-IC | Mark 10® Dimming | 120V | | (2) 32/42W | 12 1/2" | 13 1/2" | 5 3/4" |
| 9X9CCDW | Comfort Clear Diff. / White | 9X9242HJ2MX | Non-IC | Mark 10® Dimming | 277V | | (2) 32/42W | 12 1/2" | 13 1/2" | 5 3/4" |
| 9X9CCDP | Comfort Clear Diff. / Polished | | | | | | | | | |
| 9X9CCGP | Clear Corrugated / Self Flange | | | | | | | | | |
| 9X9WHW | White / White | | | | | | | | | |

Features

- Reflector Trim:** Pre-finished aluminum with low iridescence clear finish. 55° visual and reflected cutoff. Overlap flange accommodates different ceiling types. Precision mitered flange corners.
- Upper Reflector:** High efficiency, 97%, Specular Clear.
- Housing:** 20 ga. galvanized formed steel. Centerline notches and holes for consistent alignment of multiple fixtures. Accommodates ceilings up to 1 1/4" thick.
- Ballast Assembly:** Door-mounted for easy service, allows replacement from inside of fixture.
- Torsionite Springs:** Precision-tooled steel springs secure reflector trim to housing for quick tool-less installation. Positive tension holds flange tight against ceiling.
- J-Box:** 14 ga. galvanized steel. Accessible from inside and outside of the fixture. Outside J-box door is hinged for easy access.
- Mounting Brackets:** 16 ga. steel. Adjustable from inside fixture. Utilize 3/4" or 1 1/2" lathing channel, 1/2" EMT, or optional mounting bars.

Options and Accessories

- Chicago Plenum with Fuse (slow blow):** Add LCF suffix to Frame-In Kit, consult factory for specifications.
- Emergency:** Add EM suffix to Frame-In Kit, consult factory for specifications.
- Mounting Bars / T-Bar Anchor Clips:** See specification sheet "MBA".

Electrical

UL Listed for through circuit wiring with max of (8) No. 12 AWG, 90°C supply conductors.

Note: For complete ballast data and lamp / ballast compatibility refer to "Ballast" specification sheet.

General

UL Listed for damp locations, I.B.E.W. Union Made.
Specular Clear finish (CL) reflector trims meet IES RP-1 practice.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
www.lightolier.com © 2008 Philips Group • B0608

