



Reflector Trim				Frame-In Kit	
<b>(Lens:)</b>	<b>Fresnel</b>	<b>Clear</b>	<b>Prismatic</b>	<b>S6132BU</b>	6" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam)
Clear Cone, White Flange	<b>8091FCLW</b>	<b>8091CCLW</b>	<b>8091PCLW</b>	<b>Dimming Options:</b>	
Clear Cone, Polished Flange	<b>8091FCLP</b>	<b>8091CCLP</b>	<b>8091PCLP</b>	<b>S6132B</b>	<input type="checkbox"/>
White Cone, White Flange	<b>8091FWHW</b>	<b>8091CWHW</b>	<b>8091PWHW</b>	<b>CU3</b>	Lightolier PowerSpec 3% Dimming (120/277V)
				<b>J1LD3</b>	Lutron 3% Dimming (120V)
				<b>J2LD3</b>	Lutron 3% Dimming (277V)
				<b>J1MX</b>	Mark 10 Dimming (120V)
				<b>J2MX</b>	Mark 10 Dimming (277V)
				Other dimming product available, please consult factory	
	<b>Opal Diffuser</b>			<b>Remodeler Frame-In Kits</b>	
Clear Cone, White Flange	<b>8091DCLW</b>			<b>6126BURM</b>	6" aperture, 1 lamp 26W Triple Tube CFL (120/277V) 4-Pin (Amalgam)
Clear Cone, Polish Flange	<b>8091DCLP</b>			<b>6132BURM</b>	6" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam)
White Cone, White Flange	<b>8091DWHW</b>				

### Features

- Reflector:** 16 ga. Die-formed aluminum, Anobrite® finish.
- Socket Cup:** Effectively dissipates heat and positions lamp holder. Snaps onto reflector neck to assure consistently correct optical alignment without tools.
- Mounting Frame:** Galvanized steel for dry or plaster ceilings. Accepts other 6" Triple Tube reflectors (see S6132BU Spec Sheet).
- Retaining Springs:** Precision-tooled steel friction springs secure reflector to mounting frame for quick, tool-less installation.
- Mounting Brackets:** 16 ga. steel. Adjust from inside of fixture. Use 3/4" or 1 1/2" lathing channel, 1/2" EMT, or optional mounting bars.
- Ballast/J-Box:** Electronic 120V-277V. UL listed for through branch circuit wiring with max of (8) No. 12AWG, 90°C supply conductors. Outboard-mounted to reduce heat transfer and maintain lamp efficacy and life. Service from below without tools.
- Shielding Media:** Molded acrylic. Available in fresnel lens, clear lens, or opal diffuser. Secured to aperture cone.
- Cone:** 16 ga. Alzak® aluminum. Clear Iridescence Free finish or Comfort Clear™ low iridescence finish. Retained by friction springs; no loose parts.

### Electrical

**Note:** For ballast electrical data and latest lamp/ballast compatibility refer to "Ballast" specification sheet for complete electrical data.

UL Listed for through branch circuit wiring with max of (8) No 12 AWG, 90 degree C supply conductors.

### Options and Accessories

<b>Comfort Clear™ Finishes¹</b>		<b>Other Finishes</b>	
Clear	<b>CCL</b>	White	<b>WH</b>
Diffuse	<b>CCD</b>	Champagne Bronze	<b>CCZ</b>

¹Specify desired flange. **W** White, **P** Polished

### Options and Accessories (continued)

Emergency	Add suffix <b>EM*</b>
Chicago Plenum	Use 6132BULC
Existing/Thk. Ceiling	<b>FA EC6*</b>
Emergency Ltg. Kit	<b>FA EM3E*</b>
	<b>FA EM4E*</b>
Fuse (Slow Blow)	Add suffix <b>F</b>

\*See Spec. Sheets: FAEC, FAEM

Mounting Bars & Accessories; see Specification Sheet MBA. Sloped Ceiling Adapters; see Specification Sheet SCA.

IC Frame available; see **C6CFL32** specification sheet.

### Labels

All units are UL listed for wet locations; Opal Diffuser is UL listed for damp locations.

Alzak® is a registered trademark of ALCOA. **US Patent Pending.**

Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 www.lightolier.com © 2008 Philips Group • A0708

