



Complete Fixture consists of Decorative Element, standard Frame-In Kit and Trimless Reflector. Select each separately.

Ordering Information

| Decorative Element Catalog No. | Finish/Color | Trimless Reflector | Frame-In Kit | Dimensions | | | | |
|--------------------------------|--|---|---|------------|----|--------|------|---------|
| | | | | A | B | C | D | E |
| DD6 | Soda lime green glass with sandblasted band and open center aperture. | For use with all Calculite 6" Compact Fluorescent and Incandescent open trimless downlight reflectors except ProSpec. | For use with all Calculite 6" Compact Fluorescent and Incandescent open downlight Frame-In Kits except ProSpec. | 12" | 4" | 1 7/8" | 3/8" | 1 1/16" |
| DD7 | Soda lime green glass with sandblast band and an open center aperture. | For use with all Calculite 7" Compact Fluorescent and Incandescent open trimless downlight reflectors except ProSpec. | For use with all Calculite 7" Compact Fluorescent and Incandescent open downlight Frame-In Kits except ProSpec. | 14" | 5" | 1 7/8" | 3/8" | 1 1/16" |

Features

- Decor Disc:** Tempered soda lime glass 3/8" thick, sandblasted ring around center aperture 3 5/8" wide for the 6" and 4 1/2" wide for the 7". Clear edge 3/8" wide band.
- Spacer:** Matte white painted aluminum.
- Decorative Knob:** 3/8" dia. aluminum. Four placed 90° apart, matte white finish.
- Trim Ring:** .090" thick aluminum ring with matte white finish.
- Reflector:** See Reflector Trim for Specification Sheet.
- Frame-In Kit:** See Frame-In Kit for Specification Sheet.
- Mounting Frame Stud:** Four #8-32 screws.

Lighting Data

See applicable downlight Specification Sheet for base lighting data. Multiply the candlepower values or the coefficient of utilization by the following factors:

| | 6" | 7" |
|-------------------------------------|-----|-----|
| A Lamp downlights | .70 | .70 |
| Compact Fluorescent lamp downlights | .65 | .75 |
| PAR Lamp downlights | .85 | .85 |

with C700 Frame - use 250W lamp maximum.

Mechanical

Decorative elements securely fastened to four mounting frame studs and 4 (3/8" dia.) aluminum knobs.

Labels

U.L. (Damp Location)

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

Lightolier a Genlyte Thomas Company

www.lightolier.com

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

© 2003 Genlyte Thomas Group LLC (Lightolier Division) • B1003

LIGHTOLIER®