
Page 1 of 2

Lowprofile Direct Louver 1-Light T8 Per 4-Foot Section



Ordering Information

Style	Туре		
CD7	1		
	1 - Direct Loui		

Direct Louver

1 = Surface **2** = Cable

3 = Stem

4 = Wall

Mounting

4 = 4-foot 8 = 8-foot

Length

1 = 1-Lamp T8 per fixture (4' fixture) 2 = 2-Lamp T8

(8' fixture)

Total Lamps

Color WH

White

per fixture

Ballast & Voltage

E81 = T8 Electronic 120V E82 = T8 Electronic 277V **HD1** = T8 Electronic PowerSpec® HDF Dimming 120V

HD2 = T8 Electronic PowerSpec® HDF Dimming 277V

M71 = T8 Electronic Dimming Ballast 120V M72 = T8 Electronic Dimming Ballast 277V

Complete ordering instructions below.

For all fixtures represented in this family please refer to the brochure and/or additional specification sheets.

Features

- 1. Housing: Extruded aluminum. Die-cast end cap mechanically attached with no exposed fasteners. Concealed access holes in end plate for through wiring.
- 2. Lamping: One T8 32 watt fluorescent lamp, as specfied. Provided by others.
- 3. Reflector: Accurate parabolic-shaped, die-formed semi-specular anodized aluminum reflector with 36° shielding crosswise.
- Louver: Parabolic-shaped, die-formed semi-specular anodized aluminum. Provides low brightness in lengthwise and crosswise views with 37° shielding lengthwise. Concealed latches operate from either side.

Electrical

Specify 120 volt or 277 volt. 3 conductor, 18 gauge wire. Color-coded quick connectors allow ease of connection for joiner modules. For special circuiting, consult factory. Rapid start, HPF, class "P" thermally protected. PowerSpec HDF dimming ballast is available. Factory installed ballast disconnect allows the ballast to be disconnected from and reconnected to incoming power under load with out turning the entire circuit off.

Mountings

Cable Suspension (not shown) - 1-1/2" (3.81cm) and 4-1/2" (11.43cm) diameter flat canopy finished enamel white, 1/16" (0.16cm) diameter stainless steel aircraft cable adjustable up to 36" (91.44cm), adjustable cable gripper.

Stem Mounting (not shown) - 4-1/2" (11.43cm) diameter flat canopy, 1/2" (1.27cm) diameter rigid-mounted stem. White finish. Can be cut to length on job. Self-aligning swivel provides adjustability up to 42° of slopes.

Surface & Wall Mounting (not shown) - consult factory for availability.

Finish

Powder coated baked white enamel. Custom colors available, consult factory.

Options and Accessories

Emergency batteries available.

Ordering Instructions

Individual Fixtures:

1. Order number of FIXTURES (fixture comes complete with end caps, mounting hardware and power feeds).

Continuous Rows:

- 1. Determine run length.
- 2. Order the appropriate number of FIXTURES for the complete run. Fixtures can be bolted together and through wired to complete long runs.

Labels

UL, cUL and I.B.E.W.

Job Information	Туре:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	


631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. www.lightolier.com © 2008 Philips Group • C1008



Page 2 of 2

Lowprofile Direct Louver 1-Light T8 Per 4-Foot Section

Performance and Quick Calculator



CANDLEPOWER					
ZONE DEG.	0	22	45	67	90
180 175 165 155 145 135 125 115 105 90 85 75 65 55 45 35 25	0 0 0 0 0 0 0 0 0 0 0 1 1 8 93 276 387 488 564 619 630	0 0 0 0 0 0 0 0 0 0 1 9 140 387 488 551 597 631 630	0 0 0 0 0 0 0 0 0 0 1 12 173 446 614 682 651 654 634	0 0 0 0 0 0 0 0 0 0 1 11 175 462 689 783 737 678 634	0 0 0 0 0 0 0 0 0 0 1 168 457 712 814 769 675 636
0	633	633	633	633	633

CANDI EDOMED

COEFFICIENTS OF UTILIZATION

% EFFECTIVE CEILING CAVITY REFLECTANCE


			80			70			50	
		% V			VALL REFLECTAN			ANCE	NCE	
		50	30	10	50	30	10	50	30	10
	1	73	71	69	71	69	67	68	67	65
9	2	66	62	59	65	61	59	62	60	57
ROOM CAVITY RATIO	3	60	55	52	59	54	51	57	53	50
>	4	53	48	44	52	48	44	51	47	44
\equiv	5	48	43	39	47	42	38	46	41	38
S	6	43	38	34	42	37	34	41	37	33
≥	7	39	33	29	38	33	29	37	32	29
8	8	35	29	25	34	29	25	33	29	25
ш	9	31	29	22	31	26	22	30	25	22
	10	27	22	18	27	22	18	26	21	18
	20% FLOOR CAVITY REFLECTANCE						Έ			


20% FLOUR CAVITY REFLECTANC

ZONE	LUMENS	% LAMP	% LUMINAIRE
0-90	1962	67.7	100.0
90-180	0	0.0	0.0
0-180	1962	67.7	100 O


ZONAL LUMEN SUMMARY

Fixture Lengths & Mounting Locations







Sample Run



Mounting Details





Job Information Type:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. www.lightolier.com © 2008 Philips Group • C1008

