



## Ordering Information:

Cat. No.	Diameter	Extension	Finish	Voltage	Lamps (by others)	
6562BK	10 1/2"	5 1/4"	Black	120V	(1) 75W A19 MAX.	
6561BZ	10 1/2"	5 1/4"	Bronze	120V	(1) 75W A19 MAX.	
6560WH	10 1/2"	5 1/4"	White	120V	(1) 75W A19 MAX.	
6566BK	10 1/2"	5 1/4"	Black	120V	(2) 9W Twin 2-pin (G23 base)	<b>General Electric</b> <b>Osram/Sylvania</b> <b>Philips</b> F9BX/SPX/*   CF90S/*   PLS9W/* <small>*Manufactures color temperature designation.</small>
6567BZ	10 1/2"	5 1/4"	Bronze	120V	(2) 9W Twin 2-pin (G23 base)	
6566WH	10 1/2"	5 1/4"	White	120V	(2) 9W Twin 2-pin (G23 base)	

## Features

- 1. Diffuser:** Injection molder polycarbonate.
- 2. Screw:** Diffuser removal can be made tamper proof.
- 3. Lamp Shield:** Directs light efficiently through diffuser.
- 4. Lamp:** See Lamps.
- 5. Ballast:** See Electrical/Ballast.

## Electrical/Ballast

	9W NPF 120V
Total Input Watts	20
Max. Line Current (amps)	.36
Ballast Factor	.90
THD	< 20%
Min. Starting Temperature	-4°C (-25°F)

## Mounting

Wall Mount only to standard 4" octagonal outlet box.

## Labels

UL Listed. Suitable for Wet Locations.

## Job Information

## Type:

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**