



Ordering Information

Catalog Number	Finish	Size	Lamping (by others)
86130AL	Satin Aluminum	10' Coaxial Cable	35W 12V: T-4 Tungsten Halogen Bi-Pin (G6.35) Base
86130WH	Matte White	10' Coaxial Cable	
86132BK	Matte Black	10' Flexible Cord	
86132WH	Matte White	10' Flexible Cord	

Features

- Mounting Plate:** 18 ga. galvanized steel.
- Canopy:** 18 ga. steel. See above chart for finish.
- Knob:** Required to secure canopy to mounting plate.
- Transformer:** Electronic 35W, low voltage (12V). Input 120V, 50/60hz; input current 0.625A.
- Transformer Bracket:** 18 ga. steel. Gloss white.
- Electrical Cord:** 2-Conductor braided coaxial cable or flexible cord.
- Holder Casting:** Die cast aluminum alloy.
- Shade Support:** Die cast aluminum alloy.
- Lamp Guard:** Satin finished glass provided for effective light diffusion.
- Lamp:** 35W 12V T-4 Tungsten Halogen Bi-Pin (G6.35) base, (by others).
- Shade / Diffuser:** See Specification Sheet 42232 for details.

Electrical

Bi-Pin ceramic socket having a 6.35mm pin spacing. Pre-wired with braided coaxial cable.

Labels

UL Listed, Suitable for Dry Locations Only.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2005 Genlyte Group LLC • C0305

LIGHTOLIER®