



Mounting Plate Assembly

Catalog No.	Finish	Lamps	Length	Width (extension)	Height
5403WHU	White	(2) 25W T8	36 3/4"	6 7/16"	3"
5403PCU	Polished Chrome	Fluorescent			
5403PBU	Polished Brass				

Features

- 1. End Caps:** Die-cast aluminum alloy.
- 2. Luminous Strip:** White translucent acrylic.
- 3. Mounting Plate:** Die Formed, 18 ga. steel.
- 4. Junction Box Cover:** (Removable) for use with 4" or 3 1/2" octagonal junction box. Not required for horizontally mounted switchbox. Semi-gloss white.
- 5. Diffuser:** One-Piece, translucent white 100% virgin acrylic.

Electrical

Ballast: Rapid Start, Electronic 120V

Total Input Watts	51
Max.Line Current (Amps)	0.42
Power Factor	.98
Ballast Factor	0.92
THD	<10%
Min. Starting Temp.	50°

Mounting

Horizontally to wall using six 7/32" diameter mounting holes.

Note: Fixture is intended for horizontal mounting only.

Finish

All painted surfaces, baked enamel.

Labels

UL Listed, suitable for Damp Locations.

Fixtures are rated for connection to 60°C building wire. Therefore, they can be used for either old or new construction.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte Thomas Company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902