


Decorative Opalux® Diffused Light 6348

Surface Mounted Incandescent-(2) 60W A19



Ordering Information

Catalog No.	Lamps	Length	Width	Extension
6348N	2 Lt - 60W A-19	12 1/8"	4 7/8"	4 1/2"

Features

- 1. Glass Diffuser: Blown pure white opal glass, casts well-diffused general lighting.
- Fitter: Die-formed aluminum, 16 ga. White finish. Will fit 3 1/4", 4" octagon or gem outlet box. For wall mounting only.
- **3. Cam-Lock Locking Lever/Back Plate:** Concealed behind diffuser. Rotates 90° with fingertip pressure to lock glass securely in place, assures ease of relamping and maintenance. Rust proof aluminum back plate.

Electrical

No. 18 105°C thermoplastic wire. Porcelain socket-medium base. Fixture required 90°C rated supply wiring.

Labels

UL (Suitable for Damp Locations), I.B.E.W.

Lightolier a Genlyte Thomas Company 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. © 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902

Type:

Job Information

Job Name: Cat. No.:

Lamp(s): Notes: