



Catalog Number	Finish	Description	Wattage	Voltage
CS100AL	Matte Aluminum	5ft Track With Switch	NA	24V DC
CS101AL	Matte Aluminum	Magnetic Light Module	4W	24V DC
LED-RPS-50*	Matte Black	Remote Power Supply	50W Max.	120V

* See below for remote power supply dimensions.

Features

- Ultra low profile track with steel insert
- Magnetic light modules can be positioned anywhere along the track. Modules can be moved, added, or removed according to lighting needs.
- Finish: Light modules – matte aluminum
Track – Clear anodized aluminum
- Light Modules: Shallow architecturally pleasing shape. Concealed integrated fins in light module body with concentric vent designed to create air circulation to maintain appropriate junction temperature of LEDs.
- Up to (7) light modules per single wired track.
- Remote low profile power supply – 50W 120V.

Magnetic Light Module: (3) 1W 3000K white LEDs. Average expected life, under normal operating conditions is 50,000 hours with 70% lumen maintenance of original light output.

Electrical: Max connected load – 4W per fixture.

Power Supply LED-RPS-50: Class 2 24V DC output is remote mounted, 120V input. Max Connected System Load – 50W per power supply.

Wiring: 5ft track pre-wired with 8ft cord. 24V DC only.

Material: Light Modules – die-cast aluminum
Track – extruded aluminum

Mounting: Track – pre-drilled holes for screw mounting (screws not included). Magnetic light modules can be placed anywhere along track.

Labels

cULus listed, Dry Location.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
www.lightolier.com © 2008 Philips Group • C1208