



Cat No.	Finish	Length	Wattage	Color Temp	Voltage
CWL281212	Charcoal Gray	12"	6W	2800K	120V
CWL421212				4200K	
CWL280612		6"	4W	2800K	
CWL420612				4200K	

Power Cord	Lead
CWLPC120	120"

Accessories:

Mounting Track	Quantity
CLMT2548	(25) 4ft Mounting Tracks

Jumper Cables	Lead
CWLJC12	12"
CWLJC60	60"

Ordering Information: Complete fixture consists of Fixture + Power Cord.
i.e. CWL281212 + CWLPC120

Features

Dimmable, linear line voltage modules with end-to-end connections that generate high quality white light in either 2800K or 4200K.

- Integral mounting bracket with 180° rotation
- Smooth, wide symmetrical distribution
- Available in 12" (305 mm) and 6" (152 mm) lengths
- End-to-end connections
- Available in 2800 K and 4200 K
- Low power consumption (<6W startup; 4.5 W steady-state)
- 50,000 hour lifetime
- Up to 100 12" or 150 6" fixtures may be used in a series
- Line voltage for simple installations and long runs
- Dimmable with standard ELV-type dimmers

Materials: Injection-molded housing and Polycarbonate lens.

Finish: Charcoal grey.

Lamping: High brightness LEDs (5 in 12", 3 in 6").

Max. connected load: 6W for 12", 4W for 6".

Electrical: 120 VAC input.

Mounting: Holes for screw-mounting or optional mounting track.

Labels

UL/CUL, IP20, Dry Listed.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
www.lightolier.com © 2008 Philips Group • A0708