



**Ordering Information:**

Cat. No.	Width	Height	Extension	Finish	Voltage	Lamps (by others)
4809BK	10 9/16"	6 7/16"	5 11/16"	Black	120V	(1) 100W A19 MAX.
4830BZ	10 9/16"	6 7/16"	5 11/16"	Bronze	120V	(1) 100W A19 MAX.
4833WH	10 9/16"	6 7/16"	5 11/16"	White	120V	(1) 100W A19 MAX.
4811BK	10 9/16"	6 7/16"	5 11/16"	Black	120V	(2) 9W Twin 2-pin (G23 base)
4832BZ	10 9/16"	6 7/16"	5 11/16"	Bronze	120V	(2) 9W Twin 2-pin (G23 base)
4835WH	10 9/16"	6 7/16"	5 11/16"	White	120V	(2) 9W Twin 2-pin (G23 base)

**Gen. Elect. Osram/Sylvania Philips**  
 F9BX/SPX/\* CF90S/\* PLS9W/\*  
 \*Manufactures color temperature designation.

**Features**

- 1. Diffuser:** Pressed ceramic coated glass.
- 2. Diffuser Housing:** Die-cast aluminum guard.
- 3. Backplate:** 11 ga. aluminum.
- 4. Lamp:** See Lamps.
- 5. Ballast:** See Electrical/Ballast.

**Labels**

UL Listed. Suitable for Wet Locations.

**Electrical/Ballast**

	9W NPF 120V
Total Input Watts	20
Max. Line Current (amps)	.36
Ballast Factor	.90
THD	< 20%
Min. Starting Temperature	-4°C (-25°F)

**Mounting**

Wall Mount only to standard 4" octagonal outlet box.

**Job Information**

**Type:**

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**

**Lightolier** a Genlyte company [www.lightolier.com](http://www.lightolier.com)  
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 © 2005 Genlyte Group LLC • A0805