




Page 1 of 2

120V GU10 Low Profile Ring







Ordering Information

Catalog No.	Finish	Track Mountings	Lamps
FXESR	Silver	For use on all Tangent Track systems. May be horizontal or vertical wall mounted.	120V Halogen GU10 Base 35W Max

Features

- 1. Track Attachment fitting: Molded thermoplastic clamping adapter with captive, nickel-plated steel pin. Clockwise rotation of pin secures fixture adapter to track.
- 2. Fixture Stem: Two 1/8" diameter stainless steel rods.
- 3. Horizontal Pivot: 365° horizontal rotation.
- 4. Vertical Pivot: 0° to 90° vertical adjustment.
- 5. Socket: Ceramic GU10 TAL halogen socket.
- 6. Housing: Plastic socket cup.
- 7. Softening Lens: Low-iron sodalime glass lens with Solite stippled pattern. Diffuses striations and shadows from lamp while allowing 92% light transmission.
- 8. Diecast Ring

Finish

All Painted finishes are baked enamel.

Accessories

Accessory Holder: Integral

Accessories: Accepts one accessory lens; replaces clear glass shield provided

with fixture.

Lens: AF2 or ADF2 Series

Louver: AL2HC

Labels

cULus Listed

Dimming

Fixture may be used on a track with a dimmer. Consult dimmer manufacturer for correct dimmer selection.

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. www.lightolier.com © 2008 Philips Group • B1108





Page 2 of 2

120V GU10 Low Profile Ring


AIMING ANGLE:

L Beam length Distance W Beam Width Aiming Angle C Distance to center beam FC Footcandles

L and W are the outer points where the candle power drops to 50% of the maximum. FC are the initial footcandles at the center of the beam.

Lamp data shown is typical. Consult lamp manufacturers for availability and performance. CBCP= Center Beam Candle Power.

LAMP	Beam Spread (To 50% CBCP)	CBCP	Rated Life (Hrs.)
35W Philips GU10	25°	480	3000



10 3.1

5 0.0 19

6 0.0 13 2.7 2.7

0.0

0.0


2.2

3.5

2.2

3.1

3.5



FC

C


4.0 6 5 4.2


D

5 2.9 12

6 3.5 9

8 4.6





L	W	D	C	FC	L	W	D	C	FC	L	W
3.0	2.6	1.5	2.6	27	3.1	1.3	1.5	1.5	75	1.4	0.9
3.6	3.1	2	3.5	15	4.2	1.8	2	2.0	42	1.9	1.3
4.2	3.6	3	5.2	7	6.2	2.7	3	3.0	19	2.8	1.9
4.8	4.1	4	6.9	4	8.3	3.5	4	4.0	11	3.7	2.5

Job Information

Type:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. www.lightolier.com © 2008 Philips Group • B1108

