



FRAME-IN KIT



REFLECTOR TRIM

Complete Fixture consists of Reflector Trim & Frame-In Kit. Select each separately.

Frame-In Kit	Reflector Trims — See Individual Reflector Trim Specification Sheets										
	Open Downlight					Recessed			Enclosed Diffusers	Open Wet Location	Wall Washer
Reflector	Cone	Satin Cone	Baffles	Basic White	Adjustable		Eyeball				
1000IC	1045	1012	1008	1005	1071	1027	1029	1022	1021	1084CD	1035
1000ICM*	1046	1012NM	1008NM	1005NM		1027CD	1029CD	1022WH	1024	1084WH	1035WH
	1046CD	1013	1010	1005BNM		1027NM	1029NM	1023	1078		1085
		1013CD	1010NM	1005WH		1027CDNM	1029CDNM	1023WH	1090		1095
		1013BK		1076		1027BK	1029BKNM	1082			1096
		1013WH		1076WH		1027BKNM	1029GDNM				1096CD
		1013NM				1027WH	1029CLNM				
		1013CDNM				1038	1029CL				
		1013BKNM				1038NM	1029GD				
						1048	1029BK				
						1048NM	1029WH				
						1029BNM					

*3/8" Integral Plaster Lip

Features

- Housing:** .026" (#20 ga.) galvanized steel. U.L. listed for direct contact with thermal insulation. Access door for inspection of junction box.
- Mounting Frame:** .036" (#20 ga.) galvanized steel. Accommodates all ceilings up to 1" thick. ICM version has 3/8" deep integral lip. Four slots are positioned 90° apart to simplify alignment. Push-in/twist-out rotoclips hold reflector flush to ceiling.
- Junction Box:** 2" x 4" x 4", .063" (#14 ga.) galvanized steel. U.L. listed for maximum of 6 No. 12 ga., 90° C through branch circuit conductors. Quick release "L" shaped cover for outside access to wiring. Access door inside of housing allows easy inspection of wiring without removal of housing. Integral cable clamps permit attachment of nonmetallic Romex® or armored cable without the need for additional connectors.
- Mounting Bars:** .059" (#16 ga.) galvanized steel. 13" long bars extend to 27", rotatable and lockable, with integral T-bar tabs. Attach to wood joist or T-bar ceilings without need of accessories.
- Socket Housing:** Impact extruded aluminum or galvanized steel.
- Socket:** Porcelain medium base; nickel plated screw shell. Pre-wired with #18 ga. SF1 leads to junction box.
- Thermal Protector:** Meets NEC and U.L. requirements. Located inside housing.

Options & Accessories

- Mounting Bars:** **1964** - 20" set of (2)
T-Bar Ceiling Clips: **1956** - set pf (4)
Plaster Ceiling Ring: **1960** - 7/8" depth for wet plaster ceilings. Not for use with ICM housing.

Options & Accessories (continued)

- Extra-Thick Ceiling Mounting Ring:** **1967B** - up to 2" thick ceilings.
277 Remove Step-Down Transformer **7997** - 277Vdown to 120V 300W max.load.

Labels

UL (Type I.C., Suitable for Damp Locations), I.B.E.W.

Romex® is a registered Trademark of General Cable Industries Inc.
US Patent No.: 5,045,985; 4,751,624

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2006 Genlyte Group LLC • G0906