



Complete Fixture consists of Reflector Trim & Frame-In Kit. Select each separately.

Reflector Trim	Frame-In Kit — See Individual Frame-In Kit Specification Sheets			
	Low Voltage			
	Frame-In Kit	Installation Type	Lamping	Height
2026WH Matte White	2000LV	Standard Non-IC	20W-50W MR16	5 7/8"
	2000LVR	Remodeler Non-IC	37W MR16	5 7/8"
	2000LVE1	Electronic Low Voltage Non-IC 120V	20W-50W MR16	5 7/8"
	2000LVE2	Electronic Low Voltage Non-IC 277V		5 7/8"
	2004ICV/N	Lytecing AirSeal® IC	20W-50W MR16	7 1/4"
	2000LVNT	Non-IC (no transformer)	20W-42W MR16	5 7/8"

Features

- Housing:** Galvanized Steel, .026" thick (22 ga.).
- Trim Flange:** Die-cast aluminum .060" thick.
- Frame-In Kit:** (2000LV standard frame shown) Other frames shown on the right. See Frame-In Kit specification sheets for more details.
- Glass:** Frosted Glass Diffuser

Options & Accessories

Retaining Clips: 1955 - For Installing in Existing Ceiling

Labels

UL (Suitable for Wet Locations - Covered Ceiling)

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • E0808