

Ordering Information

Catalog No.	Description	Finish	Lamps
6497	Framing Projector Accessory for use with 6298, 6299, 6415, 6416, (see Lightolier Specification sheets 6298 and 6415)	Matte Black	50W MR-16 12V EXZ (Narrow Flood)
	Framing Projector Accessory for use with 6294, 6295, 6297 (see Lightolier Specification sheets 6294 and 6296)	Matte Black	50W EXZ (Narrow Flood) or 75W EYC (Wide Flood) MR-16 12V

Features

- Adjustable Shutter Blades (4):** Spring steel with insulated hand knob.
- Framing Projector Assembly:** Mechanically locks onto MR-16 Lytespots with locking screws.
- Focusing Lens**


Finish

All painted finishes baked enamel.


Labels

UL, I.B.E.W.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	



Lighting Data




Illumination On Vertical Plane

Shutter Blades Set For Maximum Beam Coverage

Distance (D)	24"			36"			48"			60"			72"			84"			96"			
Aiming Angle (A)	30°	45°	60°	30°	45°	60°	30°	45°	60°	30°	45°	60°	30°	45°	60°	30°	45°	60°	30°	45°	60°	
Width (W)	12"	18"	20"	20"	30"	35"	29"	42"	48"	37"	54"	62"	46"	66"	75"	54"	78"	88"	63"	90"	101"	
Length (L)	16"	22"	44"	27"	37"	70"	39"	51"	97"	50"	66"	123"	61"	81"	150"	72"	95"	176"	84"	110"	202"	
Distance (C)	13"	22"	33"	20"	33"	50"	26"	44"	66"	33"	55"	83"	39"	66"	99"	46"	77"	116"	52"	88"	132"	
FC	50W MR-16 FL EXN	376	183	52	130	66	20	65	34	11	39	20	7	26	14	5	18	10	3	14	7	2
	75W MR-16 PL EYC	680	332	95	234	119	37	117	61	20	70	37	12	47	25	8	33	18	6	25	13	4

Length (L) to the point that F.C. drops to 10% of maximum.



Illumination On Horizontal Plane

Shutter Blades Set For Maximum Beam Coverage

Distance (D)	4'	5'	6'	7'	8'	9'	10'	11'	12'
Sides (S)	20"	26"	32"	38"	44"	50"	56"	63"	69"
FC	50W MR-16 FL EXN	108	64	42	30	22	17	14	9
	75W MR-16 PL EYC	195	115	75	53	40	31	24	17

Job Information Type: