



Ordering Information

Catalog No.	Finishes	Track Mountings	Luminaires	Lamp
83CY70EWH 83CY70EBK 83CY70EAL	Matte White Matte Black Metallic Aluminum	Intended for ceiling mounting and surface wall mounting 5' or greater from floor. No remote mounting.	Use one of: 8313 8317 83W4 8314 8318 83W6 8316 83W7	70W Ceramic Metal Halide

Features

- Housing:** .10" thick extruded aluminum body with die cast end caps.
- Canopy:** 0.06" aluminum canopy.
- Mounting Arm:** 0.07" extruded aluminum housing.
- Cross Bar:** (not shown) .074" galvanized steel with positive rotation stop. Provides 350° rotation and positive lock every 45°. Mounting to J-Box provides simple hands-free wiring.
- On/Off Switch:** Rocker switch to disconnect power to the ballast.
- Power Receptacle:** 5kv rated, insulated. Accepts power connector from fixture.
- Integral Track Groove:** To mount PowerArc™ modular spots and wall wash fixtures.

Electrical

Magnetic Ballast

Input Voltage:	120 to 277V, 60Hz
Power Factor:	High
Input Power:	79W
Max Input Current:	0.67A
Total Harmonic Distortion:	<15%
ANSI Code:	M143 or M98

Do not use on a dimming circuit.

Finish

All painted finishes baked enamel.

Labels

cUL, UL

Patents

Products shown here are protected by applicable patents and patents pending.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • D1108