





Catalog No.	Finishes	Mounting	
8605WH	Matte White	To structurally sturdy ceilings 1/8" to 1 1/2" thick. Must have access from above ceiling.	
8618	Matte White	T-Bar Accessory mounts 8605WH to ceiling runner. Must have access from above ceiling.	

Features

munt

at **b**

1

- 1. Plug Housing: Aluminum die-casting, contains all electrical components and supports LyteJack fixture.
- 2. Plug Jack: Molded high heat resistant thermoplastic.
- 3. Molded Cap: Flame-retardant ABS; snaps onto flange of Plug Housing.
- 4. 1/2-14 NPSM Thread (Inside)
- 5. 90° Electrical Connector
- 6. Mounting Bars: see accessory table.
- 7. T-Bar Accessory: Mounts Point Power Jack to ceiling runner. Recommended for soft ceilings.
- 8. 16 Ga. Wire: Rated 90°C. 8' supplied. 8' maximum distance from Lightolier transformer to prevent excessive voltage drop.
- 9. 3/4-14 Nut: Clamps Point Power Jack to ceiling.

10.2 1/4" Dia Washer

11.3/4-14 NPSM Thread: (outside)

12.Center Bushing: Remove for Lytedrops.

Electrical

Use with either Lightolier remote transformer 8608 (75W) or 8609 (225W). Provided with 8' of wire (to prevent excessive voltage drop).

Options & Accessory

1950-18" Mounting Bars (set of 2). 1951-27" Mounting Bars (set of 2). 1956-T-Bar Mounting Clips (set of 4).

Labels

UL; I.B.E.W.

Patents

Products shown here are protected by applicable patents and patents pending.

Job Information Type: Job Name: Cat. No.: Lamp(s): Notes:

GHTOLIE

Lightolier a Genlyte Thomas Company www.lightolier.com 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710 We reserve the right to change details of design, materials and finish. © 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902

8605WH

8618