



#### Ordering Information

Catalog No.	Finishes	Track Mountings	Luminaires	Lamp
83CY39EWH	Matte White	Intended for ceiling mounting and surface wall mounting 5' or greater from floor. No remote mounting.	Use one of:	39W Ceramic Metal Halide
83CY39EBK	Matte Black		8313 83W4	
83CY39EAL	Metallic Aluminum		8314 83W6 8316	

#### Features

- Housing:** .10" thick extruded aluminum body with die cast end caps.
- Canopy:** 0.06" aluminum canopy.
- Mounting Arm:** 0.07" extruded aluminum housing.
- Cross Bar:** (not shown) .074" galvanized steel with positive rotation stop. Provides 350° rotation and positive lock every 45°. Mounting to J-Box provides simple hands-free wiring.
- On/Off Switch:** Rocker switch to disconnect power to the ballast.
- Power Receptacle:** 5kv rated, insulated. Accepts power connector from fixture.
- Integral Track Groove:** To mount PowerArc™ Modular spots and wall wash fixtures.

#### Electrical

Electronic Ballast

<b>Input Voltage:</b>	120 to 277V, 60Hz
<b>Power Factor:</b>	High
<b>Input Power:</b>	44W
<b>Max. Input Current:</b>	0.39A
<b>Total Harmonic Distortion:</b>	<15%
<b>ANSI Code:</b>	M130

Do not use on dimming circuit.

#### Finish

All painted finishes are baked enamel.

#### Labels

cUL, UL

#### Patents

Products shown here are protected by applicable patents and patents pending.

#### Job Information

#### Type:

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

www.lightolier.com © 2008 Philips Group • C1108