

Ordering Information

Catalog No.	Finishes	Track Mountings	Lamps	Shades	Reflectors
8705E WH	Matte White	All Lytespan® Track Systems, Multipoint, Monopoint, Monopoint Pin Up, Monopoint Weighted Base, Clamp On Monopoint, Extension Wands & Sloped Ceiling Adapter. (DOES NOT MOUNT ON PROSPEC® TRACK.) Note: Do not install on stem mounted Radius® track.	70W PAR30 Metal Halide	Use One: Optional 8737 8735	N/A
8705E TM	Dark Titanium				

Features

- 1. Arm:** Die-cast aluminum, brushed and clear coated finish.
- 2. Socket Cover:** Injection-molded thermoplastic.
- 3. Stem:** Stainless steel, brushed and clear coated finish, with a permanently tensioned horizontal rotation stop.
- 4. Stem Base:** Die-cast aluminum, brushed and clear coated finish with a permanently tensioned 90° vertical rotation stop (0° to 90°).
- 5. Contact Holder:** High temperature thermoplastic. Secures fixture mechanically and makes electrical contact with track.
- 6. Locking Lever:** Nickel-plated steel. For mechanical/electrical connection into track.
- 7. Track Adapter:** Die-cast aluminum, brushed and clear coated finish; attaches to track.
- 8. Moveable Brass Contact:** Extends for 2nd circuit in two circuit Lytespan track systems.
- 9. Embossed Keyway:** For attachment of optional shades.
- 10. Ballast:** U.L. Listed. High power factor Electronic Metal Halide ballast.
- 11. Ballast Housing:** Aluminum-extrusion.
- 12. Socket:** 5KV pulse rated ceramic body; leads encased in silicone coated fiberglass sleeving.
- 13. Ballast Housing End Plates:** Stamped steel.
- 14. Ground Spring:** Grounds luminaire to track.

Electrical

Electronic Ballast
 Input Voltage: 120V, 60Hz
 Power Factor: >95%
 Input Power: 78W
 Input Current: .67 amp
 Harmonic Distortion: <10%
 Do not use on a dimming circuit.

Options and Accessories

For compatible accessories see spec sheet for Metallics® PAR30 Dome Shade (8737), Metallics PAR30 Barndoor Shade (8735), Metallics PAR38 Barndoor Shade (8745) and Metallics PAR38 Dome Shade (8747).

Finish

Feature numbers 2, 11, & 13 painted in White or Titanium. Other external components, brushed metal with protective clear coat.


Labels

UL

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte Thomas Company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2002 Genlyte Thomas Group LLC (Lightolier Division) • C0902

LIGHTOLIER®




AIMING ANGLE:

- L** Beam Length
- W** Beam Width
- C** Distance to center beam

- D** Distance
- A** Aiming Angle
- FC** Footcandles

L and **W** are the outer points where the candle power drops to 50% of the maximum. **FC** are the initial footcandles at the center of the beam.

Lamp data shown is typical. Consult lamp manufacturers for availability and performance.



LAMP:

	Beam Spread (To 50% CBCP)	CBCP	Rated Life (Hrs.)	0° Horizontal Aiming				30° Horizontal Aiming				30° Vertical Aiming				45° Vertical Aiming						
				D	FC	L	W	D	C	FC	L	W	D	C	FC	L	W	D	C	FC	L	W
 70W PAR30 (MC/MH) SP	 10°	62,000	6,000	15'	276	2.6'	2.6'	10'	5.8'	403	2.3'	2.0'	5'	8.7'	310	3.6'	1.7'	8'	8.0'	343	2.0'	2.0'
				20'	155	3.5'	3.5'	15'	8.7'	179	3.5'	3.0'	8'	13.9'	121	5.7'	2.9'	12'	12.0'	152	4.2'	3.0'
				25'	99	4.4'	4.4'	20'	11.5'	101	4.7'	4.0'	11'	19.1'	64	7.9'	3.8'	18'	16.0'	86	5.6'	4.0'
 70W PAR30 (MC/MH) FL	 40°	9,000	6,000	7'	184	5.1'	5.1'	6'	3.5'	162	6.1'	5.0'	2'	3.5'	281	9.7'	2.9'	4'	4.0'	199	6.7'	4.1'
				10'	90	7.3'	7.3'	9'	5.2'	72	9.1'	7.6'	3'	5.2'	125	14.5'	4.4'	6'	6.0'	88	10.1'	6.2'
				13'	53	9.5'	9.5'	12'	6.9'	41	12.2'	10.1'	4'	6.9'	70	19.3'	5.8'	8'	8.0'	50	13.4'	8.2'
				16'	35	11.6'	11.6'	15'	8.7'	26	15.2'	12.6'	5'	8.7'	45	24.2'	7.3'	10'	10.0'	32	16.8'	10.3'

Job Information

Type:

Lightolier a Genlyte Thomas Company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2002 Genlyte Thomas Group LLC (Lightolier Division) • C0902

LIGHTOLIER®