

Ordering Information

Catalog No.	Finish	Mounting	Lamp
9022WH	Matte White	All Lytespan	55W-150W PAR38 (Cool Beam Also)
9022BK	Matte Black	Track Systems	45W-250W PAR38 (Tungsten-Halogen)

General Description

Minimal, functional form with cleanly detailed yoke and ring-shaped lampholder. Front relamping for easy maintenance. Units adjust horizontally up to 350°, vertically up to 90°

Finish

All painted finished baked enamel.

Electrical

Porcelain socket, medium base, nickel plated screw shell. No 18 braided SF-1 leads with silicone sleeving

Labels

UL, I.B.E.W.


Patents

Products shown here are protected by applicable patents and patents pending.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lightolier a Genlyte Thomas Company www.lightolier.com
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902




LIGHTOLIER®



Lighting Data

Aiming Angle:

L Beam length
W Beam width
C Distance to center of beam
D Distance
A Aiming angle
FC Footcandles
L and **W** are the outer points wherethe candlepower drops to 50% of the maximum. **FC** are the initial footcandles at the center of the beam.



LAMP	BEAM SPREAD (To 50% Max CP)	BEAM CTR. C.P. (Candelas)	RATED LIFE (Hours)	0° AIMING ANGLE (A)				30° AIMING ANGLE (A)				45° AIMING ANGLE (A)				90° AIMING ANGLE (A)						
				DIST. ANCE (D)	F.C.	BEAM LGTH (L)	BEAM WIDTH (W)	DIST. ANCE (D)	DIST. ANCE (C)	F.C.	BEAM LGTH (L)	BEAM WIDTH (W)	DIST. ANCE (D)	DIST. ANCE (C)	F.C.	BEAM LGTH (L)	BEAM WIDTH (W)	DIST. ANCE (D)	DIST. ANCE (C)	F.C.	BEAM LGTH (L)	BEAM WIDTH (W)
45W PAR38 NSP (T-H)	6°	8,500	2,000	7' 10' 13' 16'	173 85 50 33	0.7' 1.0' 1.4' 1.7'	0.7' 1.0' 1.4' 1.7'	6' 9' 12' 15'	3.5' 5.2' 6.9' 8.7'	153 68 38 25	0.8' 1.3' 1.7' 2.1'	0.7' 1.1' 1.5' 1.8'	4' 6' 8' 10'	4.0' 6.0' 8.0' 10.0'	188 83 47 30	0.8' 1.3' 1.7' 2.1'	0.6' 0.9' 1.2' 1.5'	2' 3' 4' 5'	3.5' 5.2' 6.9' 8.7'	266 118 66 43	0.8' 1.3' 1.7' 2.1'	0.4' 0.6' 0.8' 1.0'
45W PAR38 SP (T-H)	14°	4,700	2,000	6' 8' 10' 12'	131 73 47 33	1.5' 2.0' 2.5' 2.9'	1.5' 2.0' 2.5' 2.9'	5' 7' 9' 11'	2.9' 4.0' 5.2' 6.4'	122 62 38 25	1.6' 2.3' 3.0' 3.6'	1.4' 2.0' 2.6' 3.1'	3' 5' 7' 9'	3.0' 5.0' 7.0' 9.0'	185 66 34 21	1.5' 2.5' 3.5' 4.5'	1.0' 1.7' 2.4' 3.1'	2' 3' 4' 5'	3.5' 5.2' 6.9' 8.7'	147 65 37 24	2.1' 3.1' 4.1' 5.1'	1.0' 1.5' 2.0' 2.5'
45W PAR38 FL (T-H)	28°	1,700	2,000	3' 5' 7' 9'	189 68 35 21	1.5' 2.5' 3.5' 4.5'	1.5' 2.5' 3.5' 4.5'	3' 5' 7' 9'	1.7' 2.9' 4.0' 5.2'	123 44 23 14	2.0' 3.4' 4.8' 6.1'	1.7' 2.9' 4.0' 5.2'	2' 3' 4' 5'	2.0' 3.0' 4.0' 5.0'	150 67 38 24	2.1' 3.2' 4.3' 5.3'	1.4' 2.1' 2.8' 3.5'	1' 2' 3' 4'	1.7' 3.5' 5.2' 6.9'	213 53 24 13	2.5' 4.9' 7.4' 9.8'	1.0' 2.0' 3.0' 4.0'
75W PAR38 SP	12°	5,200	2,000	6' 8' 10' 12'	144 81 52 36	1.3' 1.7' 2.1' 2.5'	1.3' 1.7' 2.1' 2.5'	5' 7' 9' 11'	2.9' 4.0' 5.2' 6.4'	135 69 42 28	1.4' 2.0' 2.5' 3.1'	1.2' 1.7' 2.2' 2.7'	3' 5' 7' 9'	3.0' 5.0' 7.0' 9.0'	204 74 38 23	1.3' 2.1' 3.0' 3.8'	0.9' 1.5' 2.1' 2.7'	2' 3' 4' 5'	3.5' 5.2' 6.9' 8.7'	163 72 41 26	2.5' 4.7' 6.4' 8.3'	0.8' 1.3' 1.7' 2.1'
75W PAR38 FL	30°	1,860	2,000	4' 6' 8' 10'	116 52 29 19	2.1' 3.2' 4.3' 5.4'	2.1' 3.2' 4.3' 5.4'	3' 5' 7' 9'	1.7' 2.9' 4.0' 5.2'	134 44 25 15	2.2' 3.7' 5.1' 6.6'	1.9' 3.1' 4.3' 5.6'	3' 4' 5' 6'	3.0' 4.0' 5.0' 6.0'	73 41 26 18	3.5' 4.6' 5.8' 6.9'	2.3' 3.0' 3.8' 4.5'	1' 2' 3' 4'	1.7' 3.5' 5.2' 6.9'	233 58 26 15	2.7' 5.7' 8.2' 10.9'	1.1' 2.1' 3.2' 4.3'
90W PAR38 NSP (T-H)	7°	19,000	2,000	10' 15' 20' 25'	190 84 47 30	1.2' 1.8' 2.4' 3.1'	1.2' 1.8' 2.4' 3.1'	8' 12' 16' 20'	4.6' 6.9' 9.2' 11.5'	193 86 48 31	1.3' 2.0' 2.6' 3.3'	1.1' 1.7' 2.3' 2.8'	6' 9' 12' 15'	6.0' 9.0' 12.0' 15.0'	187 83 47 30	1.5' 2.2' 2.9' 3.7'	1.0' 1.6' 2.1' 2.6'	4' 6' 8' 10'	6.9' 10.4' 13.9' 17.3'	148 66 37 24	2.0' 3.0' 4.0' 4.9'	1.0' 1.5' 2.0' 2.4'
90W PAR38 SP (T-H)	12°	12,000	2,000	8' 12' 16' 20'	187 83 47 30	1.7' 2.5' 3.4' 4.2'	1.7' 2.5' 3.4' 4.2'	7' 10' 13' 16'	4.0' 5.8' 7.5' 9.2'	159 78 46 30	2.0' 2.8' 3.7' 4.5'	1.7' 2.4' 3.2' 3.9'	5' 7' 9' 11'	5.0' 7.0' 9.0' 11.0'	170 87 52 35	2.1' 3.0' 3.8' 4.7'	1.5' 2.1' 2.7' 3.3'	3' 4' 5' 6'	5.2' 6.9' 8.7' 10.4'	167 94 60 42	2.6' 3.5' 4.3' 5.2'	1.3' 1.7' 2.1' 2.5'
90W PAR38 FL (T-H)	30°	4,000	2,000	6' 8' 10' 12'	111 62 40 28	3.2' 4.3' 5.4' 6.4'	3.2' 4.3' 5.4' 6.4'	5' 7' 9' 11'	2.9' 4.0' 5.2' 6.4'	104 53 32 21	3.7' 5.1' 6.6' 8.1'	3.1' 4.3' 5.6' 6.8'	3' 5' 7' 9'	3.0' 5.0' 7.0' 9.0'	157 57 29 17	3.5' 5.8' 8.1' 10.4'	2.3' 3.8' 5.3' 6.8'	2' 3' 4' 5'	3.5' 5.2' 6.9' 8.7'	125 56 31 20	5.5' 8.2' 10.9' 13.7'	2.1' 3.2' 4.3' 5.4'
150W PAR38 SP	14°	10,500	2,000	8' 12' 16' 20'	164 73 41 26	2.0' 2.9' 3.9' 4.9'	2.0' 2.9' 3.9' 4.9'	7' 10' 13' 16'	4.0' 5.8' 7.5' 9.2'	139 68 40 27	2.3' 3.3' 4.3' 5.3'	2.0' 2.8' 3.7' 4.5'	5' 7' 9' 11'	5.0' 7.0' 9.0' 11.0'	148 76 46 31	2.5' 3.5' 4.5' 5.5'	1.7' 2.4' 3.1' 3.8'	3' 4' 5' 6'	5.2' 6.9' 8.7' 10.4'	146 82 53 36	3.1' 4.1' 5.1' 6.1'	1.5' 2.0' 2.5' 2.9'
150W PAR38 NSP (T-H)	9°	37,500	3,000	10' 15' 20' 25'	375 167 94 60	1.6' 2.4' 3.1' 3.9'	1.6' 2.4' 3.1' 3.9'	8' 12' 16' 20'	4.6' 6.9' 9.2' 11.5'	381 169 95 61	1.7' 2.5' 3.4' 4.2'	1.5' 2.2' 2.9' 3.6'	6' 9' 12' 15'	6.0' 9.0' 12.0' 15.0'	368 164 92 59	1.9' 2.9' 3.8' 4.8'	1.3' 2.0' 2.7' 3.3'	4' 6' 8' 10'	6.9' 10.4' 13.9' 17.3'	293 130 73 47	2.6' 3.8' 5.1' 6.4'	1.3' 1.9' 2.5' 3.1'
150W PAR38 SP (T-H)	10°	22,000	3,000	10' 15' 20' 25'	220 98 55 35	1.7' 2.6' 3.5' 4.4'	1.7' 2.6' 3.5' 4.4'	8' 12' 16' 20'	4.6' 6.9' 9.2' 11.5'	223 99 56 36	1.9' 2.8' 3.7' 4.7'	1.6' 2.4' 3.2' 4.0'	6' 9' 12' 15'	6.0' 9.0' 12.0' 15.0'	216 96 54 35	2.1' 3.2' 4.2' 5.3'	1.5' 2.2' 3.0' 3.7'	4' 6' 8' 10'	6.9' 10.4' 13.9' 17.3'	172 76 43 28	2.9' 4.3' 5.7' 7.2'	1.4' 2.1' 2.8' 3.5'
150W PAR38 FL	30°	4,000	2,000	6' 8' 10' 12'	111 62 40 28	3.2' 4.3' 5.4' 6.4'	3.2' 4.3' 5.4' 6.4'	5' 7' 9' 11'	2.9' 4.0' 5.2' 6.4'	104 53 32 21	3.7' 5.1' 6.6' 8.1'	3.1' 4.3' 5.6' 6.8'	3' 5' 7' 9'	3.0' 5.0' 7.0' 9.0'	157 57 29 17	3.5' 5.8' 8.1' 10.4'	2.3' 3.8' 5.3' 6.8'	2' 3' 4' 5'	3.5' 5.2' 6.9' 8.7'	125 56 31 20	5.5' 8.2' 10.9' 13.7'	2.1' 3.2' 4.3' 5.4'
150W PAR38 FL (T-H)	30°	7,000	3,000	7' 10' 13' 16'	143 70 41 27	3.8' 5.4' 7.0' 8.6'	3.8' 5.4' 7.0' 8.6'	6' 9' 12' 15'	3.5' 5.2' 6.9' 8.7'	126 56 32 20	4.4' 6.6' 8.8' 11.0'	3.7' 5.6' 7.4' 9.3'	4' 6' 8' 10'	4.0' 6.0' 8.0' 10.0'	155 69 39 25	4.6' 6.9' 9.2' 11.5'	3.0' 4.5' 6.1' 7.6'	2' 3' 4' 5'	3.5' 5.2' 6.9' 8.7'	219 97 55 35	5.5' 8.2' 10.9' 13.7'	2.1' 3.2' 4.3' 5.4'

(FC) is the initial footcandles at the center of the beam.
(L) and (W) are to the point that the candlepower drops to 50% of maximum.

Job Information **Type:**

Lightolier a Genlyte Thomas Company www.lightolier.com
631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
We reserve the right to change details of design, materials and finish.
© 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902

LIGHTOLIER®