



Ordering Information

Catalog No.	Mounting	Finish	Lamps
6415	All Lytespan Track Systems	Matte White	20W-50W MR-16 12V
6416		Matte Black	

Features

- Lytespan Attachment Fitting:** Molded polycarbonate. Integral color. Fitting twists onto track and locks on.
- Housing:** .040" aluminum.
- Step Baffle:** Die-cast aluminum with stepped conical surface for low brightness. Matte black finish.
- Trunion Mounting:** Tensioned with internal spring washer and vibration-resistant nut.
- Pivot Mounting:** Tensioned; 350° stop for horizontal rotation.
- Movable Brass Contact:** Extends for connection to 2nd circuit in Advent Lytespan Track.
- Polarity Key**
- Push Tab:** Molded polycarbonate. Detaches unit.
- Yoke:** Extruded aluminum.
- Lamp Guard:** Tempered glass.
- Face Plate:** Die-cast aluminum. Matte black finish.

Electrical/Dimming

Low voltage magnetic transformer designed to operate continuously. 12V operating voltage. Two-pin base socket, No. 18 braided SF-1 leads. For dimming control, use only dimmers or specifically designed for use with transformers, such as Lightolier Lytemode, Scenist or Precision LV Series or equivalent.

Options & Accessories

2" Series Color Filters and Spread Lens.

Finish

All painted finishes baked enamel.

Labels

UL, I.B.E.W.

Patents

U.S. Patent No. 3,496,518. Foreign patents granted.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Volts/Ballast:	

Lightolier a Genlyte Thomas Company www.lightolier.com
 Technical Information: (978) 657-7600 • Fax (978) 658-0595
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 © 2002 Genlyte Thomas Group LLC (Lightolier Division)
 A0902

LIGHTOLIER®

