



Ordering Guide (complete unit only)

| Cat. No. | Lamp (circular) | Volt | Finish |
|-----------|-------------------|----------|--|
| SL203APZU | 1-22W / 1-40W CT5 | 120/277V | Anodized Aluminum & Sand Blasted Glass |

Features

- Form:** Round form fabricated from slitted corrugated anodized aluminum. Slits hold the sand blasted glass and reflector element. The illuminated edge of the glass is visible through the corrugations.
- Glass:** Center sand blasted glass with clear outer ring. Image of lamps seen through the glass to create a geometric pattern on the wall or ceiling.
- Housing:** Spun painted steel construction. Mounting plate houses the ballast and lamp sockets.

Mounting

Mounting: Surface mounting to wall or ceiling surfaces.

Lamp Change: Fluted housing simply twists-off. Held in place by 3 locking pins.

Luminaire Weight: 10.5 lbs.

Electrical

Ballast: Electronic Program Rapid Start T5 circular lamps ballast. Universal voltage "U" ballast automatically detect 120 volts or 277 volts operation. Ballast use cathode heater shut-off to increase T5 round lamp life.

Lampholder: 2GX13 base, 4 Pin.

Options and Accessories

Double Switching: Consult your Lightolier representative for more information.

Perforated Form: Consult your Lightolier representative for more information.

Dimming Ballast: Consult your Lightolier representative for more information.

Finish

Anodized corrugated aluminum sheet with precise flutes. All painted parts are with powder coat paint process.

Labels

UL "c/us" Listed. Suitable for damp locations.

| Job Information | Type: |
|------------------|-------|
| Job Name: | |
| Cat. No.: | |
| Lamp(s): | |
| Notes: | |