



### Ordering Information

Catalog No.	Finish	Track Mountings	Lamping
FXPDT	Silver	For use on all Tangent Track systems. For ceiling or suspended track installation. Not for use on wall mounted track.	100W Max

### Features

- Track Attachment fitting:** Molded thermoplastic clamping adapter with captive, nickel-plated steel pin. Clockwise rotation of pin secures fixture adapter to track.
- Splicing Chamber:** Allows for field cutting of power cord and aircraft cable (if applicable).

#### For use only with pendants that meet the following criteria:

- Total weight of all components being attached to adaptor does not exceed 2.5 lbs.
- Pendant Cord Type is 1/4" dia. 18 ga. 3-wire, 300V min. SVT, with .062 dia. aircraft cable, or without aircraft cable.
- Pendant is rated 120V/60Hz., .83A max, 100W max.

### Finish

All Painted finishes are baked enamel.

### Accessories

No accessory capability.

### Labels

cULus Listed

Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	

Lightolier a Genlyte company www.lightolier.com  
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 © 2007 Genlyte Group LLC • 0907