



Ordering Information: Complete fixture consists of Powerhead + Inner Glass + Outer Glass + Suspension Kit. Each sold separately (ie **PS13SA** + **SG03** + **GLS03** + **SK01**).

Spec ID (reference only)	Powerhead	Inner Glass	Outer Glass	Suspension Kit	Lamp	Volts
FA03	PS13SA	SG03	GLS03	*See suspensions below	4-Pin Elect. Twin Tube 13W	120V
FA203	PS132SA	SG03	GLS03		4-Pin Elect. Twin Tube 13W	277V
FA03Q	PS130SA	SG03	GLS03		4-Pin Quad Tube 13W	120V
FA203Q	PS132QSA	SG03	GLS03		4-Pin Quad Tube 13W	277V
FA0326	PS26SA	SG03	GLS03		4-Pin Quad Tube 26W	277V
FA20326	PS262SA	SG03	GLS03		4-Pin Quad Tube 26W	277V
IA03	PS50SA	SG03	GLS03		T-4 Mini Can. 50W	120V

Suspension Kits:

Cat. No	Finish	Description
SK01	Satin Aluminum	Clear Metallic Straight Cord/Cable, 120" Length, (10') with canopy
SK02	Satin Aluminum	Clear Metallic Straight Cord/Cable, 300" Length, (25') with canopy
ST01	Satin Aluminum	36" Length 3/8" Stem with canopy
ST02	Satin Aluminum	60" Length 3/8" Stem with canopy
CTC	Satin Aluminum	Close to Ceiling Kit with canopy
TM01	Satin Aluminum	Silver Track Mounting Kit with Clear Metallic Straight Cord/Cable, 120" Length, (10') (120V only)

Features

- Power Compartment:** Die Cast and Machined Aluminum Components. Brushed and Clear Lacquer Finish.
- Primary Glass:** Triplex Hand Blown Glass.
- Decorative Glass Assembly:** A conical section of clear hand blown glass with polished edges, die-cast aluminum holder ring and stainless steel support pins.

Lamping (by others)

Incandescent: 50W Max. T-4 Mini Candelabra

Fluorescent: 13W 4-Pin Electronic Twin Tube Specify Lightolier #56964

(**see chart below)

****Compact Fluorescent:**

General Electric	Osram/Sylvania	Philips
(1) 13W Twin Tube 4-Pin Compact Fluorescent Lamp		
N/A	CF13DS/E/*	N/A
(1) 13W Quad Tube 4-Pin Compact Fluorescent Lamp		
F13DBX/SPX*/4P	CF13DD/E/*	PL-C13W/*/4P/ALTO
(1) 26W Quad Tube 4-Pin Compact Fluorescent Lamp		
F26BX/*EC04P	CF26DD/E/*	PL-C26W/*/4P/ALTO

*Manufacturers Color Temperature Designation

Electrical

Lampholders

Incandescent: E11 Base, Porcelain, Plated Copper Alloy Screw Shell

Compact Fluorescent: 13W Twin: 2GX7 Base, High Impact Thermoset Polymer with Brass Contacts.

Electrical (continued)

13W Quad: GX242-1 Base, High Impact Thermoset Polymer with Brass Contacts.

26W Quad: GX24Q-3 High impact thermoset polymers with brass contacts.

Ballasts: Fluorescent: Electronic	13 Watts	
Voltage	120	277
Max. Watts	18	14
Max. Line Current (Amps)	.33	.18

Labels

cULus Listed. Suitable for Damp Locations.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

www.lightolier.com © 2008 Philips Group • B0508