# **RECESSED GRID CEILING MOUNT**

w/ OPEN HOUSING PAR30

## DESCRIPTION:

An adjustable PAR30 fixture suitable for multiple downlighting applications with one point of electrical entry. For use in lay-in t-bar grid style ceilings. Powder coat finish on housing & lamp assembly.

## CONSTRUCTION:

Housing Assembly: 18 gauge CRS. J-Box Assembly: 16 gauge CRS (galvanized). Fixture utilizes specially developed retaining clips for snap-in mounting directly to t-bar supports. Tabs on housing top accommodate above ceiling aircraft cable support for added stability.

## LAMP ASSEMBLY:

Two PAR30 lamps mounted in adjustable bezels. Each lamp can accept up to two optical accessories. 380° x 45° locking lamp adjustment. Provides 45° visual cut-off.

## SYSTEM PROTECTION:

Thermal protection provided to guard against overheating, and misuse of insulation over and around fixture. Vent holes in housing provide cooler operation

## **ELECTRICAL**:

Junction box is UL listed for through branch wiring, (access above ceiling not required) for 8 #12, 90°C supply conductors or 60°C for end of run. J-box and wiring accessible through ceiling opening.

ALL RSA COMBOLIGHT PRODUCTS ARE MADE IN THE U.S.A.




Catalog #

Type

Project

## COMBOLIGHT® GR Series

TWO (2) Light Recessed Multi-Lamp Luminaire for Lay-in, T-Bar Grid Style Ceiling Open Housing Aperture Line Voltage PAR30



Cat. # / Description	Interior Finish	Lamp Holder
<b>GR230</b> - 2 Light Recessed Combo for Lay-in Grid Style Ceilings 120V PAR30	<b>BK</b> - Black	YK - Regular Yoke (Standard)
	WH - White	RT - Retractable Yoke
	S - Silver	
	PT - Custom	
SPECIFY - GR230		