


MODEL H0591 MICRO DIE GRINDER INSTRUCTION SHEET



Introduction

This Micro Die Grinder allows extreme flexibility in all kinds of environments. No-load speed is 56,000 RPM and requires 90 PSI of air pressure with 7 CFM of compressor capacity. Collet size is ½".

Inventory

| Α. | Micro Die Grinder | 1 |
|----|----------------------|---|
| B. | 1/4" NPT Air Fitting | 1 |
| | Collet Wrenches | |
| D. | Oil Bottle | 1 |

Operation

Insert your ½" tool bit into the collet and tighten with the collet wrenches provided. Make sure the tool you use is rated for 56,000 RPM or less. Connect air fitting to your regulated air source.




Figure 1. Model H0591.

Micro die grinder MUST have 3-4 drops of oil directly dropped into the air fitting before each use as shown in **Figure 2**.





Figure 2. Lubricating directly into air fitting.

If you need help with your new pneumatic tool, call our Tech Support at: (570) 546-9663.

H0591 Parts Breakdown and List



| REF | PART # | DESCRIPTION |
|-----|-----------|-------------------|
| 1 | PH0591001 | HOUSING PLUG |
| 2 | PH0591002 | REAR END HOLDER |
| 3 | PH0591003 | SCREW |
| 4 | PH0591004 | O-RING |
| 5 | PH0591005 | BUSHING |
| 6 | PH0591006 | SLIDING KNOB |
| 7 | PH0591007 | PIN |
| 8 | PH0591008 | INTAKE STEEL TUBE |
| 9 | PH0591009 | SLEEVE |
| 10 | PH0591010 | INTAKE PLATE |
| 11 | PH0591011 | BALL BEARING |
| 12 | PH0591012 | BEARING PLATE |
| 13 | PH0591013 | PIN |

| REF | PART # | DESCRIPTION |
|-----|-----------|--------------|
| 14 | PH0591014 | CYLINDER |
| 15 | PH0591015 | ROTOR BLADES |
| 16 | PH0591016 | ROTOR |
| 17 | PH0591017 | LATERAL |
| 18 | PH0591018 | SPACER |
| 19 | PH0591019 | BALL BEARING |
| 20 | PH0591020 | SPINDLE |
| 21 | PH0591021 | FRONT COVER |
| 22 | PH0591022 | COLLET |
| 23 | PH0591023 | COLLET NUT |
| 24 | PH0591024 | WRENCH SET |
| 25 | PH0591025 | OIL BOTTLE |