

## **GENERAL DESCRIPTION:**

Cast brass valve bodies with reinforced flexible hose connections for 6" to 12" (152mm to 305mm) installations. 1/4 turn washerless ceramic disc valve cartridges. Cast brass spout. One-half inch brass male inlets with brass coupling nuts. 20" (500mm) long flexible stainless steel drain cable is pre-assembled to faucet body. Metal Speed Connect<sup>™</sup> drain body with 1-1/4 inch (32mm) tail piece, (3875.409). Non-Metallic Speed Connect<sup>™</sup> drain body with 1-1/4 inch (32mm) tail piece, (3875.403). 2.2 gpm/8.3L/min. maximum flow rate.

## **PRODUCT FEATURES:**

**Brass Construction:** Durable. Ideal for prolonged contact with water.

**Ceramic Disc Valve Cartridges:** Assures a lifetime of smooth handle operation and drip-free performance.

**Low Lead:** Meets NSF Standard 61/Section 9 & Prop 65 lead requirements.

#### **Speed Connect Drain:**

- Fewer Parts installs in less time.
- No adjustments required seals the first time, every time.
- Flexible stainless steel cable installs effortlessly in tight spaces.

#### **Choice of Finishes**

### SUGGESTED SPECIFICATION:

Two handle widespread lavatory faucet shall feature cast brass valve bodies with reinforced flexible hose connections for 6" to 12" installations. Shall also feature 1/4 turn washerless ceramic disc valve cartridges. Shall also feature a drain body with stainless steel cable actuation. Fitting shall be American Standard Model # 3875.\_\_.


American Standard

# COLONY SOFT TWO-HANDLE WIDESPREAD LAVATORY FAUCET WITH ACRYLIC HANDLES

# **CODES AND STANDARDS**

These products meet or exceed the following codes and standards:

ASME A112.18.1 CSA B 125 NSF 61/Section 9



			Finish Options	
Product		Polished Chrome	PVD Polished Brass	
Number	Description	002	099	
3875.403	Lavatory faucet. With Lever Handles. Non-metallic Speed Connect™ Pop-up drain.			
3875.409	Lavatory faucet. With Lever Handles. Metal Speed Connect™ Pop-up drain.			