

PremierView15ID

15" XGA Multimedia LCD Monitor for Industrial, OEM and Desktop Use



Calibre specialises in high performance LCD display solutions for industrial, surveillance, OEM, military, aerospace and broadcast applications. PremierView monitors feature flexible signal capability, excellent motion reproduction and accurate, artifact free image re-sizing.

Calibre's PremierView15ID is a very high performance TFT-LCD display. Based around Calibre's proprietary PremierView4 LCD driver technology, it is able to connect directly to a very wide range of video or computer image sources and display images full screen on its 15" viewable diagonal, wide viewing angle screen.

PremierView4 is one of the most flexible LCD systems on the market able to accept a wide range of input resolutions. PremierView4 features true autoscanning real-time software algorithms to allow it to be adjusted to suit most non-standard resolutions and signal timings within its resolution, line and field rate ranges. Specific compatibility with non-standard signal timings and custom resolutions can also be provided as a customer specific option and special industrial models are available for use on ABB Mod300/Tesselator, CGA/EGA/BBC TTL signals & Siemens WF470. These are detailed on model-specific datasheets, please see our website or call your Calibre sales representative for full details.

PremierView15ID uses a 1024x768 TFT LCD panel for display of real-time Video or computer VGA-SXGA full screen, full-motion in real time. Through the standard VGA connector, composite sync and sync on green from high resolution sources such as workstations are also supported. A DVI digital graphics input is available as an optional extra.

A professional grade video decoder is available as an option which gives outstanding composite and YC video performance through the use of a 4-line comb filter and vertical noise reduction algorithm. This option also adds a selectable RGB/YUV component video input. SDI serial digital video with PAL or NTSC timings is also available as an additional option. **A lower cost standard grade video decoder is also available for less demanding applications.**

High performance scaling algorithms work without compromising image quality or resolution irrespective of the signal resolution implemented. It is compatible with Composite and Y/C (SVHS, S-video) inputs with automatic detection of PAL, NTSC & SECAM video, and/or most computer RGB signals from 640x350 up to 1280x1024. Very flexible wide-ranging picture controls are provided via an on-screen menu. These controls include picture size/position controls as well as contrast, brightness, and colour/hue for video.

PremierView15ID uses a premium grade high-brightness high-contrast 15" TFT-LCD panel with 24-bit per pixel colour depth and very wide viewing angles. This ensures maximum colour depth and accurate grey-scale reproduction, with no field merging, no field dropping or repetition and no pixel or line dropping to ensure **accurate motion reproduction and clean image scaling.**

PremierView15ID comes as a metal cased display unit or as an OEM open chassis module. The metal cased display unit incorporates side mounting points and VESA-compatible rear mountings. Cased units include an anti-scratch, anti-glare front viewing window. Touchscreens are also available for all models. Optional accessories include a desk stand, wall mounts, telescopic arm mount and 19" rackmount adapter.

Technical Information

Panel Specification:

Viewable image size 38cm/15" nominal.
Panel resolution 1024x768.
Colour depth 24-bits per pixel
Viewing angles 70 deg L/R, 55U/60D typical
Panel brightness 450cd/m² nominal.
Panel contrast ratio 400:1 typical.

Signal compatibility:

Input 1 – computer RGB via 15HDD socket.
640x350 up to 1280x1024, 50-75Hz refresh, non-interlaced. (Note: 1280x1024 support is via image downscaling to fit the 1024x768 resolution panel. There may be a slight loss of image quality in downscale mode.)

Syncs: separate TTL/5V positive or negative, negative combined sync TTL level, or negative sync on green consisting of 0.3V sync and 0.7V video.

Input 2 – composite video via BNC
PAL, NTSC or SECAM, automatic standards detection. Pro Video model has automatic enhanced-bandwidth monochrome mode.

Input 3 – YC/S-Video via 4-pin Mini-DIN
PAL, NTSC or SECAM, automatic standards detection.

Input 4 – Pro Video Option Only
RGB or YUV component video via 3 or 4 BNCs.

Input 5 – Pro Video with SDI Option Only
SDI Serial Digital Video via BNC.

Input 6 – DVI Option Only
DVI Digital Visual Interface, DDC2B compatible for connection to DVI compatible graphics cards.

Touchscreen option:

Resistive touchscreen with RS232 serial controller available to special order. Touchscreen has anti-glare finish, fitted in place of anti-scratch anti-glare viewing window.

Power requirement:

12VDC at approximately 40W.

An optional mains PSU is available.

Other power options available to order include ground isolated 12VDC, 24VDC and, 28VDC with optional industrial or military grade power filtering.

Model numbers:

38XLCD26 xx y zz

| | |
| | | -M3 = industrial metal case
| | | -SC = open chassis
| | |
| | | -G6 = 450cd/m2 panel
| | |
|-01 = VGA analogue only
|-02 = VGA analogue + DVI
|-03 = VGA analogue & Std Video
|-04 = 03 + DVI
|-05 = VGA analogue & Pro Video
|-06 = 05 + DVI
|-09 = 05 + SDI Video
|-10 = 05 + DVI + SDI Video
|-11 = Standard video only
|-13 = Professional video only
|-14 = Pro Video + SDI
|-16 = 05 without RGB/YUV input

Dimensions and Weights:

Metal cased units

Size 366x307x61mm
Unit weight 5Kg, Shipping weight 8Kg
Excluding Optional Desk-Stand

Open chassis

Approximate Size 332x261x46mm
Unit weight 3Kg, Shipping weight 8Kg

Calibre UK Ltd
Cornwall House,
Cornwall Terrace,
Bradford, West Yorkshire
BD8 7JS, England

Tel +44 (0)1274 394125
Fax +44 (0)1274 730960
E-mail sales@calibreuk.com
Web-site www.calibreuk.com

