




BLACK BOX[®]

NETWORK SERVICES

© 2005. All rights reserved.
Black Box Corporation.

Black Box Corporation • 1000 Park Drive • Lawrence, PA 15055-1018 • Tech Support: 724-746-5500 • www.blackbox.com • e-mail: info@blackbox.com

MULTI-FUNCTION LINE DRIVER



Use this line driver in just about any RS-232 UTP or STP application.

Key Features

- ▶ **Speeds up to 38.4 kbps.**
- ▶ **Distances up to 6 miles (9.7 km).**
- ▶ **Async or sync operation, point-to-point or multipoint.**
- ▶ **Transformer isolation and surge protection.**

Operating asynchronously or synchronously, the Multi-Function Line Driver supports data rates up to 38.4 kbps and distances up to 6 miles (9.7 km).

The line driver will operate over 4 wires in point-to-point or multipoint environments. In synchronous mode, the Multi-

Function Line Driver supports internal, external, or receive loopback clocking.

Two V.54 and two V.52 BER test modes can be activated via the RS-232 interface. Built-in LEDs let you monitor test mode operation. With transformer

isolation and surge protection, your data is safe.

The Multi-Function Line Driver is designed to plug directly into the RS-232 interface. Twisted-pair wire is connected using an RJ-45 connector or terminal blocks with strain relief.

Specifications

Clocking: Internal, external, receive
Distance (Maximum): 6 mi. (9.7 km)
Speed (Maximum): 38.4 kbps
Line Type: (2) twisted pair
Operation: 4-wire, full duplex, point-to-point, or multipoint
Protocol: Asynchronous or synchronous
Interface: RS-232 (DCE)

Connectors: ME657A-M:
(1) DB25 M, (1) terminal block;
ME657A-F: (1) DB25 F,
(1) terminal block;
ME659A-F: (1) DB25 F, (1) RJ-45
Indicators: BERT, Loop
Power: 6 VDC from the interface,
Pins 4, 9, 20
Size: 0.8"H x 2.1"W x 3"D (2 x 5.3 x
7.6 cm)
Weight: 0.1 lb. (<0.1 kg)

Ordering Information

ITEM	CODE
Multi-Function Line Driver	
DB25 Male, Terminal Block.....	ME657A-M
DB25 Female, Terminal Block.....	ME657A-F
DB25 Female, RJ-45.....	ME659A-F