


Overview

AT A GLANCE

- All-in-one form factor with three spindle support
- Intel Mobile Pentium® II processor up to 400 MHz
- Up to 14.1-inch CTFT display supporting resolutions up to 1024 x 768
- 64-MB standard SDRAM, expandable up to 192 MB
- MultiBay supports additional battery, second hard drive, floppy diskette drive (standard), SuperDisk LS-120 Drive or Zip Drive
- Up to 10-GB¹ upgradable SMART Hard Drives
- Internal 24X Max² CD-ROM Drive upgradable to DVD-ROM
- Integrated 56K v.90³ fax modem
- Sound Blaster Pro-compatible with 16-bit stereo Compaq Premier[®] Sound[™], integrated speakers and microphone
- Intelligent Manageability for lower total cost of ownership
- Optional Pass-Through or Ethernet Convenience Bases
- Compaq Services, including a one-year, Worldwide Limited Warranty⁴ with second business day⁵ expedited pick-up and repair in North America



- | | |
|---|--|
| 1. Power Button | 12. 24X Max ² CD-ROM Drive upgradable to DVD-ROM Drive |
| 2. Microphone | 13. MultiBay (supports floppy drive, additional battery, second Hard Drive, Zip Drive, SuperDisk LS-120 Drive) |
| 3. 4 MB/s ⁶ Infrared Communication Port | 14. Memory Slot |
| 4. Integrated AC Adapter | 15. Stereo Speakers |
| 5. Processor Board | 16. Touchpad Pointing Device |
| 6. TV Out | 17. Full-size Keyboard with Four User-Programmable Keys |
| 7. USB Port | 18. Stand-by Button |
| 8. Integrated 56K V.90 ³ Worldwide Modem | 19. Display |
| 9. Two Type II/One Type III PC Card Slots; CardBus-capable ⁷ | |
| 10. Li-Ion Battery Pack | |
| 11. Upgradable SMART Hard Drive | |

Standard Features

MODELS

Windows NT Workstation 4.0 and Integrated Modem

6400/T14/10.0/D/M/3
316590-xx6

6366/T14/6400/D/M/3
316570-xx6

6333/T14/6400/D/M/3
120398-xx6

6366/T14/4000/D/M/3
129014-xx6

6333/T14/6400/D/M/3
316550-xx6

6333/T14/4000/D/M/3
129012-xx6

6300/T14/4000/D/M/3
316530-xx6

Windows NT Workstation 4.0 Non-Modem

6400/T14/10.0/D/O/3
316580-xx6

6366/T14/6400/D/O/3
316560-xx6

6366/T14/4000/D/O/3
129013-xx6

6333/T14/6400/D/O/3
120397-xx6

6333/T14/6400/D/O/3
316540-xx6

6333/T14/4000/D/O/3
129011-xx6

6300/T14/4000/D/O/3
316520-xx6

Windows 98 and Integrated Modem

6400/T14/10.0/D/M/2
316590-xx4

6366/T14/6400/D/M/2
316570-xx4

All-in-one Design

All-in-one design includes integrated Diskette Drive, Hard Drive, CD-ROM Drive, modem and AC Adapter, providing full functionality in the office or on the road; MultiBay supports diskette drive, second hard drive, second battery, SuperDisk LS-120 Drive or Zip drive for additional flexibility.

Processor

Intel Mobile Pentium II processor 400 MHz

6400/T14/10.0/D/M/3
6400/T14/10.0/D/M/2
6400/T14/10.0/D/M/1
6400/T14/10.0/D/O/3
6400/T14/10.0/D/O/2
6400/T14/10.0/D/O/1

Intel Mobile Pentium II processor 366 MHz

6366/T14/6400/D/M/3
6366/T14/6400/D/M/2
6366/T14/6400/D/M/1
6366/T14/6400/D/O/3
6366/T14/6400/D/O/2
6366/T14/6400/D/O/1
6366/T14/4000/D/M/3
6366/T14/4000/D/M/2
6366/T14/4000/D/M/1
6366/T14/4000/D/O/3
6366/T14/4000/D/O/2
6366/T14/4000/D/O/1

Intel Mobile Pentium II processor 333 MHz

6333/T14/6400/D/M/3
6333/T14/6400/D/M/3
6333/T14/6400/D/M/2
6333/T14/6400/D/M/1
6333/T14/6400/D/O/3
6333/T14/6400/D/O/3
6333/T14/6400/D/O/2
6333/T14/6400/D/O/1
6333/T14/6400/D/O/1
6333/T14/4000/D/M/3
6333/T14/4000/D/M/2
6333/T14/4000/D/M/1
6333/T14/4000/D/O/3
6333/T14/4000/D/O/2
6333/T14/4000/D/O/1

Intel Mobile Pentium II processor 300 MHz

6300/T14/4000/D/M/3
6300/T14/4000/D/M/2
6300/T14/4000/D/M/1
6300/T14/4000/D/O/3
6300/T14/4000/D/O/2
6300/T14/4000/D/O/1

Cache Memory

Integrated 256 KB L2

Memory

Standard 64 MB
Maximum 192 MB

Standard Features

MODELS (continued)

Windows 98 and Integrated

Modem (continued)

6366/T14/6400/D/M/2
129014-xx4

6333/T14/D/M/2
120398-xx4

6333/T/6400/D/M/2
316550-xx4

6333/T/4000/D/M/2
129012-xx4

6300/T/4000/D/M/2
316530-xx4

Windows 98 Non-Modem

6400/T14/10.0/D/0/2
316580-xx4

6366/T14/6400/D/0/2
316560-xx4

6333/T14/6400/D/0/2
120397-xx4

6366/T/4000/D/0/2
129013-xx4

6333/T/6400/D/0/2
316540-xx4

6333/T4000/D/0/2
129011-xx4

6300/T/4000/D/0/2
316520-xx4

Windows 95 and Integrated

Modem

6400/T14/10.0/D/M/1
316590-xx2

6366/T14/6400/D/M/1
316570-xx2

6366/T/4000/D/M/1
129014-xx2

6333/T14/6400/D/M/1
120398-xx2

6333/T/6400/D/M/1
316550-xx2

6333/T/4000/D/M/1
129012-xx2

6300/T/4000/D/M/1
316530-xx2

(continued next page)

Communications

Integrated v.90/K56flex³ data/14.4 Kb/s fax modem with full-duplex speakerphone

Keyboard

101/102-key compatible keyboard with isolated, inverted-T cursor control keys, and right-control key, four user-programmable keys, special feature hotkeys for instant access to power conservation, QuickLock/QuickBlank, toggle between internal and external, or simultaneous displays, battery gauge, speaker volume control, brightness and contrast

Pointing Device

Touchpad

PC Card Slots

Two Type II/One Type III PC Card Slot(s) which support both 32-bit CardBus⁷ and 16-bit PC Cards; zoomed video support in bottom slot only

Storage

Removable Diskette Drive 1.44 MB

CD-ROM 24X Max²

Hard Drives

10-GB¹ SMART

6400/T14/10.0/D/M/3
6400/T14/10.0/D/M/2
6400/T14/10.0/D/M/1
6400/T14/10.0/D/0/3
6400/T14/10.0/D/0/2
6400/T14/10.0/D/0/1

6.4-GB¹ SMART

6366/T/6400/D/M/3
6366/T/6400/D/M/2
6366/T/6400/D/M/1
6366/T/6400/D/0/3
6366/T/6400/D/0/2
6366/T/6400/D/0/1
6333/T14/6400/D/M/3
6333/T/6400/D/M/3
6333/T14/6400/D/M/2
6333/T/6400/D/M/2
6333/T14/6400/D/M/1
6333/T/6400/D/M/1
6333/T14/6400/D/0/3
6333/T/6400/D/0/3
6333/T14/6400/D/0/2
6333/T/6400/D/0/2
6333/T14/6400/D/0/1
6333/T/6400/D/0/1

Standard Features

MODELS (continued)

Windows 95 Non-Modem

(continued)

6400/T14/10.0/D/0/1

316580-xx2

6366/T14/6400/D/0/1

316560-xx2

6366/T/4000/D/0/1

129013-xx2

6333/T14/6400/D/0/1

120397-xx2

6333/T/6400/D/0/1

316540-xx2

6333/T/4000/D/0/1

129011-xx2

6300/T/4000/D/0/1

316520-xx2

Storage (continued)

Hard Drives

4-GB¹ SMART

6366/T/4000/D/M/3

6366/T/4000/D/M/2

6366/T/4000/D/M/1

6366/T/4000/D/0/3

6366/T/4000/D/0/2

6366/T/4000/D/0/1

6333/T/4000/D/M/3

6333/T/4000/D/M/2

6333/T/4000/D/M/1

6333/T/4000/D/0/3

6333/T/4000/D/0/2

6333/T/4000/D/0/1

6300/T/4000/D/M/3

6300/T/4000/D/M/2

6300/T/4000/D/M/1

6300/T/4000/D/0/3

6300/T/4000/D/0/2

6300/T/4000/D/0/1

Multimedia

Compaq Premier•Sound for enhanced stereo audio, including integrated 16-bit Sound Blaster Pro-compatible stereo audio, integrated acoustic bass reflex stereo speakers with 2-Watt/channel amplifier and 4 stage EQ. Microphone, software/hardware volume control, headphone out, microphone in jacks support; internal 24X Max² CD-ROM Drive or DVD-ROM Drive

Interfaces

PC Card	Two Type II/One Type III
Enhanced Parallel	1
Serial	1
External Monitor	1
External Keyboard/ Pointing Device	1
Convenience Base	1
Headphone/Line-out	1
Microphone	1
AC Power	1
RJ-11	1
Infrared	1 (4 Mb/s ⁶ support)
USB	1

Graphics

64-bit video graphics with 4-MB SGRAM for increased color depth and graphics performance

Standard Features

Display

14.1-inch color TFT with 1024 x 768 resolution (up to 16.7M colors internal)

6400/T14/10.0/D/M/3
6400/T14/10.0/D/M/2
6400/T14/10.0/D/M/1
6400/T14/10.0/D/O/3
6400/T14/10.0/D/O/2
6400/T14/10.0/D/O/1
6366/T14/6400/D/M/3
6366/T14/6400/D/M/2
6366/T14/6400/D/M/1
6366/T14/6400/D/O/3
6366/T14/6400/D/O/2
6366/T14/6400/D/O/1
6333/T14/6400/D/M/3
6333/T14/6400/D/M/2
6333/T14/6400/D/M/1
6333/T14/6400/D/O/3
6333/T14/6400/D/O/2
6333/T14/6400/D/O/1

13.3-inch color TFT with 1024 x 768 resolution (up to 16.7M colors internal)

6333/T/6400/D/M/3
6333/T/6400/D/M/2
6333/T/6400/D/M/1
6333/T/6400/D/O/3
6333/T/6400/D/O/2
6333/T/6400/D/O/1
6300/T/4000/D/M/3
6300/T/4000/D/M/2
6300/T/4000/D/M/1
6300/T/4000/D/O/3
6300/T/4000/D/O/2
6300/T/4000/D/O/1

12.1-inch color TFT with 800 x 600 resolution (up to 16.7M colors internal)

6366/T/4000/D/M/3
6366/T/4000/D/M/2
6366/T/4000/D/M/1
6366/T/4000/D/O/3
6366/T/4000/D/O/2
6366/T/4000/D/O/1
6333/T/4000/D/M/3
6333/T/4000/D/M/2
6333/T/4000/D/M/1
6333/T/4000/D/O/3
6333/T/4000/D/O/2
6333/T/4000/D/O/1

Standard Features

Software

Windows NT Workstation 4.0
Insight Management Agents
Intelligent Manageability
Security 32
Diagnostics for Windows NT
Compaq Power Management
Online Safety and Comfort Guide
Reference Guide
Carbon Copy

6400/T14/10.0/D/M/3
6400/T14/10.0/D/O/3
6366/T14/6400/D/M/3
6366/T14/6400/D/O/3
6333/T14/6400/D/M/3
6333/T14/6400/D/O/3
6366/T/4000/D/M/3
6366/T/4000/D/O/3
6333/T/6400/D/M/3
6366/T/6400/D/M/3
6366/T/6400/D/O/3
6333/T14/6400/D/M/3
6333/T/6400/D/M/3
6333/T14/6400/D/O/3
6333/T/6400/D/O/3
6333/T/4000/D/M/3
6333/T/4000/D/O/3
6300/T/4000/D/M/3
6300/T/4000/D/O/3

Windows 98
Insight Management Agents
Intelligent Manageability
Security 32
Diagnostics for Windows 98
Compaq Power Management
Online Safety and Comfort Guide
Reference Guide
Carbon Copy

6400/T14/10.0/D/M/2
6400/T14/10.0/D/O/2
6366/T14/6400/D/M/2
6366/T14/6400/D/O/2
6366/T/4000/D/M/2
6366/T/4000/D/O/2
6366/T/6400/D/M/2
6366/T/6400/D/O/2
6333/T14/6400/D/M/2
6333/T/6400/D/M/2
6333/T14/6400/D/O/2
6333/T/6400/D/O/2
6333/T/4000/D/M/2
6333/T/4000/D/O/2
6300/T/4000/D/M/2
6300/T/4000/D/O/2

Standard Features

Software (continued)

Windows 95
Insight Management Agents
Intelligent Manageability
Security 32
Diagnostics for Windows 95
Compaq Power Management
Online Safety and Comfort Guide
Reference Guide
Carbon Copy
6400/T14/10.0/D/M/1
6400/T14/10.0/D/O/1
6366/T14/6400/D/M/1
6366/T14/6400/D/O/1
6366/T/4000/D/M/1
6366/T/4000/D/O/1
6366/T/6400/D/M/1
6366/T/6400/D/O/1
6333/T14/6400/D/M/1
6333/T/6400/D/M/1
6333/T14/6400/D/O/1
6333/T/6400/D/O/1
6333/T/4000/D/M/1
6333/T/4000/D/O/1
6300/T/4000/D/M/1
6300/T/4000/D/O/1

OS Support

Windows NT Workstation 4.0
Windows 98
Windows 95

Intelligent Manageability Software

Lowers total cost of ownership by providing enhanced security, asset management, and fault prediction with SMART drives. Also provides SMART drive alert, battery fault alert, thermal alert and memory alert for investment and data protection

Security

Cable lock support
Power-on password
Set-up passwords
Ability to disable serial port, parallel port, diskette drive, diskette drive boot sequence
Drive Lock for advanced data protection

Power

Integrated AC Adapter for less bulky transportation; 10-foot power cord included

Battery

Li-Ion, providing over two and a half hours of battery life⁸ supported with one battery; a second battery can be supported in the MultiBay for additional battery life

Power Conservation

Hibernation, Instant-On via Standby; pop-ups with three presets and one custom level of power conservation.
ACPI hardware ready

Service and Support

Compaq Services provides a range of services for the Armada 1750, including a one-year, Limited Warranty⁴, with 7 x 24 service line at 1-800-OK-Compaq (1-800-652-6672) and a free, one-year, second business day⁵ pick-up and delivery service from Compaq. All shipping and handling materials are supplied by Compaq.

Options

Memory

128-MB Memory Upgrade	315177-B21
64-MB Memory Upgrade	314891-B21
32-MB Memory Upgrade	314890-B21

Monitors⁹

TFT8000 Flat Panel	307906-001
TFT5000 Flat Panel	325700-001
P1100 Color ¹⁰	325606-001
P900 Color	386326-001
P700 Color	380207-001
P110 Color ¹⁰	325600-001
P75 Color	307806-001
V1100 Color ¹⁰	386472-001
V1000 Color ¹⁰	351757-001
V900 Color ¹⁰	303500-001
V75 Color (carbon)	307710-002
V500 Color	325900-001
V700 Color (opal)	325800-001
S910 Color ¹⁰	138485-001
S900 Color ¹⁰	360562-001
S710 Color	152991-001
S700 Color	360512-001

Hard Drives

10-GB ¹ SMART Hard Drive	388446-B21
6-GB ¹ SMART Hard Drive	382778-B21
4-GB ¹ SMART Hard Drive	316247-B21

MultiBay Options

Zip Drive	316311-B21
SuperDisk LS-120 Drive	316257-B21
DVD-ROM Drive Kit	316258-B21

PC Cards/Communications

Compaq Microcom 420 56K ³ Global Fax Modem PC Card	317900-001
Compaq Microcom 550 Combo PC Card	321550-001
Compaq Ethernet LAN PC Card	224750-001
10/100 TX PC Card UTP Controller	335506-B21
10 T PC Card UTP Controller	292806-B21
10 2 PC Card Coax Controller	292807-B21
10/100 TX PC Card UTP Controller Upgrade	292813-B21
16/4 TR PC Card IBM UTP/STP Controller	301208-B21

Convenience Bases

Armada Convenience Base II with USB (Ethernet) ¹¹	316239-001
Armada Convenience Base II with USB (Pass-Through) ¹¹	316238-001
Monitor Stand-Conversion Kit ¹²	316246-B21

Power

Li-Ion Battery	316237-B21
External Battery Charger	254938-B21
Auto/Aircraft Adapter	296537-B21
AC Line Cord (10-ft)	217932-002

Input Devices

External Enhanced III Keyboard (Carbon)	118003-008
External Enhanced III Keyboard (Beach Gray)	110562-001
External Enhanced III Keyboard (Opal)	294343-001
Compaq Mouse (Carbon)	
Compaq Mouse (Beach Gray)	143315-001
Compaq Mouse (Opal)	143315-B21

Other

Security Lock	294316-B21
Portable Video Conferencing Kit	296954-001
Armada Headset with microphone	220460-001
Universal Monitor Stand	294315-B21

Carrying Cases

CPQ Value Case	294266-B21
CPQ Workstation Case	294267-B21
CPQ Global Case	294268-B21
CPQ Professional Case (Nylon)	401366-B21
CPQ Professional Case (Leather)	401367-B21

For additional Compaq Brand cases, call 1-800-888-5903.

Memory

Compaq Armada 1750

STANDARD MEMORY

64 MB installed on the System Board (1 slot available)

Standard	Slot
64 MB	1 Empty

STANDARD MEMORY PLUS

OPTIONAL MEMORY


Support for up to 192 MB of SDRAM is available with the installation of an optional memory upgrade.

Up To	Slot
96 MB	1 32 MB
128 MB	64 MB
192 MB	128 MB

Following are memory options available from Compaq:

- 128-MB Memory Upgrade 315177-B21
- 64-MB Memory Upgrade 314891-B21
- 32-MB Memory Upgrade 314890-B21

Storage



- 1 MultiBay
- 2 CD-ROM Drive Bay
- 3 Upgradable Hard Drive

DRIVE SUPPORT

	Quantity Supported	Drive Bay Supported
Removable Media		
1.44-MB Diskette Drive	Up to 1	MultiBay
SuperDisk LS-120 Drive	Up to 1	MultiBay
DVD-ROM Drive Kit	Up to 1	MultiBay
Zip Drive	Up to 1	MultiBay
24X Max ² CD-ROM Drive	Up to 1	CD-ROM Drive Bay
Hard Drives		
10-GB ¹ SMART Hard Drive	Up to 1	Upgradable Hard Drive
6.4-GB ¹ SMART Hard Drive	Up to 1	Upgradable Hard Drive
4-GB ¹ SMART Hard Drive	Up to 1	Upgradable Hard Drive

Technical Specifications

System Unit

Dimensions (HxWxD)	9.9 x 12.5 x 2.3 in/25.1 x 31.8 x 31.2 cm
Weight	
Modem models	8.37 lbs/3.8 kg
Non-Modem models	8.3 lbs/3.77 kg
Stand-Alone Power Requirements	
Nominal Operating Voltage (Li-Ion)	14.2 VDC
Maximum Operating Power	45W
Peak Operating Power	50W
Temperature	
Operating	5° to 95°F/10° to 35°C
Non-operating	-4° to 140°F/-20° to 60°C
Relative Humidity (non-condensing)	
Operating	10% to 90%
Non-operating	5% to 95%
Shock	
Operating	10 G, 11 ms, half-sine
Non-operating	60 G, 11 ms, half-sine
Vibration	
Operating	0.25 G, 1 Oct/Min sweep rate
Non-operating	1 G, 1 Oct/Min sweep rate
Maximum Altitude (unpressurized)	
Operating	10,000 ft/3,048 m
Non-operating	30,000 ft/9,144 m

14.1-Inch Color TFT 1024 x 768 Display

Dimensions (HxW)	8.92 x 11.75 in/22.66 x 29.84 cm
Diagonal Size	14.1 in/35.8 cm
Mounting	Internal
Number of Colors	16.7M
Contrast Ratio	Minimum 100:1
Brightness	Over 120 cd/m ²
Pixel Resolution	
Pitch	0.279 x 0.279 mm
Format	1,024 x 768
Configuration	RGB stripe
Backlight	Edge Lit
Character Display	80 x 25
Total Power Consumption (maximum)	7W

Technical Specifications

13.3-Inch Color TFT 1024 x 768 Display

Dimensions (HxW)	7.9 x 10.6 in/20.1 x 26.9 cm
Diagonal Size	13.3 in/33.8 cm
Mounting	Internal
Number of Colors	16.7M
Contrast Ratio	Minimum 100:1
Brightness	Over 120 cd/m ²
Pixel Resolution	
Pitch	0.264 x 0.264 mm
Format	1,024 x 768
Configuration	RGB stripe
Backlight	Edge Lit
Character Display	80 x 25
Total Power Consumption (maximum)	7W

12.1-Inch Color TFT 800 x 600 Display

Dimensions (HxW)	7.24 x 9.7 in/18.4 x 24.6 cm
Diagonal Size	12.1 in/30.7 cm
Mounting	Internal
Number of Colors	16.7M
Contrast Ratio	100:1
Brightness	Over 120 cd/m ² (typical)
Pixel Resolution	
Pitch	0.3 x 0.3 mm
Format	800 x 600
Configuration	RGB stripe
Backlight	Edge Lit
Character Display	80 x 25, 80 x 50
Total Power Consumption (maximum)	6W (maximum)

QUICK SPECS

Compaq Armada 1750

Technical Specifications

Hard Drives

10 GB¹	Capacity	10 GB	Seek Time (typical reads, including settling)	
	Height	0.5 in/12.7 mm	Single Track	4 ms
	Width	2.5 in/63.5 mm	Average	13 ms (read)
	Interface	ATA	Full-Stroke	23 ms
	Transfer Rate		Rotational Speed	4200 rpm
	Synchronous (Maximum)	33.3 MB/s	Physical Configuration	
			Bytes/Sector	512
			Operating Temperature	41° to 131°F/5° to 55°C

6.4 GB¹	Capacity	6.4 GB	Seek Time (typical reads, including settling)	
	Height	0.5 in/12.7 mm	Single Track	4 ms
	Width	2.5 in/63.5 mm	Average	13 ms (read)
	Interface	ATA	Full-Stroke	23 ms
	Transfer Rate		Rotational Speed	4200 rpm
	Synchronous (Maximum)	33.3 MB/s	Physical Configuration	
			Bytes/Sector	512
			Operating Temperature	41° to 131°F/5° to 55°C

4 GB¹	Capacity	6.4 GB	Seek Time (typical reads, including settling)	
	Height	0.5 in/12.7 mm	Single Track	4 ms
	Width	2.5 in/63.5 mm	Average	13 ms (read)
	Interface	ATA	Full-Stroke	23 ms
	Transfer Rate		Rotational Speed	4200 rpm
	Synchronous (Maximum)	33.3 MB/s	Physical Configuration	
			Bytes/Sector	512
			Operating Temperature	41° to 131°F/5° to 55°C

Diskette Drive

Diskette Size	3.5 inch
Light	None
Height	0.82 in/2.08 cm
Bytes per Sector	512
Sectors per track	
High density	18 (1.44 MB)/15 (1.2 MB)
Low density	9
Tracks per side	
High density	80 (1.44 MB)/80 (1.2 MB)
Low density	80
Read/Write heads	2
Access Times	
Track-to track (high/low)	3 ms/6 ms
Average (high/low)	94 ms/174 ms
Settling time	15 ms
Latency average	100 ms

Integrated AC Adapter

Weight	0.66 lb/0.3 kg
Power Supply (Input)	
Operating Voltage	90 to 260 VAC RMS
Operating Current	1.1 A RMS
Operating Frequency Range	47 to 63 Hz AC
Maximum Transient	4/50 KV

Technical Specifications

Li-Ion Battery Pack

Dimensions (HxWxL)	0.82 x 3.2 x 5.8 in/2.08 x 8.13 x 14.73 cm
Weight	0.85 lbs/0.39 kg
Energy	
Voltage	14.4 V
Amp-hour capacity	3.1 Ah
Watt-hour capacity	43Wh
Temperature	
Operating	50° to 104°F/10° to 40°C
Non-operating	-12° to 140°F/-25° to 60°C

Convenience Base

Dimensions (HxWxD)	4.9 x 14.2 x 14.7 in/12.46 x 36.07 x 37.34 cm
Weight	4.25 lbs/1.93 kg
Power Supply (Input)	
Operating Voltage	100 to 240 VAC
Operating Current	1.1 Amp Maximum
Rated Voltage	100 to 240 VAC
Rated Current	1 Amp Maximum
Line Frequency	47 to 63 Hz
Temperature	
Operating	50° to 95°F/10° to 35°C
Non-operating	-4° to 140°F/-20° to 60°C
Relative Humidity	
Operating	10% to 90%
Non-operating	5% to 95%
Altitude	
Operating	10,000 ft/3,048 m
Non-operating	30,000 ft/9,144 m
Shock	
Operating	10 G, 11 ms, half-sine
Non-operating	140 G, 2 ms, half-sine
Vibration	
Operating	0.25 G, 5 to 500 Hz, 0.5 octave/min sweep rate
Non-operating	1 G, 5 to 500 Hz, 0.5 octave/min sweep rate
Monitor Support	Up to 85 lbs/38.56 kg

Technical Specifications

24X Max³ CD-ROM Drive

Applicable Disc	CD-DA, CD-ROM, CD-R, CD-ROM XA (except ADPCM), CD-I, Photo CD (Multi-session), Video CD, CD-Extra (CD+), CD-G, CD-RW
Center Hole Diameter	15 mm
Disc Diameter	12 cm, 8 cm
Disc Thickness	1.2 mm
Track Pitch	1.6 μ m
Laser	
Output power	0.24 \pm 0.1mW
Type	GaAlAs double hetero laser diode
Wave length	780 nm at Ph-4.3 mW
Access Times (typical reads, including settling)	150 ms
Audio Output Level	
Line-out	\pm 0.27 Vrms
Headphone	None
Cache Buffer	128 KB
Data Transfer Rate	
Sustained	150 KB/s (sustained 1X)
Variable	1500 to 3600 KB/s (10X to 24X)
Start-up Time	< 8 sec
Stop Time	< 4 sec

¹ For Hard Drives, GB = Billion Bytes.

² Data transfer rates will vary from 150 KB/s to 3600 KB/s.

³ Designed only to allow faster downloads from K56flex or V.90 compliant sources. Maximum achievable download transmission rates currently do not reach 56 KB/s, and will vary with line conditions. Modem only supports Windows 9.x and Windows NT 4.0.

⁴ Certain restrictions and exclusions apply. Service and Support programs vary by geographic region. Consult the Compaq Customer Support Center for details.

⁵ Pick-up and delivery service is available in 48 contiguous US States and Canada. Eligibility for priority pick-up (second business day return) is limited to certain geographic locations. Carry-in service available outside the US and Canada.

⁶ IrDA 4 MB compliant. IR performance will vary depending on performance of IR peripherals and applications used.

⁷ Full support in Windows 9.x.

⁸ Actual results may vary individual usage. When tested in the standard configuration, using the Ziff-Davis BatteryMark Life test version 2.0, the battery life of the Amada 1750 will range over 2.5 hours. Standard configuration at time of announcement (1/25/99) 14.1" panel,

64-MB memory and no drives other than the hard drive active.

⁹ AssetControl monitor. AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability.

¹⁰ May not be compatible with the Armada Station Monitor Support Stand, the Convenience Base I, or the Convenience Base II due to weight limitations.

¹¹ Armada 1500 compatible.

¹² Allows the Armada 1500 Convenience Base to support the Armada 1750.