

# CELSIUS<sup>®</sup> Mobile H

Outstanding computing power  
and graphic performance



CELSIUS Mobile sets the standard in the market of Intel based mobile workstations. If you demand outstanding performance in different business fields like construction, simulation, finance or multimedia purposes and still want to be mobile – then this is the product of your choice. BIOS-Lock password system and hard disk drive protection, integrated fingerprint solution and native support for SmartCards make the CELSIUS Mobile Series the most secure mobile family in the world. The modular design makes expansion a 5 second exercise with a variety of available devices.

#### System:

- Intel<sup>®</sup> Mobile Pentium<sup>®</sup> III processor 1.13 GHz with SpeedStep™ technology for improved battery life

#### Audio

- Five channel digital Dolby surround system

#### Graphics / Display:

- 15.1"-TFT-UXGA display
- professional Workstation graphics with Quadro2 Go, 64 MB video memory and TwinView
- Certified for various CAD and DCC applications

#### Ease of Use:

- Detachable keyboard for ergonomic working
- Ease of use through FlexiBay concept for DVD/CD-RW / Combo drive, second battery, up to three HDDs, LS-240 drive, ..

#### Security:

- Boot lock via fingerprint sensor or password
- Integrated SmartCard reader

#### Connectivity:

- Optimal connectivity through built-in 56 Kbps V.90 international modem and 10/100 MB/s Ethernet LAN adapter or alternatively FireWire (OHCI compliant) and 10/100 MB/s Ethernet LAN adapter
- Digital and analogue video out (DVI-I), fast Infrared link (Fast IrDa 1.1) and 2 USB ports

# Technical Data - CELSIUS Mobile H - Outstanding Workstation

## System, processors, architecture

Intel® Mobile Pentium® III processor 1.13 GHz with SpeedStep™ technology  
512KB second-level cache on-die

## BIOS and chipset

Phoenix NoteBIOS 4.06  
Intel® 830 EM chipset

## Memory

2 memory slots, SDRAM, PC 133 modules  
max. 1 GB

## Standard devices / drives

30 GB or 48 GB IDE hard disk (UDMA 100)  
Combo CD-RW / DVD, LS-240 drive in FlexiBay  
Li-Ion battery in FlexiBay

## FlexiBay

LS 240	240 MB, standard
Combo CD/RW-DVD	standard
DVD	optional
CD/RW	optional
2nd/3rd Hard disk	optional (30/48 GB)
2nd Battery pack	optional

## Display

LCD-TFT 15" UXGA	
Display diagonal	38.3 cm (15")
Resolution LCD	1600 x 1200
Color depth	32-bit
Brightness	> 150 cd/m <sup>2</sup>
Resolution external monitor	max. UXGA, 1600 x 1200

## Graphics processor

NVIDIA Quadro2 Go, 4x AGP,  
64 MB Video memory, DDR-RAM, TwinView

ext. Resolutions	Colors	Refresh rates (max.)
800 x 600	True Color	120 Hz
1024 x 768	True Color	120 Hz
1280 x 1024	True Color	100 Hz
1600 x 1200	True Color	85 Hz

## Audio

ESS Allegro. 16-bit stereo sound,  
SoundBlaster™ Pro compatible, (3D-Sound full-duplex)  
Integrated microphone, two built in stereo speakers  
Optical digital audio output (SPDIF)

## Keyboard and pointing device

Detachable full-sized keyboard with Windows keys  
TouchPad pointing device

## I/O interfaces

1 x fast infrared link (IrDa 1.1, 4 MB/s)  
2 x type II or 1 x type III PC Card slots:  
(32-bit Card Bus & ZV support)  
2 x USB ports , 1 x serial port, 1x parallel port  
1 x PS/2 for external keyboard /mouse (with Y-cable)  
1 x DVI-I (digital and analogue video out)  
(adapter DVI-I / VGA included)  
1 x line out combined with SPDIF out  
1 x microphone in, 1 x headphone out

## Communications

Built-in V.90 international modem and 10/100 MB/s LAN  
combination or alternatively  
IEEE 1394 FireWire

## Mobile management

PXE (only combined with built-in LAN), DMI 2.0 and WfM 2.0 compliance

## Security functions

Boot lock via fingerprint sensor  
Password protection for system, setup, hard disk,  
Boot protection for floppy disk drive and PCCard  
Deactivation of serial and parallel interface  
Kensington Lock device  
SmartCard reader (integrated, separate slot)  
Anti-virus program

## Power system

Li-Ion battery, 9 cell, 11.9 V, 6000mAh, 66Wh,  
External Mini AC adapter 100 - 240 V / 50 - 60 Hz  
AC voltage range 100 - 240 V (automatic)  
Rated frequency 50 - 60 Hz (automatic)  
max. power output of 19 V, 4.2 A  
power supply 80 W  
Dimensions (H x W x D) 30 x 132 x 58 mm  
Weight 375 g excluding power cord  
Up to 3 hours with 1 battery, 6 hours with 2<sup>nd</sup> battery installed  
(ZD BatteryMark 2.0)

## Operating system / software

Windows NT/2000 Dual Installation,  
Adobe Acrobat Reader v4.0  
Phoenix Card Executive and Power Panel utilities for Windows NT  
Easy CD Creator, Direct CD  
WinDVD for MPEG II decode (Windows NT/2000)  
Easy Guide on-line user documentation  
Ready to Experience Windows XP  
Fujitsu Siemens Computers PC use genuine  
Windows® Operating Systems  
[www.microsoft.com/piracy/howtotell](http://www.microsoft.com/piracy/howtotell)

## Compliance with standards

Product safety	EN60950/IEC60950 UL1950, CSA22.2 No.950
Ergonomics	ISO9241
Electromagnetic compatibility	EN55022/B, EN50082-1 FCC class B
CE mark	to EU Directives, 89/336/ECC(EMV)

## Approvals

There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons (e.g. for Canada and USA, eastern European countries, Norway) on request.

## Operating conditions

5° C to 35° C degrees (ambient temperature)  
Sound pressure level < 32 dB(A) at workplace  
20 % to 85 % relative humidity, non-condensing

## Dimensions and weight

340 x 278 x 42 mm  
3.3 kg (including battery and DVD)

## Warranty

Country-specific

Published by  
Fujitsu Siemens Computers

World Wide Web:  
<http://www.fujitsu-siemens.com>

All rights, including rights created by patent grant or registration of a utility model or design, are reserved. Delivery subject to availability; right of technical modifications reserved.  
All hardware and software names used are trade names or trademarks of their respective manufacturers.

Copyright ©  
Fujitsu Siemens Computers GmbH, 11/2001

Company stamp