


### Overview

#### What's New

- AMD K6®-2+ 550MHz Processor
- AMD PowerNow!™ Technology
- 13.3" XGA Display

#### At A Glance

- AMD K6®-2+ 550MHz Processor
- Choice of either 12.1 in. High Performance Addressing (HPA) SVGA, 12.1 in. TFT SVGA, or 13.3 in. TFT XGA displays
- Full set of system ports
- Microsoft Windows 98 SE
- Integrated 56K modem available
- Upgradable to 160/192 MB memory (depending upon standard configuration)
- Full size keyboard user
- One Type I, Type II or Type III CardBus PC Card slot
- Between 6.7 and 6.8 lbs. or 3.0 to 3.1 kg
- USB port expansion options available
- Lightweight/Extended Capacity Lithium Ion battery available.
- Protected by a one-year Warranty — Certain restrictions and exclusions apply. Consult the Compaq Customer Support Center for details.



- |  |  |
|--|--|
| 1. 12.1-inch HPA, 12.1-inch TFT or 13.3-inch TFT Color Display | 8. PC Card slot                          |
| 2. CD-Rom  | 9. Integrated RJ-11 Jack, 56K v.90 modem |
| 3. Infrared Transceiver  | 10. Power Switch                         |
| 4. Keyboard  | 11. Cable lockslot                       |
| 5. 1.44-MB Disk Drive  | 12. Microphone                           |
| 6. TouchPad  | 13. LED indicator Lights                 |
| 7. Battery Bay   | 14. Display Latch                        |

## Standard Features

<b>Processor</b>	Mobile AMD K6 <sup>®</sup> -2+ 550MHz Global Processor <ul style="list-style-type: none"> <li>• Leading-edge Super7<sup>™</sup> platform features, including 100-MHz front side bus</li> <li>• 3DNow!<sup>™</sup> technology with new DSP Instructions</li> <li>• AMD PowerNow!<sup>™</sup> Technology</li> <li>• 2X AGP Graphics</li> <li>• High speed 128K on-chip L2 cache</li> <li>• Compatible with Windows 2000 and Windows 98</li> </ul>	
<b>Cache Memory</b>	192-KB total internal cache <ul style="list-style-type: none"> <li>• Internal split, two-way set associative, 64-KB L1 Cache             <ul style="list-style-type: none"> <li>• 32-KB instruction cache with additional 20 KB of predecode cache</li> <li>• 32-KB writeback dual-ported data cache</li> <li>• MESI protocol support</li> </ul> </li> <li>• Internal full-speed, four-way set associative, 128-KB, L2 Cache</li> </ul>	
<b>Memory</b> <i>One of the following required</i>	Standard Maximum	64 MB (12.1" & 13.3" TFT) (8 MB allocated to frame buffer) 192 MB
<b>Communications</b>	56K v.90 modem Note: Designed only to allow faster downloads from v.90 compliant sources. Maximum achievable download transmission rates currently do not reach 56 KB/s, and will vary with line conditions.	
<b>PC Card Slots</b>	One Type I, II or III PC Card Slot which supports both 32-bit CardBus (Full support in Windows 98) and 16-bit PC Cards	
<b>Storage</b>	Diskette Drives Hard Drives	1.44 MB 5 GB
<b>Multimedia</b>	Integrated 16-bit Sound Blaster Pro-compatible stereo audio Integrated speakers and microphone Software and hardware volume controls Headphone-out Jack Microphone-in Jack Hardware assisted MPEG2 support	
<b>Interfaces</b>	PC Card Slot Enhanced Parallel Port PS/2 Serial Port External Monitor Port Speaker Out (Headphone) Jack Microphone In Jack AC Power Connector RJ-11 Jack Infrared Port USB Port	One Type I, II or Type III 1 1 1 1 1 1 1 1 (with modem only) 1 ("Fast IR" compliant, IR performance will vary depending on performance of IR peripherals and application used) 1
<b>Graphics</b>	Trident CyberBlade 7 with AGP 2X support	


## Standard Features

<b>Display</b> (Internal) <i>One of the following</i>	12.1-inch color HPA with 800 x 600 SVGA resolution 12.1-inch color TFT with 800 x 600 SVGA resolution 13.3-inch color TFT with 1024 x 768 XGA resolution
<b>Display</b> (External)	16 Million colors supported 640x480, 800x600, 1024x768 or 1280x1024 up to 60,75,85 Hz refresh rate
<b>Operating System</b>	Microsoft Windows 98 Second Edition
<b>Software</b>	Online Safety and Comfort Guide Online Reference Guide Norton Anti Virus * Microsoft Word 2000 * Microsoft Office Small Business * Available on select models
<b>Security</b>	Cable lock support Power-on password Setup passwords Ability to disable serial port, parallel port, diskette drive, diskette drive boot capability
<b>Power Supply</b>	External AC Adapter; 6-foot power cord included
<b>Battery</b>	A 9-cell NiMH battery ships standard and provides over two hours of battery life using ZD BattMark 3.0. An optional 8-cell Li-ION battery is also available. <i>Note: Actual results may vary with individual usage. When tested in standard configuration, using the Ziff-Davis BatteryMark Test version 3.0, the battery life of the Armada 100S will exceed 2.0 hours using "max performance" mode in PowerNow!. Standard configuration at time of announce is considered to be one battery, a 800x600 (High color – 16-bit color) panel set at 50percent brightness, 32 MB or 64 MB RAM, and no drives other than the hard drive active.</i>
<b>Power Conservation</b>	Hibernation Instant-On via Standby Five power consumption levels available through AMD PowerNow!™ Technology Pop-ups with three presets One custom level of power conservation
<b>PowerNow! Technology</b>	◆AMD PowerNow! technology is a combination of software and hardware support that allows the processor to run at different frequencies and voltages.
<b>Service and Support</b>	Compaq Services includes a one-year limited warranty, whole-unit replacement via second-business-day, pick-up and delivery. ( <i>Eligibility depends on geographic location.</i> ) Optional services include a one-year warranty extension CarePaq (FM-AMMAI-36 or 400514-002). <i>Note: Certain restrictions and exclusions apply. See the Limited Warranty Statement for details.</i>

## Standard Features

### Naming Convention

The Etymology of a Model name:



## Standard Features

---

### Models

<b>A1S/K62/550/T3X/5/D/M/64/98W</b> 219677-004 <b>GEM ONLY</b>	<b>Display</b>	13.3-inch color TFT/XGA
	<b>Processor</b>	AMD K6-2+ 550 MHz
	<b>Cache Memory</b>	Internal 64-KB L1 Cache 64-KB integrated Internal 128-KB, L2 Cache
	<b>Memory</b>	Standard 64 MB SDRAM Maximum 192 MB SDRAM
	<b>Optical Drive</b>	24XCD-ROM
	<b>Hard Drive</b>	5 GB
	<b>Modem</b>	56K, V.90
	<b>Graphics</b>	Trident CBI7 4-MB UMA RAM(Shared RAM)
	<b>Audio</b>	16-bit SoundBlaster Pro compatible
	<b>Software</b>	Windows 98 SE, MS Word 2000

---

<b>A1S/K62/550/T3X/5/D/M/64/98S</b> 219678-004	<b>Display</b>	13.3-inch color TFT/XGA
	<b>Processor</b>	AMD K6-2+ 550 MHz
	<b>Cache Memory</b>	Internal 64-KB L1 Cache 64-KB integrated Internal 128-KB, L2 Cache
	<b>Memory</b>	Standard 64 MB SDRAM Maximum 192 MB SDRAM
	<b>Optical Drive</b>	24XCD-ROM
	<b>Hard Drive</b>	5 GB
	<b>Modem</b>	56K, V.90
	<b>Graphics</b>	Trident CBI7 4-MB UMA RAM(Shared RAM)
	<b>Audio</b>	16-bit SoundBlaster Pro compatible
	<b>Software</b>	Windows 98 SE, Office 2000 Small Business

---

<b>A1S/K62/550/T2S/5/D/M/64/98W</b> 219673-004	<b>Display</b>	12.1-inch color TFT SVGA
	<b>Processor</b>	AMD K6-2+ 550 MHz
	<b>Cache Memory</b>	Internal 64-KB L1 Cache 64-KB integrated Internal 128-KB, L2 Cache
	<b>Memory</b>	Standard 64 MB SDRAM Maximum 192 MB SDRAM
	<b>Optical Drive</b>	24XCD-ROM
	<b>Hard Drive</b>	5 GB
	<b>Modem</b>	56K, V.90
	<b>Graphics</b>	Trident CBI7 4-MB UMA RAM(Shared RAM)
	<b>Audio</b>	16-bit SoundBlaster Pro compatible
	<b>Software</b>	Windows 98 SE, MS Word 2000

## Standard Features

---

### Models (continued)

---

<b>A1S/K62/550/T2S/5/D/M/32/ 98W 219669-004</b>	<b>Display</b>	12.1-inch color HPA SVGA
	<b>Processor</b>	AMD K6-2+ 550 MHz
	<b>Cache Memory</b>	Internal 64-KB L1 Cache 64-KB integrated Internal 128-KB, L2 Cache
	<b>Memory</b>	Standard      64 MB SDRAM Maximum      192 MB SDRAM
	<b>Optical Drive</b>	24XCD-ROM
	<b>Hard Drive</b>	5 GB
	<b>Modem</b>	56K, V.90
	<b>Graphics</b>	Trident CB17 4-MB UMA RAM(Shared RAM)
	<b>Audio</b>	16-bit SoundBlaster Pro compatible
	<b>Software</b>	Windows 98 SE, MS Word 2000

### Options

Memory	32-MB Memory Upgrade	179863-B21
	64-MB Memory Upgrade	179864-B21
	128-MB Memory Upgrade	179865-B21
	*(Due to the non-industry standard nature of some third party memory modules, we strongly recommend using only Compaq branded memory modules)	
Monitors	<i>CRTs</i>	
	<i>Standard Series</i>	
	S710 Color CRT 17-inch (carbon)	154499-002
	S510 Color CRT 15-inch (carbon)	168636-002
Docking Solutions	Xircom PortStation USB Port Expansion Solution w/NIC	180947-001
PC Cards/Communications	Compaq Microcom 420 56K Global Modem (Designed only to allow faster downloads from v.90 compliant sources. Maximum achievable download transmission rates currently do not reach 56 KB/s, and will vary with line conditions.)	317900-001
	10/100 TX PC Card UTP Controller	335506-B21
	100BaseTX Ethernet Upgrade	225435-001
WLAN Options	Compaq WL100 11-Mb/s Wireless LAN PC Card (Industry-Standard Wireless Technology)	146927-001
	Compaq WL 400 11-Mb/s Wireless LAN Hardware Access Point	158603-001
Power	Li-Ion (8-cell) Optional	175103-B25
	AC Adapter (50W)	175101-001
	Auto Adapter	188200-B21
Input Devices	External Enhanced III Keyboard (carbon)	118003-008
	Compaq Mouse (carbon)	103180-00-B21
	Intellimouse	294306-B21
	10 Key Numeric Keypad	294317-B21
Useful Accessories	Security Cable Lock	294316-B21
	Armada Headset with Microphone	220460-001
	MP1800 Microportable Projector	180226-001
	MP1600 Microportable Projector	386202-001
	MP1400 Microportable Projector	174626-001
	Multimedia Adapter and Remote kit (comes with MP 1800)	174963-001
	MP1800/1400 Lamp Replacement kit	189798-001

## Options

---

Carrying Cases	Compaq Value Case	294266-B21
	Compaq Workstation Case	294267-B21
	Compaq Global Case	294268-B21
	Compaq Executive Case	294269-B21
	Compaq Professional N Case	401366-B21
	Compaq Professional L Case	401367-B21

---

For additional Compaq Brand cases, call 1-800-888-5903.

---



## Memory

---

### Compaq Armada 100S

#### STANDARD MEMORY (AMD K6-2+ 550-MHz Models)


64 MB on-board (1 slot available)

Memory		Onboard	Slot 1
Standard	64 MB	64 MB	Empty
	96 MB	64 MB	32 MB
	128 MB	64 MB	64 MB
	192 MB	64 MB	128 MB

Following are memory options available from Compaq:

- 32-MB Memory Upgrade            179863-B21
- 64-MB Memory Upgrade        179864-B21
- 128-MB Memory Upgrade       179865-B21

## Storage



1. CD-ROM
2. HDD
3. FDD

### DRIVE SUPPORT

System Drive Support	Quantity Supported	Drive Bay Supported
<b>Media</b>		
24X CD-ROM	Up to 1	Fixed
1.44-MB Diskette Drive	Up to 1	Fixed
<b>Hard Drives</b>		
5-GB Hard Drive	Up to 1	Fixed

## Technical Specifications

<b>System Unit</b>	<b>Dimensions (HxWxD)</b>	1.6 x 11.7 x 9.4 in/4.1 x 29.7 x 23.9 cm	
	<b>Weight</b>	AMD K6-2+ 550 MHz	6.6 lbs/3 kg to 6.8 lbs/3.1 kg
<b>Stand-Alone Power Requirements</b>	Nominal Operating Voltage (Li-Ion)	14.8 VDC	
	Nominal Operating Voltage (NiMH)	10.8 VDC	
	Maximum Operating Power	20W	
	Peak Operating Power	26W	
<b>Temperature</b>	Operating	50° to 95°F/10° to 35°C	
	Non-operating	-4° to 140°F/-20° to 60°C	
<b>Relative Humidity</b>	Operating	10% to 90% relative humidity, non-condensing	
	Non-operating	5% to 95% relative humidity, 101.6°F/38.7°C Maximum wet bulb temperature	
<b>Shock</b>	Operating	10 G, 11 ms, half-sine	
	Non-operating	60 G, 11 ms, half-sine	
<b>Vibration</b>	Operating	0.5 G zero-to-peak, 10 to 500 Hz, at 0.5 oct/min sweep rate	
	Non-operating	1.0 G, zero-to-peak, 10 to 500 Hz, at 0.5 oct/min sweep rate	
<b>Maximum Altitude (unpressurized)</b>	Operating	0 to 10,000 ft/0 to 3,048 m	
	Non-operating	0 to 40,000 ft/0 to 9,144 m	

## Technical Specifications

<b>12.1-Inch Color HPA SVGA Display</b>	<b>Dimensions (HxW)</b>	8.17 x 10.83 in/20.25 x 27.5 cm		
	<b>Diagonal Size</b>	12.1 in/30.74 cm		
	<b>Mounting</b>	Internal		
	<b>Number of Colors</b>	65K		
	<b>Contrast Ratio</b>	40:1		
	<b>Brightness</b>	70+ nit		
	<b>Pixel Resolution</b>	Pitch	0.1021 x 0.306 mm	
		Format	800 x 600	
		Configuration	RGB Stripe	
	<b>Backlight</b>	Cold cathode fluorescent, 1 tube		
	<b>Character Display</b>	80 x 25		
	<b>Total Power Consumption</b>	2.75W		
	<b>Refresh</b>	60 Hz		

<b>12.1-Inch Color TFT SVGA Display</b>	<b>Dimensions (HxW)</b>	7.83 x 10.83 in/19.9 x 27.5 cm		
	<b>Diagonal Size</b>	12.1 in/30.74 cm		
	<b>Mounting</b>	Internal		
	<b>Number of Colors</b>	262K		
	<b>Contrast Ratio</b>	200:1		
	<b>Brightness</b>	115+ nit		
	<b>Pixel Resolution</b>	Pitch	0.3075 x 0.3075 mm	
		Format	800 x 600	
		Configuration	RGB Vertical Stripe	
	<b>Backlight</b>	Cold cathode fluorescent, 1 tube		
	<b>Character Display</b>	80 x 25		
	<b>Total Power Consumption</b>	4.5W		
	<b>Refresh</b>	60 Hz		

## Technical Specifications

13.3-Inch Color TFT XGA Display	<b>Dimensions (HxW)</b>	7.83 x 10.83 in/19.9 x 27.5 cm		
	<b>Diagonal Size</b>	13.3 in/33.78 cm		
	<b>Mounting</b>	Internal		
	<b>Number of Colors</b>	262K		
	<b>Contrast Ratio</b>	200:1		
	<b>Brightness</b>	140+ nit		
	<b>Pixel Resolution</b>	Pitch	0.264 x 0.264 mm	
		Format	1024 x 768	
		Configuration	RGB Vertical Stripe	
	<b>Backlight</b>	Cold cathode fluorescent, 1 tube		
	<b>Character Display</b>	80 x 25		
	<b>Total Power Consumption</b>	5W		
	<b>Refresh</b>	60 Hz		

5 GB Hard Drive	<b>Capacity</b>	5 GB		
	<b>Height</b>	0.37 in/9.5 mm		
	<b>Width</b>	2.5 in/63.5 mm		
	<b>Interface</b>	ATA-5		
	<b>Transfer Rate</b>	Media	86.4-153.3 Mb/s	
		Interface	UDMA 33.3MB/s	
	<b>Seek Time</b> (typical reads, including settling)	Single Track	3 ms	
		Average	13 ms (read)	
		Full-Stroke	24 ms	
	<b>Rotational Speed</b>	4200 rpm		
<b>Physical Configuration</b>	Bytes/sector	512		
<b>Operating Temperature</b>	41° to 131°F/5° to 55°C			

Diskette Drive	<b>Diskette Size</b>	3.5 in		
	<b>Activity Indicator</b>	On system		
	<b>Height</b>	0.5in/12.7 mm		
	<b>Bytes per Sector</b>	512		
	<b>Sectors per track</b>	High density	18 (1.44 MB)/15 (1.2 MB)	
		Low density	9	
	<b>Tracks per side</b>	High density	80 (1.44 MB)/80 (1.2 MB)	
		Low density	80	
	<b>Read/Write heads</b>	2		
	<b>Access Times</b>	Track-to track (high/low)	3 ms/6 ms	
		Average (high/low)	94 ms/174 ms	
		Settling time	15 ms	
Latency average		100 ms		

## Technical Specifications

<b>External AC Adapter</b>	<b>Weight</b>	0.45 lb/0.21 kg		
	<b>Power Supply (Input)</b>	Operating Voltage	100 to 240 VAC RMS Nominal	
		Operating Current	1.5 A RMS	
		Operating Frequency Range	50 to 60 Hz AC Nominal	
		Maximum Transient	4/50 kV	
<b>Li-Ion Battery Pack</b>	<b>Dimensions (HxWxD)</b>	0.58 x 5.91 x 2.76 in/1.48 x 15.02 x 7.02 cm		
	<b>Weight</b>	0.93 lb/0.42 kg		
	<b>Cells</b>	8 Li-Ion		
	<b>Energy</b>	Voltage	14.8 V	
		Amp-hour capacity	3.2 Ah	
		Watt-hour capacity	47.36Wh	
	<b>Temperature</b>	Operating	50° to 104°F/10° to 40°C	
		Non-operating	-12° to 140°F/-30° to 60°C	
<b>NiMH Battery Pack</b>	<b>Dimensions (HxWxD)</b>	0.58 x 5.91 x 2.76 in/1.48 x 15.02 x 7.02 cm		
	<b>Weight</b>	1.25 lb/0.57 kg		
	<b>Cells</b>	9 NiMH		
	<b>Energy</b>	Voltage	10.8 V	
		Amp-hour capacity	3.8 Ah	
		Watt-hour capacity	41.04Wh	
	<b>Temperature</b>	Operating	50° to 104°F/10° to 40°C	
Non-operating		-12° to 140°F/-25° to 60°C		