Data Sheet

We make sure



Issue July 2007

LIFEBOOK S6410 Get ready for your next business trip

Pages 4

The exclusive LIFEBOOK S6410 is your best friend on the move, leaving no compromises!

The sturdy notebook keeps the balance between low weight, best connectivity, high-end performance and modularity. With its integrated UMTS/HSUPA, ConfCamera and brilliant 13.3-inch wide display, you are going to experience true mobility – anywhere, anytime.

The combination of performance, modularity and flexibility gives you the functionality and ease of use of a full-sized PC. Intel® Centrino® Duo Mobile Technology with latest Intel GM965 chipset technology delivers high performance and Business-day-long independency from the power socket.

This notebook is designed for highest quality with extensive testing and an extra-strong magnesium lid.

Elegance

Designed for the most demanding mobile users, LIFEBOOKs are the perfect synthesis of form, function and style.

- Light-weight modular 13.3-inch wide notebook with only 1.7 kg
- Exclusive protective leather bag
- Modular bay fitting an optical disk drive or battery
- Excellent resolution and video quality

Ergonomics

- 13.3-inch WXGA -display for maximum viewing comfort
- Convenient working with full sized keyboard
- Small in size but great expandability with maximum ports
- Eco Button to extend battery life by powering down energy consumption

Connectivity

- Bluetooth and Wireless LAN optional integrated
- Optional Port Replicator for easy connection to all your peripherals, compatible with LIFEBOOK E Series and LIFEBOOK C Series
- Long lasting battery for Business-day long independency with first and second battery

Security

- Trusted platform module (TPM 1.2) provides more secure applications and makes transitions safe
- Biometric fingerprint sensor
- Built-in SmartCard controller and optional SmartCase Logon+: software with best integration into your IT environment
- Lock workstation Button for fast sign off the system

Reliability

- Highest quality design with magnesium lid
- Hard disk drive ShockSensor minimizes data loss and guarantees a higher reliability of your data
- Spill-proof keyboard offers protection against system damage

Manageability

- Integrate the bundled system management software Desk View Admin in every common IT infrastructure
- Seamless integration in heterogeneous enterprise management systems
- Get optional add on packages: With DeskView Migrate and DeskView Control for e.g. migration projects and extensive client lifecycle management tasks









System	LIFEBOOK S6410
Processor	
Intel® Core2™ Duo Processor Second level cache	T7100 (1.8GHz) 2 MB
Front side bus (FSB)	667 MHz
Intel® Core2™ Duo Processor	T7300 (2.0GHz) T7500 (2.2GHz)
Second level cooks	T7700 (2.4GHz)*
Second level cache Front side bus (FSB)	4 MB 800Mhz
Chipset Northbridge	Intel GM965
Southbridge	ICH 8-M
Memory DIMM slots	2
DDR2-667 SDRAM, 667 MHz BIOS	up to 4GB
BIOS Flash EPROM	BIOS based on Phoenix TrustedCore Notebook
Interfaces SIM card slot	1
Infrared link (Fast IrDa 1.1, 4 Mbps)	1
Type I/II PC Card slot Memory card slot (SD, MS, xD and MSPRO)	1 1
USB 2.0	3
S-Video out (TV-out) without adapter cable VGA	1
Modem RJ-11 LAN RJ-45	1
Audio-in (line-in / microphone)	1
Audio-out (line-out / headphone) DC-in	1
IEEE1394	1
Kensington Lock Docking connector for Port Replicator	1 1
Port Replicator interfaces (optional): USB 2.0	4
VGA	4 1
DVI-D	1 (with HDCP support)
Serial port	1
Parallel port LAN RJ-45	1
PS/2	1
DC-in Microphone	1 1
Headphone Power on switch	1
Kensington Lock	1
Camera Modem on board	Built-in ConfCamera (1,3 megapixle VGA Camera)
56K V.92 modem MDC1.5	1
LAN on board built-in 10/100/1000 Mbps Marvell 88E8055	X
Wireless Technologies (WLAN)	
Import and usage according to country-specific regulations. 3 Dual band WLAN antennas, 2 UMTS antennas	
Intel Pro Wireless 4965 a/g/n Atheros Minicard b/g 802.11 b/g	optional optional
WiFi certified	X
Integrated UMTS/HSUPA, also supported are GPRS and EDGE or higher Bluetooth	Optional (downlink 7.2, uplink 2.0)
Bluetooth V2.0	optional
Audio Stereo speakers	х
Sound chip Internal microphone	RealTek ALC262 2
Keyboard and pointing device	
Keyboard	Spill proof keyboard, 85 keys, 19mm pitch,
Touchpad	3mm key stroke with two mouse buttons, scroll via fingerprint sensor
Fingerprint sensor	X
Launch Keys Application Buttons	4
Lock workstation Button	X
Mobility Center Button Eco Button	X X
Recovery Button	X
Status LED Graphics	X
Intel X3100 integrated graphics Direct X9	x x
Direct X10	x x (Q4/2007)
Pixelshader 3.0 Pixelshader 4.0	x x (Q4/2007)
1 Molonador 4.0	^ (QT/2001)

I	
DualView (Windows XP & Windows Vista)	X
Display	
13.3-inch TFT WXGA /1280 x 800 pixel, glare display	x 1920 x 1200 / true color / 60 Hz (tbd.)
Max. resolution for external displays Hard disk drives (internal) *	1920 X 1200 / true color / 60 Hz (tbd.)
S.M.A.R.T.	X
ShockSensor for HDD shock protection	X
80 GB S-ATA 150 (5400 rpm)	X
120 GB S-ATA 150 (5400 rpm)	X
160 GB S-ATA 150 (5400 rpm)**	X
* 1 Gbyte equals one billion bytes, when referring to hard disk drive	
capacity; accessible capacity may vary, also depending on used software	
and tool.	
** for projects only	
Modular Drives	
DVD super-multi drive incl. RAM	X
More information in specific Data Sheet:	
http://www.fujitsu-siemens.com/optical_drives/	
Manageability	
Please refer to	
http://www.fujitsu-siemens.com/solutions/business solutions/manageability	<u>/featurefinder.html</u>
Supported Standard	
WMI / CIM / WBEM PXE	X X
BootP	x made4you
Security	made4you
Physical security	
Kensington Lock support	X
System Security	^
Boot sector virus protection	
Trusted Platform module 1.2	optional
Symantec Norton Internet Security	X
User Security	
User and supervisor BIOS password	X
SystemLock BIOS SmartCard security	X
Hard disk password	X
Integrated Fingerprint Sensor	X
Integrated SmartCard controller in PC Card with system lock support	X
SmartCase Logon+ incl. Fingerprint Software Power supply	X
1st Li-lon battery 6 cell 5200mAH (53.3 Wh)	
2nd Li-lon battery 6 cell 2300mAh (24.8Wh) (Option)	optional
First battery * (Mobile Mark 2005) [up to]	tbd
First + Second battery * (Mobile Mark 2005)	tbd
AC adapter 19V/80W Adapter	ibu
Rated voltage (AC input) 100 - 240 V	
Rated frequency 50 - 60 Hz	X
DC output 19 V, 4.22	
Operating temperatures	
Relative humidity (non-condensing)	20% - 85% (running)
Ambient temperature	5° - 35° C
Dimensions / Weight	
Dimensions (H x W x D)	314 x 234 x 22.7 – 31.5 mm
Weight*	1,75 kg
* Weight may vary depending on actual configuration	
Certificates CE Marking	v
CE according to EU Directives 89/336/EEC (EMC)	X
73/23/EEC (Product safety)	X
CE according to 99/5/EEC (R&TTE)	X
CE! (Wireless)	x (with integrated WLAN)
CE (Emission/Immunity)	X (Will Mogrator VE) II ()
R&TTE	X
FCC	•
GS (German ergonomic approval)	tbd
UL/cUL	Х
CB Generic Report	X
CB (Safety)	X
RoHS	X
WHQL TBR21	X
Energy Star	X tbd
WiFi certified	tibd X
Operating System	Α
Microsoft Windows XP Professional	driver support
Microsoft Windows Vista™	X
Software (compatibility / preinstalled)	
Adobe Acrobat Reader	X
Application panel tool	X
Camera	X
Windows Vista recovery media	optional (extra order number)
Driver and Utility DVD (DUDVD)	optional (extra order number S26361 F2007 E903)
Eco Power Saving Utility	X
Easy Guide on-line user documentation	Х
Nero Essentials	X
Norton Internet Security (incl. Firewall) on DUDVD for Microsoft Windows	X
XP	"

SmartCase Logon+ Toshiba Bluetooth Stack UMTS watcher DVD playback software	x x optional with UMTS optional
Accessories (order number)	
AC-adapter	tbd
Case	tbd
Port Replicator	New Port Replicator S26391-F5031-L550
Battery	tbd
Battery charger	tbd
Modem adapter set 1: D, UK	
Modem adapter set 2: SW, NO, FI, DK	
Modem adapter set 3: CH, A, B, NL, F, I, E, POR	
http://www.fujitsu-siemens.com/accessories/	
Spare part availability	5 years