

Bush Hog® TOUGH Backhoes

BUSH HOG® TOUGH FEATURES

TOUGH High Quality Cylinders

TOUGH Box Construction Of Dipperstick

TOUGH Heavy Duty Booms

TOUGH Robotic Welds With Consistent Penetration

TOUGH Reinforced Buckets

TOUGH 2 1/2 Inch Welded Cutting Edges

TOUGH Powder Coat Paint



BH850



BH950

MODELS	BH850	BH950
Tractor HP Range	35 - 100 PTO	55 - 100 PTO
Maximum Digging Depth	9 ft 0 inches	10 ft 0 inches
Digging Depth (two foot flat bottom)	8 ft 6 inches	9 ft 6 inches
Swing Arc	180°	180°
Loading Height (bucket at 60°)	6 ft 8 inches	7 ft 6 inches
Reach From Center Line of Swing Pivot	11 ft 1 inch	12 ft 4 inches
Transport Height (maximum)	6 ft 11 inches	8 ft 0 inches
Bucket Rotation	180°	180°
Loading Reach (bucket at 60°)	4 ft 1 inch	4 ft 7 inches
Transport Overhang	4 ft 5 inches	4 ft 9 inches
Undercut	3 ft 0 inches	3 ft 0 inches
Stabilizer Spread (down position)	8 ft 9 inches	8 ft 9 inches
Stabilizer Spread (up position)	4 ft 7 inches	4 ft 7 inches
Bucket Cylinder Digging Force	4023 lbs	4668 lbs
Bucket Cylinder Digging Force (in "power dig" position)	4319 lbs	4853 lbs
Dipperstick Cylinder Digging Force	2445 lbs	3261 lbs
Craning Force (boom lift ability)	800 lbs	1000 lbs
Angle of departure (subframe mounted)	18°	18°
Shipping Weight (less bucket)	1445 lbs	1610 lbs
Hydraulic Volume Requirements	8 GPM	8 GPM
Hydraulic Pressure Requirements	2400 PSI	2400 PSI
Reinforced Buckets (regular duty & commercial grade buckets)	Yes	Yes
Buckets	12 to 24 inch Buckets Both Regular Duty and Commercial Grade, 36 inch Regular Duty Only	
Replaceable Bucket Tooth Tips (regular duty & commercial grade buckets)	Yes	Yes
Options	PTO Pump/Reservoir Kit, Power Beyond Kit, Closed Center Hydraulic Kit, Street Pad Kit, Flow Divider Kit	
Warranty	1 year limited warranty	
FEATURES	Available in major tractor colors	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE