



WIDE-AREA WALK-BEHIND COMMERCIAL MOWERS

- G 1236
- G 1332
- G 1548
- H 1536
- H 1748
- H 1952

POWER, PERFORMANCE AND INNOVATION FOR BETTER RESULTS ANYWHERE.

Like all Cub Cadet Commercial equipment, these walk-behind mowers are designed to deliver a better experience and better results. And that starts with features that mean business, like reinforced 7-gauge steel skirts and fully welded one-piece engine platforms and cutting decks. And with the Command Cut System,[™] your customers will get a premium, quality cut — every time.

INNOVATIVE FEATURES FOR AN INCREDIBLE EXPERIENCE. THAT'S THE **CUB CADET ADVANTAGE.**



SEVERAL MODELS AVAILABLE

Walk-behind mowers are available with 32", 36", 48" and 52" Command Cut System[™] cutting decks. You can also choose from gear-drive or hydrostatic-drive models. You're sure to get the mower that's right for you — and ready to work.



DUAL-LEVER CONTROLS

Clean, premium cuts are well within reach thanks to innovative pistol-grip controls that make it easier to follow the contours of the land. Hydrostatic models provide simple on-the-go tracking adjustments.



TACKLE TOUGH TERRAIN

Patented Vari-Touch foot controls let you adjust drive-belt tension on the go from 8 to 24 lbs., which gives you better traction, control and handling in wet, steep terrain.

FEATURES

GEAR- OR HYDROSTATIC-
DRIVE SYSTEMS

12.5, 13, 15, 17 OR 19 HP*
KAWASAKI® OR BRIGGS
& STRATTON® ENGINES

DUAL-LEVER CONTROLS

FULLY WELDED
ONE-PIECE DECK

HEAVY-DUTY
BELT GUARDS

BAGGER, SULKY
AND MULCH KIT
ATTACHMENTS

2-YEAR LIMITED
COMMERCIAL
WARRANTY, NO HOUR
LIMITATIONS[†]

[†]See specifications for warranty information.
*as rated by engine manufacturer

LOCATE A DEALER AT
CUBCADET.COM

YOUR INDEPENDENT DEALER CAN ANSWER ALL YOUR QUESTIONS
ABOUT THE MANY BENEFITS OF OWNING A CUB CADET.

cubcadetcommercial.com

Gear-Drive Models

ENGINE	G 1236	G 1332	G 1548
Engine type	12.5 HP* Briggs & Stratton® IC single cylinder OHV	13 HP* Kawasaki® V-Twin OHV	15 HP* Kawasaki® V-Twin OHV
Engine start	Recoil		
Engine lubrication	Splash lube	Full pressure w/spin-on oil filter	Full pressure w/spin-on oil filter
Fuel capacity	5-gallon tank		
TRANSMISSION			
Transmission	5-speed Peerless®	5-speed Peerless® with Vari-Touch traction control	5-speed Peerless® with Vari-Touch traction control
Ground speed (max.)	6 mph		
Controls	Light-touch pistol grip		
Handle	1-1/4" outer diameter		
Brakes	Band on drum		
TIRES			
Front tires	9" x 3.5" - 4", no flat		
Front bearings	Bronze bushing, greasable		
Rear tires	13" x 6.5" - 6"		
Rear bearings	Ball bearing, greasable		
MOWING DECK			
Deck PTO	Manual		
Deck size	36"	32"	48"
Deck style	Fixed fabricated		
Deck construction	10-gauge		
Deck drive	Belt drive Kevlar®		
Deck blades	2	2	3
Cutting height adjustment	2" - 4"		
Blade spindle	Tapered-roller spindle bearing		
DIMENSIONS			
Weight (approx.)	440 lbs.	403 lbs.	480 lbs.
WARRANTY†			
2-year limited commercial, no hour limitations			

Hydrostatic-Drive Models

ENGINE	H 1536	H 1748	H 1952
Engine type	15 HP* Kawasaki® V-Twin OHV	17 HP* Kawasaki® V-Twin OHV	19 HP* Kawasaki® V-Twin OHV
Engine start	Recoil	Electric	Electric
Engine lubrication	Full pressure w/spin-on oil filter		
Fuel capacity	5-gallon tank		
TRANSMISSION			
Transmission	Dual Hydro-Gear™ 10cc pumps and Parker® wheel motors		
Ground speed (max.)	7 mph		
Controls	Dual hydro pistol grip		
Handle	1-1/4" outer diameter		
Brakes	Internal drum		
TIRES			
Front tires	9" x 3.5" - 4", no flat		
Front bearings	Bronze bushing, greasable		
Rear tires	16" x 6.5" - 8"		
Rear bearings	In wheel motors		
MOWING DECK			
Deck PTO	Manual		
Deck size	36"	48"	52"
Deck style	Fixed fabricated		
Deck construction	10-gauge		
Deck drive	Belt drive Kevlar®		
Deck blades	2	3	3
Cutting height adjustment	2" - 4"		
Blade spindle	Tapered-roller spindle bearing		
DIMENSIONS			
Weight (approx.)	534 lbs.	550 lbs.	641 lbs.
WARRANTY†			
2-year limited commercial, no hour limitations			

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.