

TANK™

COMMERCIAL ZERO-TURN RIDERS

- TANK™ 48
- TANK™ 60
- TANK™ M48
- TANK™ M54
- TANK™ M60
- TANK™ M72

FEATURES

48", 54", 60" OR 72"
FABRICATED DECK SIZE

ENGINE OPTIONS
UP TO 37 HP*

PIVOTING FRONT AXLE
FOLLOWS CONTOURS
OF THE GROUND

CUTS UP TO 6.5
ACRES PER HOUR

FOLDABLE ROPS

FOOT PEDAL DECK LIFT

GROUND SPEEDS
UP TO 12 MPH

PATENTED SMARTJET™
DECK WASH SYSTEM

2-YEAR AND 3-YEAR
LIMITED COMMERCIAL
WARRANTY†

COMMERCIAL



WE MEAN BUSINESS.™



YOUR CLIENTS WON'T JUST BE SATISFIED, THEY'LL BE SPEECHLESS.


If you're looking for a top-of-the-line commercial mower, you've found it. The TANK™ is designed to do it all. The Select Cut System™ deck can cut all types of grass in all types of conditions. Plus, it produces a high-quality cut at faster ground speeds. It easily handles attachments without sacrificing productivity, and has features that keep the operator comfortable in rough conditions. And with true commercial-grade toughness, it's no wonder that the TANK™ is the mower that all other mowers aspire to be.

SEE HOW THESE FEATURES HELP YOU GET THE JOB DONE RIGHT AT CUBCADETCOMMERCIAL.COM.



PIVOTING FRONT AXLE

Follows the contours of the ground for superior cutting, providing a smoother, more uniform look and versatility for different terrain.



SELECT CUT SYSTEM™ DECK

The innovative sloped-nose deck features a configurable inner baffle, offset and adjustable leading edges, ball wheels and the SmartJet™ deck washing system.



FULL SUSPENSION SEAT

This premium seat allows the operator to customize suspension settings for weight and personal preference. It also features foldable armrests and tilt capability for lower back support.

WHAT THAT MEANS TO YOU

Professional results every time and everywhere you mow.

You get premium cuts even in the toughest grass-cutting conditions from a deck that's easy to service.

Maximum comfort and support reduce fatigue, and make it easier and more enjoyable to work a long day.

* as rated by engine manufacturer † See specifications for warranty information

YOUR INDEPENDENT DEALER CAN ANSWER ALL YOUR QUESTIONS
ABOUT THE MANY BENEFITS OF OWNING A CUB CADET.

LOCATE A DEALER AT
CUBCADETCOMMERCIAL.COM

TANK™ COMMERCIAL ZERO-TURN RIDERS

ENGINE	TANK™ 48	TANK™ 60	TANK™ M48-KW	TANK™ M54-KH
Engine type	23 HP* Kohler® V-Twin OHV	25 HP* Kohler® V-Twin OHV	23 HP* Kawasaki® V-Twin OHV	27 HP* Kohler® Command® V-Twin OHV
Engine displacement/orientation	674cc/vertical	725cc/vertical	675cc/vertical	725cc/vertical
Engine fuel	Gas			
Ignition	Transistor controlled			
Lubrication/filter	Full pressure w/spin-on oil filter			
Cooling system	Air			
Air cleaner	Heavy-duty remote-mounted replacement dual element			
Alternator	12V – 15 amp. regulated			
Fuel capacity	Twin 5-gallon tanks	Twin 5-gallon tanks	Twin 7-gallon tanks	Twin 7-gallon tanks
DRIVE SYSTEM				
Drive system	Kanzaki DUP-10 pumps & White® wheel motors	Kanzaki DUP-10 pumps & Parker wheel motors	Dual Hydro-Gear™ PK-12 pumps & Parker wheel motors	Dual Hydro-Gear™ PK-12 pumps & Parker wheel motors
Ground speed	Fwd: 10 mph/Rev: 5 mph	Fwd: 10 mph/Rev: 5 mph	Fwd: 12 mph/Rev: 5 mph	Fwd: 12 mph/Rev: 5 mph
Hydraulic fluid	Rimula® – 15W40			
Hydro fluid capacity	2.5 qt.	2.5 qt.	3 qt.	3 qt.
Hydraulic oil filter	Standard			
Controls	3-way adjustable lap bars			
Lap bar dampers	Standard			
Return to neutral	Standard			
Braking/parking brake	Dynamic/Knott drum			
STEERING				
Caster wheel pivot bearings	Sintered self-lubricating	Sintered self-lubricating	Timken® roller, greasable	Timken® roller, greasable
Front axle	Pivoting/fixed with lockout pins			
CHASSIS				
Frame	Fully welded steel 2" square tubing			
TIRES				
Front tire size	13" x 5" – 6" (smooth)	13" x 5" – 6" (smooth)	13" x 6.5" – 6" (smooth)	13" x 6.5" – 6" (smooth)
Rear tire size	23" x 9.5" – 12" (turf)	23" x 9.5" – 12" (turf)	23" x 9.5" – 12" (turf)	24" x 12" – 12" (turf)
DIMENSIONS				
Length x width x height	74" x 59" x 40.5"	78" x 71" x 40.5"	74.5" x 59" x 72"	78" x 65" x 72"
Wheelbase	44.5"	48.5"	44.5"	50.5"
Front track width	40"	44"	40.25"	45.5"
Rear track width	45.5"	46.5"	45.5"	52"
Weight (approx.)	995 lbs.	1,035 lbs.	1,080 lbs.	1,100 lbs.
MOWING DECK				
Deck size/type	48" sloped-nose design	60" sloped-nose design	48" Select Cut System™	54" Select Cut System™
Deck style/system	Floating			
Deck blades	3-blade			
Deck construction	10-gauge fabricated with 7-gauge reinforcements	10-gauge fabricated with 7-gauge reinforcements	10-gauge fabricated with 7- and 10-gauge reinforcements	10-gauge fabricated with 7- and 10-gauge reinforcements
Deck wash	Patented SmartJet™ high-pressure deck washing system			
Deck lift	Foot lever, spring assisted	Foot lever, spring assisted	Dual pedal, spring assisted	Dual pedal, spring assisted
Deck height adjustment	1" – 5" (in .25" increments)			
Blade spindle construction	Cast-aluminum			
Deck PTO	Electronic fingertip engagement			
Front anti-scalping wheels/nose roller	2, greasable/1 nose roller	2, greasable/1 nose roller	4 standard, greasable	4 standard, greasable
Rear anti-scalping rollers/striper	Full width, adjustable			
ADDITIONAL SPECIFICATIONS				
ROPS	Standard, foldable			
Monitor/hour meter	Standard, electronic			
Seat type	High-back, lever adjustable suspension		High-back suspension seat, foldable, fully adjustable with armrests	
Cup holder	Standard			
Storage pouch	Standard			
Rear bumper and hitch	Heavy-duty rear bumper w/bolt-on hitch standard			
WARRANTY*				
	2-year limited commercial	2-year limited commercial	3-year limited commercial	3-year limited commercial

ENGINE	TANK™ M60-KH	TANK™ M60-KW	TANK™ M72-KW
Engine type	27 HP* Kohler® Command® V-Twin OHV	31 HP* Kawasaki® V-Twin OHV	37 HP* Kawasaki® V-Twin OHV
Engine displacement/orientation	725cc/vertical	852cc/vertical	999cc/vertical
Engine fuel	Gas		
Ignition	Transistor controlled		
Lubrication/filter	Full pressure w/spin-on oil filter		
Cooling system	Air		
Air cleaner	Heavy-duty remote-mounted replacement dual element		
Alternator	12V - 15 amp. regulated		
Fuel capacity	Twin 7-gallon tanks		
DRIVE SYSTEM			
Drive system	Dual Hydro-Gear™ PK-12 pumps & Parker wheel motors		
Ground speed	Fwd: 12 mph/Rev: 5 mph		
Hydraulic fluid with remote cooling system	Rimula® - 15W40		
Hydro fluid capacity	3 qt.		
Hydraulic oil filter	Standard		
Controls	3-way adjustable lap bars		
Lap bar dampers	Standard		
Return to neutral	Standard		
Braking/parking brake	Dynamic/Knott drum		
STEERING			
Caster wheel pivot bearings	Timken® roller, greasable		
Front axle	Pivoting/fixed with lockout pins		
CHASSIS			
Frame	Fully welded steel 2" square tubing		
TIRES			
Front tire size	13" x 6.5" - 6" (smooth)		
Rear tire size	24" x 12" - 12" (turf)		
DIMENSIONS			
Length x width x height	78" x 71" x 72"	78" x 71" x 72"	81" x 83" x 72"
Wheelbase	50.5"	50.5"	53.5"
Front track width	45.5"	45.5"	51"
Rear track width	58"		
Weight (approx.)	1,150 lbs.	1,150 lbs.	1,380 lbs.
MOWING DECK			
Deck size/type	60" Select Cut System™	60" Select Cut System™	72" Select Cut System™
Deck style/system	Floating		
Deck blades	3-blade		
Deck construction	10-gauge fabricated with 7- and 10-gauge reinforcements	10-gauge fabricated with 7- and 10-gauge reinforcements	9-gauge fabricated with 7- and 10-gauge reinforcements
Deck wash	Patented SmartJet™ high-pressure deck washing system		
Deck lift	Dual pedal, spring assisted		
Deck height adjustment	1" - 5" (in .25" increments)		
Blade spindle construction	Cast-aluminum		
Deck PTO	Electronic fingertip engagement		
Front anti-scalping wheels	4 standard, greasable		
Rear anti-scalping rollers/striper	Full width, adjustable	Full width, adjustable	Full width, adjustable/2 rear corner rollers
ADDITIONAL SPECIFICATIONS			
ROPS	Standard, foldable		
Monitor/hour meter	Standard, electronic		
Seat type	High-back suspension seat, foldable, fully adjustable with armrests		
Cup holder	Standard		
Storage pouch	Standard		
Rear bumper and hitch	Heavy-duty rear bumper w/bolt-on hitch standard		
WARRANTY*			
3-year limited commercial			



ATTACHMENTS

Depending on the time of year or your geographic location, being productive can be a matter of having the right accessories. So whether it's challenging terrain, needing to work past dusk, collecting leaves or even plowing snow, Cub Cadet Commercial accessories make your job easier — and a lot more enjoyable.



LIGHT KIT
Easy-to-install kit provides increased visibility and safety for early or late days.



MULCHING KIT
Mulching baffles install easily to control airflow and reliably re-cut clippings for superior mulching.



12-VOLT OUTLET
Adding electrical power to your TANK™ is simple and easy.



ULTRA-TRACTION TIRES
Deliver improved traction on hills, or in sandy or snowy conditions.



72" BLADE
The steel blade attaches for light dozer work and snow plowing, with skid shoes for height adjustment.



TRIPLE BAGGER
Large, 10-bushel, triple-bag grass collection system for a professional, well-groomed look.



SPREADER
Attaches to either front or rear of the TANK™ to spread salt, seed or fertilizer.



POWER ASSIST DUMP HOPPER
Easily transports and unloads grass clippings or leaves.



ELECTRIC LIFT CYLINDER
Useful all year long. It raises the deck or snow blade easily.

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

Commercial products are intended for professional use.

773-03951 Printed in U.S.A. 12/09 © 2010 Cub Cadet