

THE TANK™

COMMERCIAL ZERO-TURN MOWERS

- THE TANK™ M48
- THE TANK™ M54
- THE TANK™ M60
- THE TANK™ M72

FEATURES

ENGINE OPTIONS
UP TO 37 HP*

CUTS UP TO 6.5
ACRES PER HOUR

GROUND SPEEDS
UP TO 12 MPH

HEAVY-DUTY
REAR BUMPER

STANDARD HEAVY-DUTY
REMOTE-MOUNTED
AIR CLEANER

FOLDABLE ROPS

48", 54", 60" OR 72"
FABRICATED DECK SIZE

COMMERCIAL
MOWING
EQUIPMENT



WE MEAN BUSINESS.™




YOUR CLIENTS WON'T JUST BE SATISFIED, THEY'LL BE SPEECHLESS.

If you're looking for a top-of-the-line commercial mower, you've found it. THE TANK™ is designed to do it all. The Select Cut System™ deck can cut all types of grass in all types of conditions. Plus, it produces a high-quality cut at faster ground speeds. It easily handles attachments without sacrificing productivity, and has features that keep the operator comfortable in rough conditions. And with true commercial-grade toughness, it's no wonder that THE TANK™ is the mower that all other mowers aspire to be.

PIVOTING FRONT AXLE

Follows the contours of the ground for superior cutting, providing a smoother, more uniform look and versatility for different terrains.



FOOT PEDAL DECK LIFT

Quick-release operation allows for easy deck adjustment while mowing.

FULL SUSPENSION SEAT

The exclusive premium seat allows the operator to customize suspension settings for weight and personal preference to reduce fatigue. It also features collapsible, foldable arm rests and tilt capability for increased lower back support.

SELECT CUT SYSTEM™ DECK

This innovative deck design features a patented sloped-nose front skirt with an adjustable leading edge and a configurable inner baffle that allow you to cut any type of grass on any terrain. Plus, the deck is offset for efficient cutting and reduced trimming. Heavy-duty cast-iron trail links allow the deck to follow the terrain without scalping. The greasable cast-aluminum spindles deliver longevity and are easier to service. A patented SmartJet™ deck wash system™ makes it easy to keep the deck clean. The Select Cut System™ deck also features adjustable stripping rollers and vented cast-iron pulleys for longer belt life.



*as rated by engine manufacturer

THE TANK™ COMMERCIAL ZERO-TURN MOWERS

ENGINE	M48-KW	M48-KH	M54-KH	M54-KW
Engine type	23 HP* Kawasaki® V-Twin OHV	25 HP* Kohler® Command® V-Twin OHV	27 HP* Kohler® Command® V-Twin OHV	25 HP* Kawasaki® V-Twin OHV
Engine displacement/orientation	675cc/vertical	725cc/vertical	725cc/vertical	675cc/vertical
Engine fuel	Gas			
Ignition	Transistor controlled			
Lubrication/filter	Full pressure w/spin-on oil filter			
Cooling system	Air			
Air cleaner	Heavy-duty remote-mounted replacement dual element			
Alternator	12V - 15 amp. regulated			
Fuel capacity	Twin 7-gallon tanks			
DRIVE SYSTEM				
Drive system	Dual Hydro-Gear™ BDP-12 pumps & White® wheel motors			
Ground speed	Fwd: 12 mph/Rev: 5 mph			
Hydraulic fluid	Rimula — 15W40			
Hydro fluid capacity	3 qt.			
Hydraulic oil filter	Standard			
Controls	3-way adjustable lap bars			
Lap bar dampers	Standard			
Return to neutral	Standard			
Braking/parking brake	Dynamic/Knott drum			
STEERING				
Caster wheel pivot bearings	Timken® roller, greasable			
Front axle	Pivoting/fixed			
CHASSIS				
Frame	Fully welded steel 2" square tubing			
TIRES				
Front tire size	13" x 6.5" - 6" (smooth)			
Rear tire size	23" x 9.5" - 12" (turf)	23" x 9.5" - 12" (turf)	24" x 12" - 12" (turf)	24" x 12" - 12" (turf)
DIMENSIONS				
Length x width x height	74.5" x 59" x 72"	74.5" x 59" x 72"	78" x 65" x 72"	78" x 65" x 72"
Wheelbase	44.5"	44.5"	48"	48"
Front track width	40.25"	40.25"	39"	39"
Rear track width	47"	47"	51"	51"
Weight (approx.)	1,080 lbs.	1,080 lbs.	1,150 lbs.	1,150 lbs.
MOWER DECK				
Deck size/type	48" Select Cut System™	48" Select Cut System™	54" Select Cut System™	54" Select Cut System™
Deck style/system	Floating			
Deck blades	3-blade			
Deck construction	10-gauge fabricated with twin 7- and 10-gauge reinforcements			
Deck wash	Patented SmartJet™ high-pressure deck washing system			
Deck lift	Foot pedal, spring assisted			
Deck height adjustment	1" - 5" (in .25" increments)			
Blade spindle construction	Cast-aluminum			
Deck PTO	Electronic fingertip engagement			
Anti-scalping wheels	4 standard, greasable			
Rear anti-scalping rollers/striper	Full width, adjustable			
ADDITIONAL SPECIFICATIONS				
ROPS	Standard, foldable			
Monitor/hour meter	Standard			
Seat type	High-back, foldable			
Cup holder	Standard			
Storage pouch	Standard			
Rear hitch	Standard			
WARRANTY†				
	3-year limited commercial			

ENGINE	M60-KH	M60-KW	M72-KW
Engine type	27 HP* or 30 HP* Kohler® Command® V-Twin OHV	31 HP* Kawasaki® V-Twin OHV	37 HP* Kawasaki® V-Twin OHV
Engine displacement/orientation	725cc or 747cc/vertical	852cc/vertical	999cc/vertical
Engine fuel	Gas		
Ignition	Transistor controlled		
Lubrication/filter	Full pressure w/spin-on oil filter		
Cooling system	Air		
Air cleaner	Heavy-duty remote-mounted replacement dual element		
Alternator	12V-15 amp. regulated		
Fuel capacity	Twin 7-gallon tanks		
DRIVE SYSTEM			
Drive system	Dual Hydro-Gear™ BDP-12 pumps & White® wheel motors		
Ground speed	Fwd: 12 mph, Rev: 5 mph		
Hydraulic fluid with remote cooling system	Rimula – 15W40		
Hydro fluid capacity	3 qt.		
Hydraulic oil filter	Standard		
Controls	3-way adjustable lap bars		
Lap bar dampers	Standard		
Return to neutral	Standard		
Braking/parking brake	Dynamic/Knott drum		
STEERING			
Caster wheel pivot bearings	Timken® roller, greasable		
Front axle	Pivoting/fixed		
CHASSIS			
Frame	Gas		
TIRES			
Front tire size	13" x 6.5" – 6" (smooth)		
Rear tire size	24" x 12" – 12" (turf)		
DIMENSIONS			
Length x width x height	78" x 71" x 72"	78" x 71" x 72"	81" x 83" x 72"
Wheelbase	48"	48"	51"
Front track width	39"	39"	44"
Rear track width	57"		
Weight (approx.)	1,150 lbs.	1,150 lbs.	1,380 lbs.
MOWER DECK			
Deck size/type	60" Select Cut System™	60" Select Cut System™	72" Select Cut System™
Deck style/system	Floating		
Deck blades	3-blade		
Deck construction	10-gauge fabricated with twin 7- and 10-gauge reinforcements	10-gauge fabricated with twin 7- and 10-gauge reinforcements	9-gauge fabricated with twin 7- and 10-gauge reinforcements
Deck wash	Patented SmartJet™ high-pressure deck washing system		
Deck lift	Foot pedal, spring assisted		
Deck height adjustment	1" – 5" (in .25" increments)		
Blade spindle construction	Cast-aluminum		
Deck PTO	Electronic fingertip engagement		
Anti-scalping wheels	6 standard, greasable		
Rear anti-scalping rollers/striper	Full width, adjustable		
ADDITIONAL SPECIFICATIONS			
ROPS	Standard, foldable		
Monitor/hour meter	Standard		
Seat type	High-back, foldable		
Cup holder	Standard		
Storage pouch	Standard		
Rear hitch	Standard		
WARRANTY*			
	3-year limited commercial		



ATTACHMENTS

Depending on the time of year or your geographic location, being productive can be a matter of having the right accessories. So whether it's challenging terrain, needing to work past dusk, collecting leaves or even plowing snow, we have the accessories that can help you get your jobs done.



LIGHT KIT
Easy-to-install kit, provides increased visibility and safety for early or late days.



MULCHING KIT
Mulching baffles install easily to control airflow and reliably re-cut clippings for superior mulching.



12 VOLT OUTLET
Adding electrical power to your TANK™ is simple and easy.



ULTRA-TRACTION TIRES
Deliver improved traction on hills, or in sandy or snowy conditions.



72" BLADE
The steel blade attaches for light dozer work and snow plowing, with skid shoes for height adjustment.



TRIPLE BAGGER
Large, 10-bushel, triple-bag grass collection system for a professional, well-groomed look.



SPREADER
Attaches to either front or rear of THE TANK™ to spread salt, seed or fertilizer.



POWER ASSIST DUMP HOPPER
Easily transports and unloads grass clippings or leaves.



ELECTRIC LIFT CYLINDER
Useful all year long. It raises the deck or snow blade easily.