

Cub Cadet[®]



WE PUT MORE IN IT SO YOU CAN SPEND MORE TIME OFF IT.

Our Z-Force[®] Zero-Turn Riders deliver more power and performance, so you can get your work done faster and easier. The zero turning radius means you'll spend less time cutting and more time doing the things you like to do. In addition to saving you time, it offers a very comfortable ride with features like front caster wheels, pivoting front axle and high-back seat with gel suspension.

INNOVATIVE FEATURES FOR AN INCREDIBLE EXPERIENCE. THAT'S THE **CUB CADET ADVANTAGE.**



EASIER TO OPERATE

Foot-pedal deck height adjustment makes it easier to select and set preferred mowing height without stopping or leaving your seat.



SMOOTHER CUT

Pivoting front axle and floating deck follow the contours of the ground for superior cutting, providing a smoother, more manicured look to the lawn.



STRONGER ENGINES

Professional-grade Kohler[®] Courage[®] V-Twin engine features hardened crankshaft bearings and large capacity filters.

Z-FORCE[®]

**HEAVY-DUTY
ZERO-TURN RIDERS**

Z-FORCE[®] 48

Z-FORCE[®] 54

FEATURES

48" AND 54"
TRIPLE-BLADE
FABRICATED DECKS

WEIGHT 722 LBS. TO
740 LBS.

DUAL HYDRO-GEAR[™]
ZT-2800[™] TRANSMISSION

4.25-GALLON FUEL TANK

ANTI-SCALPING WHEELS

ADJUSTABLE SEAT WITH
GEL SUSPENSION

PIVOTING FRONT AXLE

FULLY WELDED STEEL
FRAME

ARM RESTS ON
ALL MODELS

SMARTJET[™] DECK WASH

3-YEAR/180-HR LIMITED
WARRANTY[†]

[†]See specifications for warranty information.

LOCATE A DEALER AT
CUBCADET.COM

YOUR INDEPENDENT DEALER CAN ANSWER ALL YOUR QUESTIONS
ABOUT THE MANY BENEFITS OF OWNING A CUB CADET.

cubcadet.com

ENGINE	Z-FORCE® 48	Z-FORCE® 54
Engine type	22 HP* Kohler® Courage® V-Twin* OHV	24 HP* Kohler® Courage® PRO V-Twin OHV
Engine displacement	725cc	
Engine orientation	Vertical	
Engine fuel	Gas	
Ignition	Transistor controlled	
Lubrication/filter	Full pressure w/spin-on oil filter	
Cooling system	Air	
Air cleaner	Replaceable/dual element	
Alternator/battery	12V-15 amp. regulated/275 cca	
Wiring	Automotive-style	
Fuel capacity/pod	Single 4.25-gallon tank/single storage pod	
DRIVE SYSTEM		
Transmission	Dual Hydro-Gear™ ZT-2800™ w/oil reservoir and filter	
Ground speed	Fwd: 8 mph, rev: 3.5 mph	
Hydraulic fluid	Rotella® Triple Plus 15W40	
Hydraulic fluid capacity	5.0 qt. (2.25 qt. per side including filter) including expansion tank	
Hydraulic oil filter	Standard	
Return to neutral	Standard	
Braking/parking brake	Mechanical lever	
STEERING		
Controls	3-way adjustable lap bars	
Lap bar dampers	Standard	
Caster wheel pivot bearings	Composite bushing	
Front axle	Pivoting, steel	
CHASSIS		
Frame	Fully welded steel 1.5" x 2.0" tubular section	
TIRES		
Front tire size	13" x 5" - 6" (rib)	
Rear tire size	20" x 8" - 10" (turf)	20" x 10" - 10" (turf)
DIMENSIONS		
Length	70"	
Wheelbase	43"	
Weight (approx.)	722 lbs.	740 lbs.
MOWER & DECK DESIGN		
Safety	Operator presence	
Deck size	48"	54"
Deck blades	Triple	
Deck construction	11-gauge fabricated deck, w/7-gauge reinforced top plate	
Deck style/system	Floating	
Deck drive	Belt driven, Kevlar®	
Deck wash	Patented SmartJet™ high-pressure deck washing system	
Deck lift	Foot-pedal, spring assisted	
Deck height adjustment	1.0" - 4.0" (in. 25" increments)	
Blade spindle construction	Cast aluminum with tapered roller bearings	
Greasable spindle bearings	Standard	
Blade length	17"	19"
Blade brake clutch	Ogura GT-1	
Front anti-scalping roller	Adjustable nose roller and 2 greasable anti-scalp wheels	
Rear anti-scalping rollers/striper	4 striping	
Deck PTO	Electronic fingertip engagement	
ADDITIONAL SPECIFICATIONS		
Monitor/hour meter	Standard	
Seat type/arm rest	High-back w/arm rests and gel suspension	
Cup holder	Standard - in storage pool	
Rear hitch	Optional	
Front platform design	Extruded steel	
WARRANTY*		
	3-year/180-hr limited warranty	

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.